



ЛИЦЕНЦИРАНА  
КОМПАНИЈА ЗА  
ТЕХНИЧКО  
ОБЕЗБЕДУВАЊЕ

МАКСИПРИНТ

CERTIFIED

**alhua**  
TECHNOLOGY

DISTRIBUTOR

**alhua**  
TECHNOLOGY

Максипринт Компјутери ЛТД ДОО  
Бул. Туристичка бр.4, Охрид  
Охридска банка Жиро сметка:  
530000100483931

Контакт: 046-262 500 / 070-249 724 / 070-212 929  
e-mail: prodazba@maksiprint.com.mk



## HDCVI 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-T1A21 – 2.8mm</b> <b>2MP HDCVI IR Eyeball Camera</b> Max. 30 fps@1080p; CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens Max. IR length 20 m, Smart IR; 12 VDC	<b>1.700ден</b>
	<b>DAHUA HAC-T2A21 – 2.8mm</b> <b>2MP HDCVI Fixed-focal Eyeball Camera</b> Max. 30 fps@1080p; Smart IR Illumination; 20 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	<b>1.750ден</b>
	<b>DAHUA HAC-HDW1200T-Z-A</b> <b>2MP HDCVI IR Eyeball Camera</b> Max 30fps@1080P; HD and SD output switchable; Built-in mic; 2.7-12mm motorized lens; Max. IR length 60m, Smart IR; IP67, DC12V	<b>4.400ден</b>
	<b>DAHUA HUM1220G-B - 2.8mm</b> <b>2MP HDCVI Bullet Camera</b> Max 30fps@1080P, 2.8mm fixed lens,DC12V; HD and SD output switchable;	<b>1.750ден</b>
	<b>DAHUA HAC-HUM3200A</b> <b>2MP IR HDCVI Fixed-focal Cube Camera</b> Max 30 fps@1080p; 10 m illumination distance (940nm IR No IR Exposure); Super Adapt; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC;	<b>2.850ден</b>
	<b>DAHUA HAC-B1A21 – 3.6mm</b> <b>2MP HDCVI IR Bullet Camera</b> Max. 30 fps@1080p; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed lens; Max. IR length 20 m, Smart IR; IP67,12 VDC;	<b>1.700ден</b>
	<b>DAHUA HAC-B2A21</b> <b>2MP HDCVI Fixed-focal Bullet Camera</b> Max. 30 fps@1080p; Smart IR Illumination; 20 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	<b>1.750ден</b>
	<b>DAHUA HAC-HFW1200T-BLACK – 2.8mm</b> <b>2MP HDCVI IR Bullet Camera</b> Max 30fps@1080P; HD and SD output switchable; 2.8mm fixed lens; Max. IR length 30m, Smart IR; IP67, DC12V	<b>1.900ден</b>
	<b>DAHUA HAC-HFW1231TM-I8-A – 3.6mm</b> <b>2MP Starlight HDCVI IR Bullet Camera</b> Max 30 fps@1080p; Starlight, 130 dB true WDR, 3D NR; 3.6 mm fixed lens; Super Adapt; Built-in mic; Max. IR length 80 m, Smart IR; IP67, DC 12 V;	<b>2.200ден</b>
	<b>DAHUA LC1220T-TH - IoT Series - 2.8mm</b> <b>2MP HDCVI Temperature &amp; Humidity Camera</b> Max 30fps@1080P, 2.8mm fixed lens, Max. IR length 20m, Detection range: - 40°C~60°C, 10-95% RH, Smart IR, IP67, DC12V	<b>2.400ден</b>

## HDCVI 2MP Smart-Dual Light Camera



МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1200TLM-IL-A</b> <b>2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera</b> Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	<b>2.500ден</b>
	<b>DAHUA HAC-HFW1200CM-IL-A</b> <b>2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	<b>2.500ден</b>
	<b>DAHUA HAC-HDW1200CLQ-IL-A – 2.8mm</b> <b>2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera</b> Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; 12 VDC.	<b>1.800ден</b>
	<b>DAHUA HAC-HFW1200CL-IL-A – 2.8mm</b> <b>2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC.	<b>1.900ден</b>
	<b>DAHUA HAC-HFW1200TLM-IL-A - 2.8mm</b> <b>2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max. 30 fps@1080p; 3D NR; Smart Dual Light; 40m illumination distance; Super Adapt; Built-in mic; 2.8mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12VDC	<b>2.100ден</b>

## HDCVI 2MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1209TLQ-A-LED - 2.8mm</b> <b>2MP Full-color HDCVI Quick-to-install Eyeball Camera</b> 24/7 color imaging; 20 m illumination distance; Max. 30 fps@1080p; Built-in mic; CVI/CVBS/AHD/TVI switchable; IP67, 12V±30% DC;	<b>2.500ден</b>
	<b>DAHUA HAC-HFW1209C-LED - 2.8mm</b> <b>2MP Full-color HDCVI Bullet Camera</b> 24/7 color imaging; 20m illumination distance; Max. 30 fps@1080p; CVI/CVBS/AHD/TVI switchable; IP67, 12V±30% DC;	<b>2.000ден</b>
	<b>DAHUA HAC-HDW1239T-A-LED 2.8mm with Audio</b> <b>2MP Full-color HDCVI Eyeball Camera</b> 24/7 color imaging, Max. 30 fps@1080p; 40 m illumination distance; Super Adapt, 130 dB true WDR, 3D NR; CVI/CVBS/AHD/TVI switchable; IP67, DC 12 V;	<b>2.850ден</b>
	<b>DAHUA HAC-HFW1239TLM-A-LED - 3.6mm</b> <b>2MP Full-color Starlight HDCVI Eyeball Camera</b> Full-color starlight; 40m LED distance; Max. 30fps@1080P; CVI/CVBS/AHD/TVI switchable; IP67 12V±30% DC;	<b>2.850ден</b>






## HDCVI 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HFW1500C - 3.6mm 5MP Starlight HDCVI IR Bullet Camera</b> Max 25 fps@5MP; CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 30 m, Smart IR; IP67, 12V DC;	<b>2.700ден</b>
	<b>DAHUA HAC-HFW1500TH-I8 - 3.6mm 5MP Starlight HDCVI IR Bullet Camera</b> Max 25fps@5MP; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed lens; Max. IR length 80 m, Smart IR; IP67, 12V DC;	<b>3.550ден</b>
	<b>DAHUA HAC-EW2501 5MP HDCVI IR-Fisheye Camera</b> 1/2.8" 5Megapixel progressive scan CMOS; Panoramic fisheye lens; Max. 20fps@5MP; Built-in Mic; 120dbtrue WDR, Starlight, 2D&3D NR; Max. IR length 10m,Smart IR;DC12V	<b>9.999ден</b>
	<b>UTC Controller PFM820</b> Support different formats (HDCVI/AHD/HDTV/TVI/CVBS) switch, which ito satisfy the requirements of different storage device environments for clients;	<b>900ден</b>

## HDCVI 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1500CLQ-IL-A 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera</b> Max 25 fps@5MP (16:9 video output); Smart Dual Light; 20m illumination distance; Super Adapt; Built-in MIC; CVI/CVBS/AHD/TVI switchable; IP67,12 VDC	<b>2.450ден</b>
	<b>DAHUA HAC-HFW1500CL-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max 25 fps@5MP; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	<b>2.450ден</b>
	<b>DAHUA HAC-HFW1500TLM-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	<b>2.600ден</b>
	<b>DAHUA HAC-PT1500A-IL-A - 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal PT Camera</b> Max. 25 fps@5MP; Smart Dual Light; Smart Area Lighting; Pan & Tilt; 40 m illumination distance; Super Adapt; Built-in Mic; 2.8mm fixed lens; IP66, 12 VDC.	<b>4.450ден</b>

## HDCVI 5MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1509TLQ-LED - 3.6mm 5MP Full-color HDCVI Quick-to-install Eyeball Camera</b> Max 25 fps@5MP (16:9 video output); 120dB true WDR, 3D NR;24/7 color image;20 m illumination distance; CVI/CVBS/AHD/TVI switchable;IP67, 12 V DC;	<b>3.600ден</b>
	<b>HAC-HFW1509C-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera</b> Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance 2.8 mm fixed lens; IP67, 12V DC	<b>3.600ден</b>
	<b>HAC-HFW1509C-A-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera</b> Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance; Built-in mic; 2.8 mm fixed lens; IP67, 12V DC	<b>3.650ден</b>
	<b>DAHUA HAC-HFW1509T-A-LED - 3.6mm with Audio 5MP Full-color HDCVI Bullet Camera</b> Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance;Built-in mic (-A); 3.6 mm lens; IP67, 12 V DC	<b>3.700ден</b>
	<b>DAHUA HAC-HFW1509TLM-A-LED - 3.6mm with Audio 5MP Full-color HDCVI Bullet Camera</b> Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 40 m illumination distance; Built-in mic (-A); 3.6 mm fixed lens; IP67, 12 V DC;	<b>3.900ден</b>

## HDCVI 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1801T-IL-A - 2.8mm 4K Smart Dual Light HDCVI Fixed-focal Eyeball Camera</b> Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 2.8 mm fixed lens; IP67, 12 VDC;	<b>4.300ден</b>
	<b>DAHUA HAC-HFW1801TLM-IL-A - 3.6mm 4K Smart Dual Light HDCVI Fixed-focal Bullet Camera</b> Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	<b>4.300ден</b>

## HDCVI 8MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HAC-HDW1809T-A-LED - 2.8mm 4K Full-Color HDCVI Eyeball Camera</b> Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging 40 m illumination distance; Super Adapt; Built-in MIC(-A); IP67, 12 VDC.	<b>5.550ден</b>
	<b>DAHUA HAC-HFW1809TLM-A-LED - 3.6mm 4K Full-Color HDCVI Bullet Camera</b> Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging; 40 m illumination distance; Super Adapt; Built-in MIC(-A); 3.6 mm fixed lens; IP67, 12 VDC;	<b>ден</b>








## HDCVI 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HDW1800TL-A - 2.8mm</b> <b>4K Real-time HDCVI IR Eyeball Camera</b> Max. 4K resolution, real-time video transmission, Built-in mic (-A), Max. IR length 30m CVI/CVBS/AHD/TVI switchable, Smart IR, IP67, 12V±30%DC	<b>3.700ден</b>
	<b>DAHUA HAC-HFW1800TL-A - 3.6mm</b> <b>4K Real-time HDCVI IR Bullet Camera</b> ax. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	<b>4.000ден</b>
	<b>DAHUA HAC-HFW1801TL-A - 3.6mm</b> <b>4K Real-time HDCVI IR Bullet Camera</b> 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	<b>4.200ден</b>
	<b>DAHUA HAC-HFW1800TH-I8 - 3.6mm</b> <b>4K Real-time HDCVI IR Bullet Camera</b> Max. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	<b>4.500ден</b>
	<b>DAHUA HAC-HFW1801TH-I8 - 3.6mm</b> <b>4K Starlight HDCVI Fixed IR Bullet Camera</b> Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC.	<b>4.700ден</b>
	<b>DAHUA HFW1801R-Z-IRE6 with Audio 2.7-13.5mm</b> <b>4K 8MP HDCVI IR Bullet Camera</b> 120dB true WDR, 3D NR Max. 4K resolution, CVI/CVBS/AHD/TVI switchable, Auto focus, Motorized lens, Max. IR length 60m, smart IR, IP67, 12V ±30% DC	<b>7.500ден</b>
	<b>DAHUA HAC-HFW2802TU-A - 3.6mm</b> <b>4K Starlight HDCVI Fixed-focal Bullet Camera</b> Max. 15 fps@4K; Starlight, 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	<b>7.500ден</b>

## HDCVI Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA SD49225-HC -LA</b> <b>2MP 25x Starlight IR PTZ HDCVI Camera</b></p> <p>1/2.8" 2Megapixel STARVIS™ CMOS, Powerful 25x optical zoom, Starlight technology, Max. 25/30fps@1080P, 25/30/50/60fps@720P, 120dB true WDR, 3D DNR, IR distance up to 100m, IP66</p>	<b>24.000ден</b>
	<p><b>DAHUA NKB1000-E</b> <b>Network Keyboard</b></p>	<b>17.000ден</b>







## Specialized Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA IPC-HFW7442H-ZFR</b> <b>4MP IR Bullet WizMind Network Camera</b></p> <p>Max outputs 4MP (2688 × 1520) @50 fps/60 fps; 12V DC power output; 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition;</p>	
	<p><b>DAHUA TPC-BF5421-T</b> <b>Thermal Network Hybrid Bullet Camera</b></p> <p>Vanadium oxide uncooled focal plane detector; Built-in white light and speaker; Features temperature measurement; Micro SD memory, IP67, PoE, ePoE</p>	
	<p><b>DAHUA JQ-D70Z</b> <b>Thermometric Blackbody</b></p>	
	<p><b>DAHUA ITC413-PW4D</b> <b>Series Dahua Access ANPR Camera</b></p> <p>High-performance CMOS image sensor and processor that supports continuously extracting metadata 24/7; Easily adapts to scenarios through its motorized vari-focal lens; Adopts intelligent deep learning algorithms and supports recognition of unlicensed vehicles and the type, brand and color of vehicles;</p>	<b>37.800ден</b>

## Digital Video Recorder Up to 2MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA XVR1B04-I</b> <b>4 Channel Penta-brid 1080N/720p Cooper 1U WizSense</b> H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth	<b>3.600ден</b>
	<b>DAHUA XVR1B08-I</b> <b>8 Channel Penta-brid 1080N/720p Cooper 1U WizSense</b> H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth;	<b>4.600ден</b>
	<b>DAHUA XVR1B16-I</b> <b>16 Channel Penta-brid 1080N/720p Compact 1U WizSense</b> H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth;	<b>9.200ден</b>

## Digital Video Recorder Up to 6MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA XVR5104HS-I3</b> <b>4 Channel Penta-brid 5M-N/1080p Compact 1U WizSense</b> Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 6 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition;	<b>6.500ден</b>
	<b>DAHUA XVR5104HS-I3(1TB)</b> <b>4CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense</b> Comes with an internal 1TB SSD, and can record videos for about 22 days. 4-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 1-channel face recognition for analog channels which supports face comparison.	<b>9.300ден</b>
	<b>DAHUA XVR5108HS-I3</b> <b>8 Channel Penta-brid 5M-N/1080p Compact 1U WizSense</b> H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 12 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 8 channels video stream SMD Plus;	<b>9.000ден</b>
	<b>DAHUA XVR5108HS-I3(1TB)</b> <b>8CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense</b> Comes with an internal 1TB SSD, and can record videos for about 11 days. 8-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 4-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI.	<b>12.000ден</b>
 	<b>DAHUA XVR5116HS-I3 – WizSense</b> <b>16 Channel Penta-brid 5M-N/1080P Compact Digital Video Recorder</b> H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus; IoT & POS functionalities	<b>15.500ден</b>



	<p><b>DAHUA XVR5232AN-I3</b> <b>32 Channels Penta-brid WizSense Digital Video Recorder</b> H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; IoT &amp; POS functionalities.</p>	<p><b>33.000ден</b></p>
<p><b>Digital Video Recorder Up to 8MP</b></p>		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA XVR5104HS-4KL-I3</b> <b>4 Channel Penta-brid 5MP Compact 1U WizSense</b> Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 8 channels IP camera inputs, each channel up to 8MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition</p>	<p><b>9.500ден</b></p>
	<p><b>DAHUA XVR5108HS-4KL-I3 - WizSense</b> <b>8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder</b> H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;</p>	<p><b>15.000ден</b></p>
	<p><b>DAHUA XVR7108H-4K-I3</b> <b>8 Channels Penta-brid 4K Mini WizSense Digital Video Recorder</b> H.265+/H.265 dual-stream video compression. Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; IoT &amp; POS functionalities.</p>	<p><b>22.000ден</b></p>
	<p><b>DAHUA XVR5116H-4KL-I3</b> <b>16 Channels Penta-brid 4K-N/5MP Mini 1U WizSense</b> H.265+/H.265 dual-stream video compression; · Supports Full-channel AI-Coding; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT &amp; POS functionalities;</p>	<p><b>27.500ден</b></p>
	<p><b>DAHUA XVR5216A-4KL-I3</b> <b>16 Channels Penta-brid 4K-N/5MP 1U WizSense</b> H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT &amp; POS functionalities;</p>	<p><b>30.000ден</b></p>
	<p><b>DAHUA XVR7216A-4KL-X – Pro Series</b> <b>16 Channel Penta-brid 4K 1U Digital Video Recorder</b> H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Supports 16/32 channels of IPC access, each channel up to 8MP input; Max 64/128Mbps Incoming Bandwidth;</p>	<p><b>33.000ден</b></p>
	<p><b>DAHUA XVR7216AN-4K-I3</b> <b>16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder</b> H.265+/H.265 dual-stream video compression; Supports 16-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP ; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Up to 16 channels video stream SMD plus; IoT &amp; POS functionalities</p>	<p><b>40.000ден</b></p>
	<p><b>DAHUA XVR5232AN-4KL-I3</b> <b>32 Channels Penta-brid 4K-N/5MP WizSense Digital Video Recorder.</b> H.265+/H.265 dual-stream video compression.; Supports 32-channel AI-Coding.; Supports HDCVI/AHD/TVI/CVBS/IP video inputs.; Max 32 channels IP camera inputs, each channel up to 8MP; IoT &amp; POS functionalities.</p>	<p><b>50.000ден</b></p>



## Hard Disk Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA HDD 1TB Seagate</b> 1000G/5900RPM/64M/ SATA 6Gb/s/ Dahua LOGO ST1000VX013SEAGATE , SURVELLIANCE 24x7 Operation	<b>3.800ден</b>
	<b>DAHUA HDD 2TB Seagate</b> 2000G/5900RPM/64M/ SATA 6Gb/s/ Dahua LOGO ST2000VX017SEAGATE , SURVELLIANCE 24x7 Operation	<b>4.800ден</b>
	<b>DAHUA HDD 4TB Seagate</b> 4000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST4000VX016SEAGATE SURVELLIANCE , 24x7 Operation	<b>6.500ден</b>
	<b>DAHUA HDD 6TB Seagate</b> 6000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST6000VX009SEAGATE SURVELLIANCE , 24x7 Operation	<b>9.800ден</b>
	<b>DAHUA HDD 8TB Seagate</b> 8000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST8000VX010SEAGATE SURVELLIANCE , 24x7 Operation	<b>14.000ден</b>


## Memory Card & USB Flash Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DHI-TF-C100/64GB microSD Memory Card</b>	<b>ден</b>
	<b>DHI-TF-C100/128GB microSD Memory Card</b>	<b>1.250ден</b>
	<b>DHI-TF-C100/256GB microSD Memory Card</b>	<b>2.350ден</b>
	<b>DHI-USB-P629-32-64GB USB Flash Drive</b>	<b>650ден</b>
	<b>DHI-USB-P629-32-128GB USB Flash Drive</b>	<b>1.000ден</b>
	<b>DHI-USB-P629-32-256GB USB Flash Drive</b>	<b>2.000ден</b>







## IPC Smart-Dual Light 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA IPC-HFW1239TL1-A-IL</b> <b>2MP Entry Smart Dual Light Fixed-focal Bullet Network Camera</b> 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Built-in IR LED and warm light, the max. IR illumination distance is 30 m and warm light distance is 30 m; Supports human detection; 12 VDC/PoE power supply;	<b>3.700ден</b>
	<b>Dahua IPC-HDW1239V-A-IL</b> <b>2MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera</b> 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920× 1080)@25/30 fps; Built-in IR LED and warm light, the max. IR illumination distance is 30m and warm light distance is 30 m;	<b>3.700ден</b>

## IPC Full-Color 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA IPC-HFW5249T-ASE-NI – Pro AI Series</b> <b>2MP Pro AI Full-color Fixed-focal Bullet Network Camera</b> 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs max. 2MP (1920 × 1080) @30 fps; H.265 codec, SMART H.264+/H.265; 12V DC/PoE power support; ePoE for remote transmission · IP67 protection	<b>7.000ден</b>


## IPC 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA SD1A203T-GN-W – IR-15m</b> <b>2MP 3x Starlight IR PTZ Wi-Fi Network Camera</b> 1/2.8" 2Megapixel STARVIS™ CMOS , Powerful 3x optical zoom, Starlight, WDR, Max. 5/30fps@1080P, IVS, Support Wi-Fi,, IP66	<b>7.500ден</b>
	<b>DAHUA IPC-HDBW1230E</b> <b>2MP IR Mini-Dome Network Camera</b> 1/2.7" 2Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding; 25/30fps@1080P(1920x1080); Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: 2.8mm fixed lens; Max IR LEDs length 30m; IP67, IK10, PoE	<b>4.200ден</b>
	<b>DAHUA SD22204UE-GN – Lite Series</b> <b>2MP 4x Starlight PTZ Network Camera</b> 1/2.8" STARVIS™ CMOS; Powerful 4x optical zoom; Day/Night(ICR), Ultra DNR; Max. 25/30fps@1080P; Max 100°/s pan speed · IVS Support PoE; IP66, IK10	<b>14.000ден</b>
	<b>DAHUA IPC-HFW2231TP-ZS-S2 – Lite Series</b> <b>2MP Lite IR Vari-focal Bullet Network Camera</b> 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs 2MP; H.265 codec, ultra-low bit rate; Built-in IR LED, max IR distance: 60m; Supports max. 256 GB Micro SD card; 12V DC/PoE ; IP67 ,IK10	<b>8.000ден</b>
	<b>DAHUA IPC-HFW4231T-ASE with Audio 3.6mm</b> <b>2MP WDR IR Mini Bullet Network Camera</b> 1/2.8" 2Megapixel progressive scan STARVISTM CMOS; H. 265&H.264 triple-stream encoding; 50/60fps@1080P(1920×1080), 60 Hz ;WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC;LEDs Length 60m; Micro SD Memory,IP67,IK10, PoE	<b>9.000ден</b>
	<b>DAHUA IPC-HFW5242E-ZE-MF – WizMind</b> <b>2MP IR Vari-focal Bullet WizMind Network Camera</b> 1/1.8" 2Megapixel progressive scan CMOS; ROI, SMART H.264+/H.265+, flexible coding; 50/60 fps@1080P (1920 × 1080); Day/Night (ICR), 3D DNR, AWB, BLC ; 2.7 mm–12.0 mm motorized; IR LEDs Length 50 m; Micro SD memory, IP67, IK10	<b>11.000ден</b>







## IPC 4MP Smart-Dual Light Camera


МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA IPC-HFW1439TL1P-A-IL – 2.8mm 4MP Entry Smart Dual Light Fixed-focal Bullet Network Camera</b> 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm lights, max. illumination distance: 30 m; ROI, SMART H.264+/H.265+	<b>4.800ден</b>

## IPC 4MP Camera



МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA IPC-HFW1431T-ZS-S4 4MP Entry IR Vari-focal Bullet Network Camera</b> 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 50 m; 12V DC/PoE power supply;	<b>8.500ден</b>

## IPC 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>IPC-HDW1530T-S6 - 2.8mm 5MP Entry IR Fixed-focal Eyeball Network Camera</b> 5MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 5MP (2880 × 1620) @20 fps and supports 2688 × 1520 @25/30 fps; Built-in MIC; 12 V DC/PoE power supply; IP67 protection.	<b>ден</b>
	<b>DAHUA IPC-HDBW1530E-S6 5MP Entry IR Fixed-focal Dome Network Camera</b> 5MP, 1/2.7" CMOS image sensor, low illuminance and high definition image; Outputs max. 5MP @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; H.265 codec, high compression rate, and low bit rate; IR distance is 30m;	<b>ден</b>
	<b>DAHUA IPC-HDBW2541E-S 5MP IR Fixed-focal Dome WizSense Network Camera</b> 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; 12 VDC/PoE power supply, easy for installation.	<b>7.700ден</b>
	<b>DAHUA IPC-HFW1530S-S6 5MP Entry IR Fixed-focal Bullet Network Camera</b> 5MP 1/2.7" CMOS image sensor, low luminance, and high definition image; · Outputs max. 5MP @20 fps and supports 2688 × 1520 @25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m.	<b>6.000ден</b>
	<b>DAHUA IPC-HFW2531S-S-S2 – Lite Series 3.6mm 5MP Lite IR Fixed-focal Bullet Network Camera</b> 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs 2688×1520@25/30 fps, and supports max. 5MP (2592×1944); Built-in IR LED, IR distance: 30 m; 12V DC/PoE power support ; IP67 protection grade	<b>7.200ден</b>
	<b>DAHUA IPC-HFW2541E-S 5MP IR Fixed-focal Bullet WizSense Network Camera</b> 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2592 × 1944) @20 fps, and supports 4 MP (2688 × 1520) @25/30 fps; Abnormality detection: Motion detection, video tampering, scene changing, audio detection, IP conflict, illegal access, and voltage detection	<b>8.500ден</b>

	<p><b>DAHUA HY-SAV849HA-E</b> <b>5MP IR AI-fire Smoke Sensing Network Camera</b> Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices</p>	<p><b>10.000ден</b></p>
---	---	-------------------------

## IPC 6MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA IPC-HDW1639T-A-IL</b> <b>6MP Smart Dual Light Fixed-focal Eyeball Network Camera</b> 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP@20 fps, and supports 2688 × 1520@25/30fps; Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;</p>	<p><b>5.000ден</b></p>
	<p><b>DAHUA IPC-HFW1639TC-A-IL</b> <b>6MP Smart Dual Light Fixed-focal Bullet Network Camera</b> 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6MP @20 fps, and supports 2688 × 1520@25/30 fps; H.265 codec, Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;</p>	<p><b>5.300ден</b></p>




## IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA IPC-HFW2849S-S-IL</b> <b>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m</p>	<p><b>10.200ден</b></p>
	<p><b>DAHUA IPC-HDW2849TM-S-IL</b> <b>8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;</p>	<p><b>10.500ден</b></p>
	<p><b>DAHUA IPC-HFW2849T-AS-IL</b> <b>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP @20 fps, and supports 2688×1520 @25/30 fps; Built-in warm light and IR LED, IR light distance is 60 m and max. warm light is 50 m;</p>	<p><b>12.000ден</b></p>







## IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA IPC-HDW2831T-AS-S2 2.8mm 8MP Lite IR Fixed-focal Eyeball Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec,; Built-in IR LED, max IR distance: 30 m; ROI, SMART H.264+/H.265+, flexible coding; 256 GB Micro SD card, built-in MIC; 12V DC/PoE ; IP67;	<b>9.500ден</b>
	<b>DAHUA HDBW2841R-ZAS 8MP IR Vari-focal Dome WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments;	<b>13.500ден</b>
	<b>DAHUA IPC-HDBW2841E-S 8MP IR Fixed-focal Dome WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m;	<b>10.000ден</b>
	<b>DAHUA IPC-HFW2831S-S-S2 8MP Lite IR Fixed-focal Bullet Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	<b>9.800ден</b>
	<b>IPC-HFW2831T-AS-S2 3.6mm 8MP Lite IR Fixed-focal Bullet Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	<b>11.500ден</b>
	<b>DAHUA IPC-HFW2841T-AS 8MP IR Fixed-focal Bullet WizSense Network Camera</b> Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps. Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	<b>10.500ден</b>
	<b>DAHUA IPC-HFW2841T-ZAS 8MP IR Vari-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	<b>12.900ден</b>
	<b>DAHUA IPC-HFW2831TP-ZS – Lite Series 8MP WDR IR Bullet Network Camera</b> 1/1.8" 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	<b>14.000ден</b>
	<b>DAHUA IPC-HFW3849T1-AS-PV-S3 8MP Smart Dual Illumination Active Deterrence Bullet Camera</b> 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 ml Alarm: 1 in, 1 out; audio: 1 in, 1 out;	<b>16.000ден</b>

## IPC Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA SD49225GB-HNR</b>  <b>2MP 25x Starlight IR Network PTZ Camera</b>                      1/2.8" STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max.25/30fps@2M; IR distance up to 100 m; Perimeter protection; Face detection;Quick Pick; SMD 4.0; IP66.</p>	<b>30.000ден</b>
	<p><b>DAHUA SD4A425DB-HNY</b>  <b>4MP 25x Starlight IR WizSense Network PTZ Camera</b>                      1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@4MP; IR distance up to 100m; Auto-tracking 1.0; Perimeter protection; Face detection; SMD 3.0; IP66.</p>	<b>32.000ден</b>
	<p><b>DAHUA SD5A445GB-HNR</b>  <b>4MP 45x Starlight IR Network PTZ Camera</b>                      1/2.8" 4Megapixel STARVIS™ CMOS. · 45x optical zoom. · Starlight technology. · Max. 25/30fps@4M. · IR distance up to 150 m. · Auto-tracking 3.0. · Perimeter protection. · Face detection. · SMD 4.0. · Quick Pick. · IP67, IK10.</p>	<b>60.000ден</b>
	<p><b>DAHUA SD49825GB-HNR</b>  <b>8MP 25x Starlight IR Network PTZ Camera</b>                      1/2.8" 8Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@8M; IR distance up to 100 m; Perimeter protection; Face detection; Quick Pick; SMD 4.0; IP66;</p>	<b>46.000ден</b>
	<p><b>DAHUA IPC-PFW8802-A180</b>  <b>4x2MP Multi-Sensor Panoramic IR Bullet Network Camera</b>                      Four 1/1.9" 2Megapixel progressive scan CMOS; H.265/H.264 triple-stream encoding; Support 180-degree panoramic view; Day/Night(ICR), 3DNR, AWB, AGC, BLC, WDR; Smart detection; Max. IR LEDs length 30m; Micro SD memory, IP67, IK10,PoE+</p>	<b>42.000ден</b>

## IPC 2MP/4MP Wi-Fi Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA H4A</b> <b>4MP Indoor Fixed-focal Wi-Fi Pan &amp; Tilt Network Camera</b> One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	<b>3.000ден</b>
	<b>DAHUA H4C</b> <b>4MP Indoor Fixed-focal Wi-Fi Pan &amp; Tilt Network Camera</b> One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	<b>3.000ден</b>
	<b>DAHUA IPC-HFW1230DS-SAW</b> <b>2MP IR Fixed-focal Wi-Fi Bullet Network Camera</b> 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Built-in IR LED; Supports antenna 2.4G Wi-Fi, up to 80m range in open area; 12 VDC power supply;	<b>5.000ден</b>
	<b>DAHUA IPC-HDW1230DT-SAW</b> <b>2MP IR Fixed-focal WiFi Bullet Network Camera</b> 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@25/30 fps; Built-in Mic; The antenna offers 2.4G Wi-Fi with a range of 120 m; Supports max. 256 G Micro SD card;	<b>5.000ден</b>
	<b>DAHUA IPC-HDW1430DT-STW</b> <b>4MP IR Fixed-focal WiFi Eyeball Network Camera</b> Outputs max. 4MP@20 fps, and max.supports 3MP@25 fps/30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Built-in dual-antenna 2.4G Wi-Fi that covers a range of up to 120m;	<b>5.800ден</b>
	<b>DAHUA IPC-HDBW1430DE-SW</b> <b>4MP IR Fixed-focal Wi-Fi Dome Network Camera</b> 4-MP 1/3" CMOS image sensor, low luminance, and high definition image.H.265 codec, high compression rate, ultra-low bit rate. · Built-in IR LEDSupports max. 256 G Micro SD card. · 12 VDC · IP67, IK10 protection	<b>6.800ден</b>



## IPC 4MP Wi-Fi Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA T4A</b> <b>4MP Fixed-focal Wi-Fi Full-Color Turret Network Camera</b> AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	<b>4.350ден</b>
	<b>DAHUA F4C-LED</b> <b>4MP Fixed-focal Wi-Fi Full-Color Bullet Network Camera</b> AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	<b>3.100ден</b>

## IPC 4MP/5MP Wi-Fi Smart-Dual Light Camera










МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA F4C-PV</b> <b>4MP Fixed-focal Wi-Fi Smart Dual-Light Bullet Network Camera</b> AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology; Built-in warm light and IR LED, and the max. illumination distance is 30 m.	<b>6.300ден</b>
	<b>DAHUA P5AE-PV</b> <b>5MP Wireless Smart Dual-Light Network PT Camera</b> Smart Dual Light; One Camera for 360° View; Sound and Light Alarm; AI Human Detection; AI Vehicle Detection; Two-way Talk; Auto Tracking; IP66 Protection;	<b>6.000ден</b>
	<b>DAHUA P5B-PV</b> <b>5MP Outdoor Fixed-focal Wi-Fi Pan &amp; Tilt Network Camera</b> 360° monitoring without blind spots; Sound and Light Alarm Provides instant alarms to deter intruders; AI Human Detection; AI Vehicle Detection; Auto Tracking; Fast pairing with Bluetooth; Seamless integration of speed and anti-interference; Two-way audio;	<b>6.000ден</b>




## Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA NVR2104HS-P-S3</b> <b>4 Channel Compact 1U 4PoE WizSense Network Video Recorder</b></p> <p>Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding; Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus</p>	<b>ден</b>
	<p><b>NVR4104HS-4KS2/L</b> <b>4 Channel Compact 1U 1HDD Network Video Recorder</b></p> <p>New 4.0 user interface, Security baseline Max. decoding capability; 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device; VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K;</p>	<b>8.000ден</b>
	<p><b>DAHUA NVR2108-S3</b> <b>8 Channel Smart 1U 1HDD Network Video Recorder</b></p> <p>Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps; Supports adaptive decoding; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;</p>	<b>6.550ден</b>
	<p><b>DAHUA NVR2108HS-4KS3</b> <b>8CH Compact 1U 1HDD Lite Network Video Recorder</b></p> <p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 6 × 1080p@30 fps; Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; AI by Camera supports perimeter protection and SMD Plus;</p>	<b>7.200ден</b>
	<p><b>DAHUA NVR2108HS-8P-4KS3</b> <b>8 Channel Compact 1U 1HDD 8PoE Network Video Recorder</b></p> <p>Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps; Supports adaptive decoding; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;</p>	<b>10.800ден</b>
	<p><b>DAHUA NVR4108HS-EI</b> <b>8CH Compact 1U 1HDD WizSense Network Video Recorder</b></p> <p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 80 Mbps; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map.</p>	<b>10.200ден</b>
	<p><b>DAHUA NVR4108HS-8P-EI</b> <b>8CH Compact 1U 8PoE 1HDD WizSense Network Video Recorder</b></p> <p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection;</p>	<b>16.200ден</b>
	<p><b>DAHUA NVR4108HS-8P-4KS3</b> <b>8 Channel Compact 1HDD 1U 8PoE Network Video Recorder</b></p> <p>H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance,</p>	<b>12.000ден</b>









	<p><b>DAHUA NVR4116HS-4KS3</b> <b>16CH Compact 1U 1HDD Lite Network Video Recorder</b> Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps; Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD.</p>	<p><b>11.000ден</b></p>
	<p><b>DAHUA NVR4116HS-EI</b> <b>16CH Compact 1U 1HDD WizSense Network Video Recorder</b> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;</p>	<p><b>11.500ден</b></p>
	<p><b>DAHUA NVR4216-4KS2/L</b> <b>16 Channel 1U 2HDDs Network Video Recorder</b> New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device</p>	<p><b>11.800ден</b></p>
	<p><b>DAHUA NVR4216-16P-4KS2/L</b> <b>16 Channel 1U 2HDDs Network Video Recorder</b> New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols;</p>	<p><b>21.000ден</b></p>
	<p><b>DAHUA NVR4216-16P-EI</b> <b>16CH 1U 16PoE 2HDDs WizSense Network Video Recorder</b> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;</p>	<p><b>25.000ден</b></p>
	<p><b>DAHUA NVR4232-4KS3</b> <b>32 Channel 1U Network Video Recorder</b> New 4.0 user interface, Security baseline 2.1; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD;</p>	<p><b>15.500ден</b></p>
	<p><b>DAHUA NVR4232-EI</b> <b>32CH 1U 2HDDs WizSense Network Video Recorder</b> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection and recognition, perimeter protection;</p>	<p><b>17.400ден</b></p>
	<p><b>DAHUA NVR5232-EI</b> <b>32 Channels 1U 2HDDs WizSense Network Video Recorder</b> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel; Support N+M cluster;</p>	<p><b>ден</b></p>
	<p><b>DAHUA NVR5464-EI</b> <b>64 Channels 1.5U 4HDDs WizSense Network Video Recorder</b> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel;</p>	<p><b>45.000ден</b></p>



## Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA ART-ARC3000H-03-GW2(868) – Alarm KIT</b> Supports 150 wireless peripherals Peripherals status display (signal strength, battery level, temperature, program version) Wired, Wi-Fi or GPRS network connection; Dual SIM and Single Standby, auto switching; Automatic network replenishment (ANR); Video linkage on App SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	<b>18.000ден</b>
	<b>DAHUA ARD1233-W2 - Wireless PIR detector</b> Pet immunity function; Auto temperature compensation; 3-level sensitivity adjustment; Low battery alarm; Anti-tampering; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability;	<b>2.900ден</b>
	<b>DAHUA ARD1731-W2 Wireless PIR-Camera</b> Maximum resolution 1600*1200; Based on the RF-HD image transmission technology, transmission of 6 HD images with resolution of 1600*1200 needs up to 10 seconds; One-week cloud cache for videos and images; Temperature monitoring;	<b>7.600ден</b>
	<b>DAHUA ARD323-W2 - Wireless door detector</b> Signal strength detection; Low battery alarm; Temperature measurement Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure	<b>2.500ден</b>
	<b>DAHUA ARA13-W2 - Wireless outdoor siren</b> IP65 rated; Outdoor product (-25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	<b>6.000ден</b>
	<b>DAHUA ARA12-W2 - Wireless siren</b> Signal strength detection; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure.	<b>3.500ден</b>
	<b>DAHUA ARA24-W2 Wireless keyfob</b> SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	<b>1.700ден</b>
	<b>DAHUA ARK30T-W2 - Wireless Keypad</b> Supports 3 shortcut alarms: Medical, fire, emergency; Arm/Disarm with password or IC card; Supports signal strength detection to select suitable installation sites; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication; Cloud update and automatic recovery from update failure.	<b>4.800ден</b>
	<b>DAHUA ARD821-W2 - Wireless Panic Button</b> Two-way RF communication; Provides multiple LED colors to indicate different statuses; Cloud update and automatic recovery from update failure; Offers accidental press prevention; Battery life up to 5 years if used twice a week; IP54 rated	<b>1.700ден</b>
	<b>DAHUA ARM310-W2 - Wireless input expander</b> Six types of alarm: intrusion, medical, fire, emergency, gas, and tamper; NC and NO are available for alarm inputs (NO by default); Signal strength detection; Low battery alarm; Temperature monitoring; Frequency hopping function and two-way communication technology ensure communication stability;	<b>2.000ден</b>
	<b>DAHUA ARD912-W2(868D) Wireless Water Leak Detector</b> Frequency hopping and two-way communication technology ensure that communication is stable; Displays the temperature of the surrounding environment and supports the overheating alarm; Sensitivity adjustment;	<b>3.500ден</b>






	<b>DAHUA ARA43-W2 - Alarm Repeater</b> Connects up to 32 peripherals; Two-way RF communication; LED indicator displays device status; Supports auto pairing, extending RF distance for your security system; Auto switches from dual antennas to reduce blind area; Battery backs device working for over 35 hours	<b>6.000ден</b>
	<b>DAHUA HY-SA21A-W2(868) Wireless Smoke Alarm</b> Split-spectrum sensor technology; Test and silence features in one single button; Loud sound output over 85 dB(A) at 3 meters; Low quiescent current consumption; Surface-mount device (SMD) circuit board design; Low battery warning signal	<b>4.500ден</b>
	<b>DAHUA HY-SAV849HA-E 5MP IR AI-fire Smoke Sensing Network Camera</b> Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices, and user can import custom voices; 2/2 Alarm in/out, 1/1 audio in/out;	<b>9.550ден</b>

## Professional Monitoring Dahua Monitor



МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА БЕЗ ДДВ
	<b>22" FHD Monitor DHI-LM22-B200S</b> Light and cost-effective plastic housing; Ultra-narrow bezel , elegant appearance, Metal base; 178°H/178°V extra-wide viewing angle for overall viewing performance; Anti-blue light design,eye-protective; Low energy consumption, long service life;	<b>5.450ден</b>
	<b>21.45" FHD Monitor DHI-LM22-H200</b> Suitable for continuous 24/7 operation; Ultra-thin body with metal housing; Micro bezel design, elegant appearance, ultra-light base; 178°H/178°V extra-wide viewing angle for overall viewing performance;	<b>9.000ден</b>
	<b>22" FHD Monitor DHI-LM22-L200</b> Light and cost-effective plastic housing · Support 7*24 operation · High fidelity digital processing for a brilliant and vivid video · Fast response time with no image blurring or ghosting · Low energy consumption, long service life	<b>6.500ден</b>
	<b>23.8" FHD Monitor DHI-LM24-B200S</b> Light and cost-effective plastic housing; Ultra-narrow bezel , elegant appearance, Metal base; 178°H/178°V extra-wide viewing angle for overall viewing performance; High fidelity digital processing for a brilliant and vivid video; Support multiple signal inputs such as HDMI, VGA;	<b>8.500ден</b>
	<b>27" FHD Monitor DHI-LM27-B200S</b> Light and cost-effective plastic housing; Ultra-narrow bezel , elegant appearance, Metal base; 178°H/178°V extra-wide viewing angle for overall viewing performance; Anti-blue light design,eye-protective; Low energy consumption, long service life;	<b>9.300ден</b>
	<b>27" Monitor DHI-LM27-C200</b> The 1920*1080 resolution produces clearer and more vivid pictures; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB. It meets the designer's demand of image texture; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB.	<b>9.900ден</b>
	<b>32" FHD Monitor DAHUA LM32-F200</b> Light and cost-effective plastic housing · suitable for continuous 24/7 operation · 178°H/178°V extra-wide viewing angle for overall viewing performance; · Built-in speakers; Physical button and infrared remote dual control mode	<b>14.500ден</b>
	<b>43" FHD Monitor DHI-LM43-F200</b> Light and cost-effective plastic housing; suitable for continuous 24/7 operation; 178°H/178°V extra-wide viewing angle for overall viewing performance; High fidelity digital processing for a brilliant and vivid video; 8ms fast response time	<b>20.150ден</b>

	<p><b>43" FHD Monitor DHL43-F600</b> Industrial level LCD panel, suitable for continuous 24/7 operation · Physical resolution of 1920×1080 · High fidelity digital processing for a brilliant and vivid video · 5ms fast response time for no motion blur, judder or ghosting</p>	<p><b>26.650ден</b></p>
	<p><b>Bracket for monitor DAHUA TV 42"-55"</b></p>	<p><b>850ден</b></p>

## IPC Wi-Fi 2MP Smart Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>M-WJ01 Tuya Smart 1080P 2.0MP Wifi Super Mini Camera</b> APP name:TuyaSmart; Standard Lens: 2.4mm; H.264 Real time; Support Monitor; Suport Android &amp; Iphone Mobile View; Night vision distance: 5-8M; 5V, 1A;Maximum support 64G TF card;Support ONVIF, can work with NVR</p>	<p><b>3.500ден</b></p>
	<p><b>VR 2MP IP Panoramic Fisheye PTZ camera</b> H.264 Compression,Dual Stream(0.1M-8Mbps); LED:4pcs <b>LED 30M</b>(With IR CUT), <b>Fisheye 1.44mm 185° Lens</b>; WIFI: 3DB Antenna,, Motion Dectction, Alert Action, CMS For PC; Audio: Built-in 45DB Microphone; Built-in 8 Assault 2-Watt Speakers; Built in Antenna; Without RJ45 Port; White Light LED</p>	<p><b>2.000ден</b></p>
	<p><b>IPW-THS-901 WiFi Smart PT Camera Indoor</b> Support 1080P/3MP/5MP Video Record/View; Built-in 4pcs Array IR Led; IR Distance More than 5~10 Meters; Simple installation; 360 degree panoramic picture; Two Way Audio(Built-in Mic, Louder speaker);H.265/H.264 HD High Profile image decoding;Pan Rotation:355°,TiltRotation:75°;</p>	<p><b>3.500ден</b></p>
	<p><b>2MP Camera TV 288ZD Wireless WiFi with AUTO TRACKING</b> Image sensor: GC1034 Video: Image sensor: 2MP/1080P Image coding standard: Smart H.264+, <b>Monitor image quality: 1280*720/640 * 360</b> private cloud WIFI Networking, AP hotspot added Extension: IR-CUT, TF Card: maximum support for 128GB TF CardWIFI: support. <b>Lens: 3.6mm.</b></p>	<p><b>2.300ден</b></p>
	<p><b>1080PDual CarCamera</b> Color: Black; Material: ABS; Display: 2 Inch IPS Screen; Camera: 1080P Front Camera + 480P Inside Camera + 480P Rear Camera; View Angle: 140° Front + 90° Inside + 90° Rear; Loop; Date Stamp: Support; Memory Card: Max. 128G(Not Included); Battery: Built-in 150mAh Lithium Battery; Current Frequency: 50/60Hz; Power: 5V, 1.5-2A;Photo Format: JPEG; File Format: MOV</p>	<p><b>3.200ден</b></p>


## Accessories

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DH-PFM906</b> <b>Integrated Mount Tester</b></p> <p>Supports IPC, HDCVI, AHD, HDTV, CVBS and SDI monitor video display; HDMI input and output; 12 VDC 2A and USB 5V 2A output; 7-in 1080p HD full-angle retina capacitive IPS touchscreen; TDR network cable test and cable tracker function; Optical power meter function</p>	
	<p><b>VB-B503 Balun 4K-8MP</b></p> <p>8MP , AHD , TVI , CVI , Analog 2MP 3MP 4MP 5MP 1080P HD-CVI TVI AHD Compatible with DaHua HD-CVI signal.HD-TVISignal,AHD Signal Pushin Terminal Block for UTP Cable. HD-CVI720P: <b>Max.:450M/ HDCVI1080P:</b></p>	<b>350ден</b>
	<p><b>10/100/1000Mbps Fiber optic single mode simplex media converter</b></p> <p>Standard-Definition Digital Video Optic Transmission System;Fiber: Over 1 fiber; Fiber type: SMF &amp; MMF; PAR</p>	<b>1.900ден</b>
	<p><b>Converter HDMI TO AV2</b></p>	<b>900ден</b>






## Ethernet Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA PFS3005-5ET-L</b> <b>5-Port Desktop Fast Ethernet Switch</b></p> <p>Compact design: Miniature size and light weight make it easy to deploy · Plug and play: No configuration required; Green technology: Adopts high quality environmentally friendly plastics; 7×24H: Stable performance</p>	<b>620ден</b>
	<p><b>DAHUA PFS3008-8ET-L</b> <b>8-Port Desktop Fast Ethernet Switch</b></p> <p>Compact design: Miniature size and light weight make it easy to deploy · Plug and play: No configuration required · Green technology: Adopts high quality environmentally friendly plastics · 7×24H:</p>	<b>950ден</b>

## Wireless Access Point

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA EAP5212-C</b> <b>AC12 Ceiling Mount Access Point</b></p> <p>Up to 1.2 Gbps wireless speed; Supports dual concurrent wireless networks; Offers seamless roaming; MU-MIMO technology delivers a fast wireless network that can be accessed by multiple devices at the same time;</p>	<b>5.200ден</b>

## Wireless Routers


МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA N3</b> <b>N300 Wireless Router</b></p> <p>The wireless speed reaches up to 300 Mbps for IEEE 802.11n, allowing smooth internet access; 1 × WAN port and 3 × LAN ports that expand network coverage; Two external antennas offer a wider signal coverage;</p>	<b>1.400ден</b>
	<p><b>DAHUA AC12</b> <b>AC1200 Wireless Router</b></p> <p>1.2 Gbps Wireless Speed(300 Mbps@2.4 GHz, 867 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac standard); Beamforming for better Coverage; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2); Guest Wi-Fi;</p>	<b>2.500ден</b>
	<p><b>DAHUA AX15M</b> <b>AX1500 Wireless Router</b></p> <p>6th Gen Wireless Technology; 1.5 Gbps Wireless speed (300 Mbps@2.4 GHz, 1201Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3); Guest Wi-Fi</p>	<b>3.000ден</b>
	<p><b>DAHUA AX30</b> <b>AX3000 Wireless Router</b></p> <p>6th Gen Wireless Technology; 3 Gbps Wireless speed (574 Mbps@2.4 GHz, 2402 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); 160 MHz channel width; Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3);</p>	<b>5.400ден</b>
	<p><b>DAHUA MAX18</b> <b>Mesh Wireless Route</b></p> <p>Offers wireless access and high bandwidth; 1 gigabit WAN port and 2 gigabit LAN ports; Easily switches between LAN and WAN; Supports accessing 1000 Mbps optical fiber broadband; Supports being managed through the WiLynk app</p>	<b>5.200ден</b>



## Unmanaged Desktop Switch



МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>PSE904-10/100 +2 port WAN</b> 4 port , 4 port 10/100+2port WAN 10/100 , switc with 4 port PoE , RJ45 x8 , 10/100Mbps Auto-Negotiation and AUTO MDIX Fast Ethernet RJ45Port , Bulit in 8 PoE Ports , Data transmission up to 100m , Total power :120 Watts	<b>ден</b>
	<b>PSE908-10/100/1000 +2 port WAN</b> 8 port , 8 port 10/100+2port WAN 10/100 , switc with 8 port PoE , RJ45 x8 , 10/100Mbps Auto-Negotiation and AUTO MDIX Fast Ethernet RJ45Port , Bulit in 8 PoE Ports , Data transmission up to 100m , Total power :120 Watts	<b>3.700ден</b>
	<b>DAHUA PFS3009-8ET1GT-96</b> <b>9-Port Unmanaged Desktop Switch with 8-Port PoE</b> Layer 2 commercial switch; MAC auto study and aging, MAC table size is 2K MDI/MDIX self-adaption; Adopts metal enclosure; Port 1 supports Hi-PoE 60W power supply; Wall-mount installation; Long distance PoE	<b>5.500ден</b>
	<b>DAHUA PFS3010-8ET-96</b> <b>10-Port Unmanaged Desktop Switch with 8 Port PoE</b> Intelligent PoE; BT 90W; 8-pin assignment PoE power supply; Long distance PoE; PoE watchdog; Wide working temperature	<b>5.550ден</b>
	<b>DAHUA PFS3211-8GT</b> <b>11-Port Unmanaged Desktop Switch</b> 11-Port Gigabit Switch (Unmanaged); MAC auto study and aging, MAC address list capacity is 4K; High protection grade, supports common mode 4KV, differential mode 2KV; Supports dual power backup	<b>5.300ден</b>
	<b>DAHUA S3218-16ET-135</b> <b>18-Port Unmanaged Desktop Switch with 16-Port</b> 16 × RJ-45 10/100 Mbps (PoE) ports, 2 × RJ-45 10/100/1000 Mbps ports and 2 × SFP 1000 Mbps ports; Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt; PoE watchdog real-time monitors camera statues and automatically reboots faulty network cameras; Up to 250m transmission distance	<b>10.500ден</b>
	<b>DAHUA S3024-24GT</b> <b>24-Port Unmanaged Gigabit Switch</b> 24 × RJ-45 10/100/1000 ports; The all-gigabit ports transmit data without lag; Features aggregation mode which aggregates uplink ports; Features isolation mode which isolates all the ports from each other;	<b>6.150ден</b>
	<b>DAHUA PFS3226-24ET-240</b> <b>26-Port Unmanaged Switch with 24-Port PoE</b> Intelligent PoE; PD Alive(PoE Watchdog); Long Distance PoE Transmission; Smooth Transmission; Wide Working Temperature: -10 to 55°C (14°F to 131°F)	<b>13.600ден</b>

## Managed Desktop Switch



МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA PFS4226-24ET-360</b> <b>24-port 100 Mbps + 2-port Gigabit Managed PoE Switch</b> Intelligent PoE; Red port supports 90W IEEE802.3bt; Web management with friendly interface and easy operation; 250 m long distance PoE transmission; PoE watchdog;	<b>22.950ден</b>
	<b>DAHUA S4228-24GT-360</b> <b>28-Port Managed Desktop Gigabit Switch with 24-Port PoE</b> Layer 2 network management PoE switch; Supports web, and network management software based on SNMP; Supports PoE power consumption management; Supports IEEE802.3af, IEEE802.3at; Supports PoE watchdog; Supports 250 m long-distance transmission mode.	<b>31.600ден</b>

## Power Supply and Adapter









МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DC12V2A Power Adapter DAHUA PFM300</b> Easy installation and wall mount, structural water-proof; Support -30 °C ~+70 °C wide-range temperature operation, and the full load efficiency of the power; supply can be up to 100% at these temperatures; With junction function for camera wiring or can place video balun with HDCVI/AHD/TVI/CVBS cameras;	<b>750ден</b>
	<b>DAHUA PFM344D-4CH - Switching Power Supply</b> The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	<b>1.100ден</b>
	<b>DAHUA PFM344D-8CH - Switching Power Supply</b> The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	<b>1.400ден</b>
	<b>POWER SUPPLY 5A / 12V DC for CCTV Camera BIG</b> Input voltage 165 – 250 V; DC power 60W; Miniature size, high power density; ;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection	<b>800ден</b>
	<b>POWER SUPPLY 10A / 12V DC for CCTV Camera BIG</b> Input voltage 165 – 250 V; DC power 120W; Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	<b>950ден</b>
	<b>POWER SUPPLY 15A / 12V DC for CCTV Camera BIG</b> Input voltage 165 – 250 V; DC power 180W; Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	<b>1.050ден</b>
	<b>POWER SUPPLY 20A / 12V DC for CCTV Camera BIG</b> Input voltage 165 – 250 V; DC power 240W; High Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	<b>1.200ден</b>
	<b>POWER SUPPLY 30A / 12V DC for CCTV Camera BIG</b> Input voltage 165 – 250 V; DC power 360W; Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	<b>2.000ден</b>
	<b>5C5A</b> 220V AC input, 3A - 5 channel, 12VDC output, input voltage 165 – 250 V	<b>1.600ден</b>
	<b>9C10A</b> 220V AC input, 5A - 9 channel, 12VDC output, input voltage 165 – 250 V	<b>2.200ден</b>
	<b>18CH20A</b> 220V AC input, 20A - 18 channel, 12VDC output, input voltage 165 – 250V	<b>3.100ден</b>
	<b>DC12V4A 5-ch - CCTV Distributed Power Box DAHUA PFM340-5CH</b> 5 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access. Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	<b>3.500ден</b>










	<b>DC12V5A 9-ch - CCTV Distributed Power Box DAHUA PFM341-9CH</b> 9 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	<b>4.400ден</b>
	<b>DAHUA PFM343-19CH - CCTV Distributed Power Supply Box</b> 19 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	<b>8.200ден</b>

## Uninterruptible Power Supply (UPS)

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA PFM350-360</b> <b>600VA/360W Line-interactive</b> Wide input voltage range: AC81~145V or AC140~290V, meet the requirements in different parts for electric network fluctuation; Boost and buck AVR for voltage stabilization; Off-mode charging, cold start function and full protection; Continuous power supply for preventing data loss; Compact size;	<b>6.200ден</b>
	<b>DAHUA PFM350-900</b> <b>1500VA/900W Line-interactive</b> Wide input voltage range: AC81~145V or AC140~290V, meet the requirements in different parts for electric network fluctuation; Boost and buck AVR for voltage stabilization; Off-mode charging, cold start function and full protection; Continuous power supply for preventing data loss; Compact size;	<b>9.999ден</b>

## Junction Box for CCTV Camera


МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>Plastic Flush</b> UNIVERSAL Junction Box for DOME CAMERA, Camera housing with bracket, PLASTIC	<b>120ден</b>
	<b>J-BOX01DS</b> UNIVERSAL Water-proof Junction Box for BULLET CAMERA OUTDORE, Camera housing with bracket, Material: Aluminum, Operating Temperature: -40°C ~60°C	<b>ден</b>
	<b>J-BOX04PL – Bracket Plastic</b>	<b>ден</b>
	<b>J-BOX05PL – Bracket Plastic</b>	<b>150ден</b>
	<b>J-BOX06PL – Bracket Plastic</b>	<b>180ден</b>
	<b>J-BOX07PL – Bracket Plastic</b>	<b>ден</b>
	<b>J-BOX08PL – Dome Bracket Plastic</b>	<b>300ден</b>
	<b>PFB204W</b>	<b>950ден</b>

	<b>PFA122</b> <b>Water-proof Junction Box</b>	<b>999ден</b>
	<b>DAHUA PFA130-E Water-proof Junction Box</b>	<b>800ден</b>
	<b>PFA13A</b> Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: $\phi 96.8\text{mm} \times 33.5\text{mm}$	<b>580ден</b>
	<b>PFA134-B</b> Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: $\phi 90\text{mm} \times 35\text{mm}$	<b>580ден</b>
	<b>PFA134</b> Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: $\phi 90\text{mm} \times 35\text{mm}$	<b>580ден</b>
	<b>PFA135</b> Water-proof Junction Box, Camera housing with bracket, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design,	<b>620ден</b>
	<b>PFA136</b> Water-proof Junction Box, Material: Aluminum, Product Dimension: $\phi 110\text{mm} \times 33.5\text{mm}$ Pipe Thread: Operating Temperature: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$	<b>580ден</b>
	<b>PFA137</b> <b>Junction Box</b> Material: aluminum	<b>580ден</b>
	<b>PFA151</b> Corner Mount Bracket; Material: SECC; Aesthetic design; Material SECC Dimension(WxHxD) $243\text{mm} \times 170\text{mm} \times 138\text{mm}$ ( $9.57'' \times 6.69'' \times 5.43''$ )	<b>1.240ден</b>

## Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА БЕЗ ДДВ
	<p><b>DAHUA ASA3213GL-MW</b> <b>Face Recognition Time &amp; Attendance</b></p> <p>4.3-inch LCD touch screen; resolution 480 × 272; With 2MP wide-angle dual lens, white LED illuminator, IR light; Support face, card and password attendance; Support 500 users, 500 face images, 500 cards, 150,000 records and work without network; Face-camera distance: 0.3 m–1.5 m; Face verification accuracy 99.5%;</p>	<b>13.000ден</b>
	<p><b>DAHUA ASI2212H-DW</b> <b>Access Standalone</b></p> <p>PC + ABS, suitable for indoor and outdoor use; 2.4" LCD screen with a resolution of 240 × 320; IP65 rated (silicone sealant is needed, see Quick Start Guide; Option to switch between reader and controller mode for added convenience; Card/remote/password/ fingerprint unlock and unlock through their combinations;</p>	<b>11.600ден</b>
	<p><b>DAHUA ASI2212H-W - Mifare</b> <b>Access Standalone</b></p> <p>PC + ABS, suitable for indoor and outdoor use; 2.4" LCD screen with a resolution of 240 × 320; IP65 rated (silicone sealant is needed, see Quick Start Guide; Option to switch between reader and controller mode for added convenience; Card/remote/password/ fingerprint unlock and unlock through their combinations;</p>	<b>11.600ден</b>
	<p><b>DAHUA ASI1201E-D</b> <b>Water-proof RFID Standalone</b></p> <p>Support 30,000 valid cards &amp; 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;</p>	<b>4.400ден</b>
	<p><b>DAHUA ASI1201E – Mifare</b> <b>Water-proof RFID Standalone</b></p> <p>Support 30,000 valid cards &amp; 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;</p>	<b>5.000ден</b>
	<p><b>DAHUA ASI1201A-D</b> <b>Standalone Reader</b></p> <p>Touch keyboard and LCD display; Support 30,000 valid cards &amp; 150,000 records; Support multiple cards(default IC card) (“-D” means ID EM card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;</p>	<b>5.500ден</b>




## Access Control – Slave

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA ASA1222G-D Time &amp; Attendance Terminal</b></p> <p>Supports Mifare card/ID card reading distance 1 cm-3 cm, card swiping response time; Fingerprint verification response time ≤0.5 s, fingerprint recognition time ≤1.5 s; Operating temperature: 0°C to +55°C, operating humidity: ≤93%; Supports three attendance modes: fixed, manual/auto and forced;</p>	<b>8.100ден</b>

## Access Control – Slave








МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DAHUA ASR1101A-D RFID Reader</b> Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) · 125KHz(EM-ID); Red and Green LEDs; Sensitive touch keypad with blue backlight; Watch dog function ensure device free from halting; Beep Buzzer and LED indicator;Surface mounted installation	<b>1.950ден</b>
	<b>ASR1102A-D(V2) Fingerprint RFID Reader</b> RS-485 protocol; Default IC (Mifare) card ("-D" means ID EM card); Support card, fingerprint; Up to 3000 fingerprints capacity; Blue backlight; Watch dog function ensure device free from halting; Beep and indicator; Surface mounted installation;	<b>2.900ден</b>
	<b>DAHUA ASR1200E-D Water-proof RFID Reader</b> Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	<b>1.250ден</b>
	<b>DAHUA ASR1201D-D Slim Water-proof RFID Reader</b> Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) 125KHz(EM-ID); Red and Blue LEDs; Watch dog function ensure device free from halting; Water-proof(Outdoor use); Surface/Flush mounted installation	<b>1.750ден</b>

## Controllers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DEE1010B Access Control Extension Module</b> Decent appearance; Easy connection; Access control function extension	<b>2.700ден</b>
	<b>DAHUA ASC2104B-T Four Door Slave Access Control Module</b> Support 20,000 valid cards & 30,000 records; Support multiple cards; Support card, password, fingerprint and combination; Only work with ASC2204-H with CAN bus;Wiegand or RS-485 interface to readers; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	<b>6.200ден</b>
	<b>Four Door Master Access Controller DAHUA ASC2204C-H</b>	<b>18.000ден</b>


## IPC Villa Door Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA VTO2111D-P-S2</b> <b>IP Villa Door Station</b></p> <p>High definition camera; WDR; Operating temperature -30°C–60°C; IP65; Supports auto IR illumination and D/N; Card/app remote/indoor monitor unlock; Supports two-way voice call; 10,000 cards; Tamper Alarm; Control two locks</p>	<p><b>7.300ден</b></p>
	<p><b>DAHUA VTO1301R-W</b> <b>Wi-Fi Villa Door Station</b></p> <p>Ultra slim design; PC and ABS material make it ideal for indoor and outdoor use. Offers two-way video call with indoor monitors; Video call through app; IR illumination and auto WDR; Wi-Fi connection; IP65 rated; H.264 and H.265.</p>	<p><b>6.500ден</b></p>
	<p><b>DAHUA VTO2211G-WP</b> <b>IP Villa Wi-Fi Door Station</b></p> <p>Tamper alarm; Standard PoE; Control two locks; Supports wireless network; Card unlock, app unlock, and indoor monitor unlock; Two-way audio and voice call through app; Card capacity: 10,000; Thin lightweight design;</p>	<p><b>8.500ден</b></p>
	<p><b>VTO6222E-P</b> <b>2-wire IP Apartment Door Station</b></p> <p>Highly durable and elegant, it is made of aluminum panel, and has a mechanical keypad. 2MP HD camera. Supports 5,000 users and 10,000 cards. Supports multiple unlock methods including password, IC card, and unlocks remotely. Provides 12 VDC, 600 mA power. IP65 rated. IK08 rated. Standard PoE power supply.</p>	<p><b>17.000ден</b></p>
	<p><b>DAHUA VTO6521H</b> <b>Apartment Door Station</b></p> <p>4.3 inch IPS display; screen resolution 800×480; 2MP CMOS; true WDR; Touch button; IP65; Operating temperature: -30°C to +60°C; Auto light illumination reduces light pollution; Multiple unlock modes: Password unlock, IC card unlock, and remote unlock; Support 20,000 users and 10,000 cards</p>	<p><b>18.000ден</b></p>
	<p><b>DAHUA VTO6521F</b> <b>Apartment Door Station</b></p> <p>4.3 inch IPS display; screen resolution 800×480; 2MP CMOS; true WDR; Aluminum anode surface; metal button; IP65, IK07; Operating temperature: -30°C to +60°C; Auto light illumination reduces light pollution; Multiple unlock modes: Password unlock, IC card unlock, and remote unlock; Support 20,000 users and 10,000 cards; Support full duplex; management platform, and voice call through APP; Support SIP server;</p>	<p><b>ден</b></p>
	<p><b>DAHUA VTO3311Q-WP</b> <b>Wi-Fi Villa Door Station</b></p> <p>Full metal casing design. Customizable Number of Buttons. Wi-Fi connection. 1/2.8" 2-MP HD CMOS camera. IR illumination and auto WDR. Supports two locks. Voice call and unlocking ;through app. IK08 and IP65 rated. H.264 and H.265. Unlock with IC card. PoE power supply. Included rain cover.</p>	<p><b>12.500ден</b></p>
	<p><b>VTH2421FB-P</b> <b>IP Indoor Monitor</b></p> <p>7" TFT Capacitive touch screen, 1024 x 600; IPC surveillance; Alarm integration; High performance; Embedded 8GB SD card; Support standard PoE</p>	<p><b>8.000ден</b></p>



	<p><b>DAHUA VTH1550CH IP Indoor Monitor</b> 7" TFT Capacitive touch screen; IPC surveillance; Alarm integration Micro SD card optional, max 32GB; Record &amp; Snapshot(SD card needed)</p>	<p><b>6.500ден</b></p>
	<p><b>DAHUA VTH2611L-WP Dahua Wi-Fi Indoor Monitor</b> 4.3" TFT capacitive touchscreen; Unlock the door; Set DND period; IPC surveillance; 4-channel alarm input and 1-channel alarm output; Supports standard PoE; Ethernet and Wi-Fi.</p>	<p><b>5.500ден</b></p>
	<p><b>DHI-VTH2621GW-P IP Indoor Monitor</b> 7" TFT capacitive touch screen, 1024 × 600; 6-channel alarm input and 1-channel alarm output; Standard PoE; Outdoor station and IPC monitor; H.265 and H.264 video coding; High performance &amp; cost-effective</p>	<p><b>6.000ден</b></p>
	<p><b>DAHUA VTH2621GW-WP IP Indoor Monitor</b> 7" TFT capacitive touch screen, 1024 × 600 · 6-channel alarm input and 1-channel alarm output; <b>Wi-Fi</b>; Standard PoE · Door station and IPC monitor ; H.265 and H.264 video decoding; High performance &amp; cost-effective</p>	<p><b>6.800ден</b></p>
	<p><b>DAHUA VTH2621G-WP IP &amp; Wi-Fi Indoor Monitor</b> 7" TFT capacitive touch screen, 1024 × 600; 6-channel alarm input and 1-channel alarm output; Wi-Fi; Standard PoE; Door station and IPC monitor; H.265 and H.264 video decoding; High performance &amp; cost-effective</p>	<p><b>6.800ден</b></p>
	<p><b>VTH5421EW-H Wi-Fi Digital Indoor Monitor with Handset</b> 7 inch LCD, 1024 (H)×600(V); 6 alarm input ports; 1 alarm output port; 1 12V DC power output port provides power for peripheral alarm devices and sensors; 16kbps audio stream; You can answer calls hands free;</p>	<p><b>9.300ден</b></p>
	<p><b>DAHUA VTH5321GW-W Android 7-inch digital indoor monitor</b> Android 8.1; More User-Friendly UI; Ethernet and Wi-Fi; 7" TFT Capacitive touch Screen,1024×600; Quick configuration for villa system;</p>	<p><b>10.500ден</b></p>










## IPC 2-wire Hybrid Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA KTX01 Video Intercom KIT</b> 2-wire Hybrid Villa Door Station; Aluminum alloy front panel; Auto IR illumination; Video messages can be left for unanswered calls. (SD card is required for VTH); Features nameplate and DWDR; Supports local lock and second lock; Offers anti-tampering alarm; IP65 and IK07 rated;</p>	<p><b>19.500ден</b></p>



## Analogue Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p><b>DAHUA KTA02 Video Intercom Kit</b> 7" TFT screen; Video intercom function: Unlock, voice call, video call, volume adjustment; System Capacity: 2 door stations + 3 indoor monitors; Multiple bell sound; Supports digital wide dynamic range (DWDR)</p>	<p><b>7.400ден</b></p>
	<p><b>DHI-KTA04 Video Intercom Kit</b> Video intercom function: Unlock, voice call, video call, volume adjustment and doorway monitoring · Multiple bell sounds · Support digital wide dynamic range (DWDR); Display 4.3" TFT</p>	<p><b>6.500ден</b></p>

## Wired Apartment Outdoor Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>DHI-VTO1210C-X</b> IP&Analog Apartment Outdoor Station; 1.3MP CMOS camera, H:75° 3" STN LCD screen, phonebook; Stainless steel panel, IP54,IK07 Night vision & Approaching induction; Video & Audio messaging Surface & Flush mounted	<b>18.500ден</b>
	<b>DHI-VTH1200DS</b> 4.3" Analog Indoor Monitor; 4.3" TFT LCD screen Color video & audio intercom; Alarm intergration Sufrace & Flush mounted	<b>2.800ден</b>
	<b>DHI-VTH2020A</b> 7" Analog Indoor Monitor; 7" TFT LCD screen Color video & audio intercom; Alarm intergration Surface mounted	<b>4.000ден</b>
	<b>DHI-VTNA1040B</b> 4ch Analog Distributor;4ch distributor 30 cascading;Used in Analog apartment systemDC24V, Max 20W	<b>2.200ден</b>
	<b>VTNS1060A</b> Network power supply for IP System; Decent appearance Protocol network power supply switch; Connect max 6 indoor monitors with the Cat 5e cable,	<b>1.200ден</b>
	<b>ADS-65LSI-19-1</b> DC 24V 2.5A Power Supply Input: 100-240V ~50/60Hz Required for the VTNA 1040B Switch	<b>2.050ден</b>
	<b>DH-PFM321D-EN</b> DC12V 1A Power Adapter _ Dahua brand, European standardInput 100~240V, 50/60Hz, 0.5A Output 12V (+7%, -3%) ---1A (2%)	<b>1.200ден</b>

## UTP Cable Cat5 & Cat6

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>PFM920I-5EUN – 305m UTP CAT5E Cable</b> 305m UTP CAT5E, Max.160m long distance PoE supply, 99.99% OFC (oxygen free copper) Excelent material, Environmentally friendly PVC	<b>27ден</b>
	<b>PFM920I-6UN-C – 305m UTP CAT6E Cable</b> 305 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor	<b>40ден</b>

## Cable

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<b>RG6 Coaxial</b> Braiding 80*0.12 +Bonded AL-foil+PVC 100m. White Color 100m/roll,	<b>20ден</b>
	<b>RG6 Coaxial so sajla</b> Braiding 80*0.12 +Bonded AL-foil+PVC 100m. White Color 100m/roll,	<b>22ден</b>
	<b>RG59 Coaxial CCS</b> Braiding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	<b>25ден</b>
	<b>RG59 Coaxial 100% COPPER</b> Braiding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	<b>35ден</b>
	<b>RG59+2x0.75 COMBO</b> Braiding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	<b>35ден</b>
	<b>RG59+2x0.75 COMBO so SAJLA</b> Braiding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	<b>35ден</b>
	<b>RG59+2x0.50 COMBO COPPER</b> Braiding 112 +Bonded AL-foil+PVC + 2x0.50mm power COPPER. White Color, 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	<b>45ден</b>
	<b>Power Cable PPL 2x0,75 CCA (for power supply)</b> 100m Black Color	<b>20ден</b>

	<b>FTP Cat5E - 24AWG</b> Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box Grey Color	<b>20ден</b>
	<b>FTP Cat5E - 24AWG so SAJLA</b> Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA Grey Color	<b>30ден</b>
	<b>FTP Cat5E - 24AWG so SAJLA COPPER</b> Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA Grey Color	<b>40ден</b>
	<b>FTP Cat5E 24AWG - 100% FULL COOPER</b> CU Network Cable CU (100% Copper), with aluminium foil , and transparent PET film , Conductor 0.51mm , Pass Fluke test on 100M - 305m Box Grey Color	<b>35ден</b>
	<b>FTP Cat6E 23AWG</b> Network Cable , with aluminium foil , and transparent PET film, Conductor 0.57mm - 305m Box Grey Color	<b>30ден</b>
	<b>FTP Cat6E 23AWG - 100% FULL COOPER</b> Network Cable CU (100% Copper) , with aluminium foil , and transparent PET film , Conductor 0.57mm - 305m Box Grey Color 18.6	<b>40ден</b>
	<b>ALARM CABLE</b> 6 x 0.22, shield 100m , EXTRA	<b>25ден</b>
	<b>ALARM CABLE COOPER</b> 6 x 0.22, shield 100m , COOPER EXTRA	<b>35ден</b>
	<b>SIGNAL CABLE</b> 2x0,75mm2+4x0,22mm 2, 4,8±0,3mm, white color for Dorephone	<b>35ден</b>
	<b>Estetski Kanali (Bela Boja na kanali)</b> 12x12 16x16 25x16 25x25 40x25 40x40 60x40	<b>METAR</b> 28 ден 34 ден 42 ден 55 ден 85 ден 120 ден 180 ден

Цените се малопродажни препорачани од DaHua Technology и истите важат за крајни корисници. Цените се со пресметан ДДВ 5% и 18% .

Гаранција на производите е 12 – 24 месеци.

МАКСИПРИНТ го задржува правото на промена на цените без претходна најава.