

# ЦЕНОВНИК



**FAAC**  
Simply automatic.

**GENIUS**



Максипринт Компјутери ЛТД ДОО  
Бул. Туристичка бр.4, Охрид  
Охридска банка Жиро сметка:  
530000100483931  
Контакт: 046-262 500 / 070-249 724  
070-212 929  
e-mail:  
prodazba@maksiprint.com.mk

## Parking Locks

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>Solar Parking Lock</b> Control Distance: 30–50 meters; Rise and Fall Time: Less than 3–5 seconds; Size: 460 × 460 × 100MM; Rising Height: 40CM; Drop Height: 8CM; Waterproof Grade: IP67; Weight: 6–7 KG;	<b>105€</b>
	<b>Battery Powered Parking Lock</b> Size: 450 × 400 × 80mm; Lifting Height: 400mm; Descent Height: 75mm; Running Time: ≤ 5 Seconds; Control Distance: ≥ 30 Meters; Product Weight: 7.5 KG; Supply Battery: Alkaline / Lithium Battery; Rated Voltage: DC 6V; Static Voltage: ≤ 0.8mA; Waterproof: IP68; Working Temperature: -40°C ± 70°C;	<b>75€</b>


## Barriers – Автоматика за паркинзи

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>Automatic barrier PB323 Kit With Rect. Telescopic 4+2 Arm</b> Voltage: 24V; Current: 6A; Insulation Class: F; Output Efficiency: 100W; Gate Operation Time: 0.8–5s; Operating Temperature Range: -40°C to +60°C (-40°F to +140°F) – below -20°C / -4°F requires a heating element; Humidity: ≤85%; Altitude: ≤1000m; Dimensions: 860mm (H) × 320mm (W) × 200mm (D);	<b>580€</b>
	<b>Automatic barrier PB301 Kit With Rect. Telescopic 4+2m Arm</b> Chassis Size: 320 × 245 × 985 mm; Color: Silver; Chassis Thickness: 1.5 mm; Open Time: 1 – 6 s (adjustable); Motor Power: 120W – 150W (optional); Working Power Supply: 220V; Operating Temperature: -40°C to +85°C; Remote Control Distance: ≥ 30 m;	<b>610€</b>
	<b>Automatic barrier PB302 Kit With Elliptic 6m Arm</b> Chassis Size: 355 × 255 × 1035 mm; Color: Silver; Chassis Thickness: 1.5 mm; Open Time: 1 – 6 s (adjustable); Motor Power: 120W – 150W (optional); Working Power Supply: 220V; Operating Temperature: -40°C to +85°C; Remote Control Distance: ≥ 30 m;	<b>880€</b>
	<b>Arm Rest</b>	<b>45€</b>
	<b>Elliptic Beam for barrier 6m with LED</b>	<b>95€</b>
	<b>Rectangle Beam for barrier 6m Telescopic 4+2</b>	<b>83€</b>
	<b>Photocells</b>	<b>25€</b>
	<b>Remote Control</b>	<b>12€</b>

## FAAC Barriers - БАРИЕРИ ЗА ПАРКИНЗИ

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>BARRIER 24V ELECTROMECHANICAL B614-104614</b> Power supply 220-240V ~ 50/60; Hz Electric motor 24V brushed; Max. power 165 W; Max. torque 300 Nm; Back-up batteries Yes (optional); Material Steel; Surface treatment Pre-hot dip galvanized, 20µm thick + polyester powder coated; Encoder Incremental, integrated in the motor; Deceleration type Electronic + mechanical; Beam type Rectangular and rounded; Ambient operating temperature -20°C to +55°C; Protection class IP55 (Electronic control unit) - IP44; Weight 40 Kg Use frequency Continuous use; Electronic equipment E614	<b>1057€</b>
	<b>Foundation plate for barrier B614</b>	<b>32€</b>
	<b>Single Channel Receiver GENIUS - 6100334</b> FAAC original GENIUS 433 RC . Workson 433 Mhz frequency and FAAC 433 Mhz transmitters manages ECHO'S GENIUS."	<b>38€</b>
	<b>Faac B614 Double Spring Fitting - 490186</b>	<b>15€</b>
	<b>Faac B614 Spring - 721209</b>	<b>25€</b>
	<b>Faac B614 Fixing bracket for Beam - 428342</b>	<b>55€</b>
	<b>Faac B614 Beam 5M - 428091</b>	<b>160€</b>
	<b>Faac B614 Integrated Flashing Lamp - 410032</b>	<b>65€</b>
	<b>Echo TX4 RC 433 MHz Remote Control Transmitter</b> This remote control of the gate GENIUS ECHO TX4 as a frequency of 433.92 MHz and have 4 button(s). It comes with an instruction and batteries. The Programming of the remote is easy and requires no special equipment	<b>24€</b>
	<b>Genius Vega WIRED Photocells</b> Self Aligning Photocells , range 20m, 24V DC 6100147	<b>40€</b>
	<b>Genius Vega WIRELESS Photocells</b> Power Supply 12-24 V- 12 – 24 Vdc; Absorbed current RX: 30 mA; Maximum range: 15m; Transmission of signal: automatic;	<b>56€</b>

## Genius Barriers - БАРИЕРИ ЗА ПАРКИНЗИ

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>SPIN 4C ENC - 230V AC BARRIER GATE</b> SPIN 4C ENC - AUTOMATIC BARRIER for motor vehicle Barrier body with incorporated control board LYNX 06 , and 433MHz Receiver with anthenna ,springs for SPIN 4 , Power supply 230V 50Hz , Working Temp -20°C - +55°C Integrated control board with separate opening and closing inputs Elektrical and mechanical limit-switches supplied standard Version 230V is supplied with the Encoder to ensure reversing of movement	<b>823€</b>
	<b>Foundation Plate with Accessories for SPIN Barrier</b>	<b>32€</b>
	<b>Single-channel receiver GENIUS - 6100334</b> FAAC original GENIUS 433 RC . Workson 433 Mhz frequency and FAAC 433 Mhz transmitters manages ECHO'S GENIUS."	<b>38€</b>
	<b>Genius SPRING For SPIN 4</b>	<b>29€</b>
	<b>Genius Light Assembly Kit - 3900184</b>	<b>50€</b>
	<b>Genius Light Connection Kit – 390992 - 390993</b>	<b>75€</b>
	<b>BEAM 3m FOR SPIN 4</b> Alluminium beam painted with white epoxy powders , complete with retro-reflecting stickers and rubber profile . Dimensions 90x25mm. Beam 4 meter . 58P1803	<b>132€</b>
	<b>BEAM 5m FOR SPIN 4</b> Alluminium beam painted with white epoxy powders , complete with retro-reflecting stickers. Dimensions 100x50mm. Beam 6 meter . 58P1805	<b>158€</b>
	<b>BEAM L6000 6m FOR SPIN 6</b> Alluminium beam painted with white epoxy powders , complete with retro-reflecting stickers. Dimensions 100x50mm. Beam 6 meter . 58P1805	<b>182€</b>
	<b>Echo TX4 RC 433 MHz Remote Control Transmitter</b> This remote control of the gate GENIUS ECHO TX4 as a frequency of 433.92 MHz and have 4 button(s). It comes with an instruction and batteries. The Programming of the remote is easy and requires no special equipment	<b>24€</b>
	<b>Genius Vega WIRED Photocells</b> Self Aligning Photocells , range 20m, 24V DC 6100147	<b>40€</b>
	<b>Genius Vega WIRELESS Photocells</b> Power Supply 12-24 V- 12 – 24 Vdc; Absorbed current RX: 30 mA; Maximum range: 15m; Transmission of signal: automatic;	<b>56€</b>

	<p><b>Genius intermittent flashing lamp Guard 230V AC 40W</b>  Guard is a new flashing designed to be installed in multiple configurations, allowing maximum flexibility of vertical/horizontal positioning, on pillars or walls. Available in various versions 230V. 6100052</p>	<b>65€</b>
	<p><b>M-ST-DC1</b>  WIFI Smart Door Opener Relay; APP name:TuyaSmart; Work with Amazon Alexa/Google Assistance/IFTTT; Work Voltage: DC7-32V; Wifi Frequency: 2.4GHz; Relay Load: 250V/10A; Work alone, not work with alarm panel together</p>	<b>45€</b>

## Bollard

МОДЕЛЬ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<p><b>FAAC J200 Bollard Series</b>  Diameter: 200mm; Cylinder Stroke: 600mm; Rise time: 5sec; Descent Time: 7sec; Suitable for residential applications, providing intelligent control, but preserving the aesthetic impact; Product design streamlined, configurable by selecting the desired installation accessories; Ease of transport, storage and installation, thanks to the weight and content of the product; Simplified maintenance; Hydraulic lock in high position with special release key; <b>Emergency release with pressostat; Led lights kit; Movement buzzer;</b></p>	<b>2200€</b>

## Sliding Gate Kits – Мотори за лизгачки врати

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>BLIZZARD 500 C ENC -230V SLIDE GATE KIT / 500kg</b> Irreversible electro-mechanical Gear motor for moving heavy sliding gates, with control board SPRINT382 and 433MHz Receiver with antenna, foundation plate for Blizzard , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Lock With Key Switc , Power supply 230V 50Hz , Working Temp -20°C - +55°C Sturdy inner kinematic mechanism Magnetic Limit Switches Electronic Control Board with	<b>375€</b>
	<b>BLIZZARD 900 C ENC -230V SLIDE GATE KIT / 900kg</b> Irreversible electro-mechanical Gear motor for moving heavy sliding gates, with control board SPRINT382 and 433MHz Receiver with antenna, foundation plate for Blizzard , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Lock With Key Switc , Power supply 230V 50Hz , Working Temp -20°C - +55°C Sturdy inner kinematic mechanism Magnetic Limit Switches Electronic Control Board with	<b>435€</b>
	<b>FALCON M14C -230V SLIDE GATE KIT / 1400kg</b> Irreversible electro-mechanical Gear motor for moving heavy sliding gates, with control board SPRINT382 and 433MHz Receiver with antenna, foundation plate for Blizzard , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Lock With Key Switc , Power supply 230V 50Hz , Working Temp -20°C - +55° Optional Encoder installation for obstacle detection Rotating Panel for easier programming	<b>667€</b>
	<b>FALCON M20C -230V SLIDE GATE KIT / 2000kg</b> Irreversible electro-mechanical Gear motor for moving heavy sliding gates, with foundation plate for Blizzard , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Lock With Key Switc , Power supply 230V 50Hz , Working Temp -20°C - +55° Optional Encoder installation for obstacle detection. Rotating Panel for easier programming	<b>710€</b>
	<b>Genius nylon gear rack 30x20</b> 1 meter – 6100344 + welding accessories for 1meter 30x20 6100345	<b>14.5€</b>
	<b>Genius galvanized iron gear rack 30x12</b> galvanized iron gear rack + welding accessories for 1meter 30x12 - 1 meter - JA146	<b>16€</b>

## Swing Gate Kits - МОТОРИ ЗА КРИЛНИ ПОРТИ

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>GENIUS G-BAT400 - 230V AC SWING GATE KIT 4 meter</b> Kit for gates with two Swing leaves , up to 4 meter of width ,complete with accessories , with control board BRAIN 17 / 230V and 433MHz Receiver with antenna ,Ecobox with Brand , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Power supply 230V 50Hz , Working Temp -20°C - +55°C Easy release through a user friendly lever . Opening and closing slow down available in both versions	<b>525€</b>
	<b>GENIUS MISTRAL 400 - 230V AC SWING GATE KIT 4 meter</b> Kit for gates with two Swing leaves , up to 4 meter of width ,complete with accessories , with control board BRAIN 17 / 230V and 433MHz Receiver with antenna ,Ecobox with Brand , 4 channel transmitter Echo TX4 , Pair IR Photocells Vega-Genius , Flashing Lamp , Power supply 230V 50Hz , Working Temp -20°C - +55°C Release through a user friendly accessory lever Opening and closing slow down available in both versions	<b>650€</b>

## Accessories

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
	<b>M-UHF5 Pro</b> Access Control Card Reader; Operating frequency: 860–960MHz; Dimensions: 180 × 180 × 60 mm; Interface: USB, Bluetooth, RS485, Wiegand; Material: Acrylic panel;	<b>440€</b>
	<b>M-DK001 UHF</b> QR Code Access Control Card Reader; Frequency: 125KHz / 13.56MHz; Dimensions: 86 × 86 × 7 mm; Output: Wiegand 26/34, RS232, USB; Material: ABS material, tempered glass panel;	<b>124€</b>
	<b>UHF CARD</b>	<b>3€</b>
	<b>UHF LABEL</b>	<b>3€</b>
	<b>Echo TX4 RC 433 MHz Remote Control Transmitter</b> This remote control of the gate GENIUS ECHO TX4 as a frequency of 433.92 MHz and have 4 button(s). It comes with an instruction and batteries. The Programming of the remote is easy and requires no special equipment.	<b>24€</b>
	<b>Single Channel Receiver GENIUS</b> Single-channel receiver plug FAAC original GENIUS 433 RC . Works on 433 Mhz frequency and FAAC 433 Mhz transmitters manages ECHO'S GENIUS."	<b>38€</b>
	<b>Genius Vega WIRED Photocells</b> Self Aligning Photocells , range 20m, 24V DC 6100147	<b>40€</b>
	<b>Genius Vega WIRELESS Photocells</b> Power Supply 12-24 V- 12 – 24 Vdc; Absorbed current RX: 30 mA; Maximum range: 15m; Transmission of signal: automatic;	<b>56€</b>
	<b>Genius intermittent flashing lamp Guard 230V AC 40W</b>	<b>65€</b>
	<b>Genius – Outdore key</b> Optated perated selector switc ,one contact in NA/NC exchange ,Anti Break - in	<b>23€</b>
	<b>M-ST-DC1</b> WIFI Smart Door Opener Relay; APP name:TuyaSmart; Work with Amazon Alexa/Google Assistance/IFTTT; Work Voltage: DC7-32V; Wifi Frequency: 2.4GHz; Relay Load: 250V/10A; Work alone, not work with alarm panel together	<b>45€</b>



**RTU5024 GSM Door Opener**

GSM Frequency, Quad-band 850/900/1800/1900MHz, Digital Output, NC/NO dry contact 3A/240VAC, DC Power supply 9~24VDC/2A , 12V input Max. 50mA/Average 25mA, SIM Card Supporting 3V SIM Card, Humidity range Relative humidity 90% , Backup battery 3.7V/900mAH, Exterior dimension 102mm\*D76mm\*H27mm

**65€**

**Цените се END USER и истите важат за крајни корисници.**

**Цените се претставени со пресметан ДДВ 18% .**

**Гаранција на производите е од 1-12 месеци.**

**МАКСИПРИНТ го задржува правото на промена на цените без претходна најава.**