



ЛИЦЕНЦИРАНА
КОМПАНИЈА ЗА
ТЕХНИЧКО
ОБЕЗБЕДУВАЊЕ

МАКСИПРИНТ

CERTIFIED

PARADOX












DISTRIBUTOR










P  **R**  **D** **O** **X**®
S E C U R I T Y S Y S T E M S













Максипринт Компјутери ЛТД ДОО
Бул. Туристичка бр.4, Охрид
Охридска банка Жиро сметка:
530000100483931
Контакт: 046-262 500 / 070-249 724
070-212 929
e-mail:
prodazba@maksiprint.com.mk

Wireless Alarm System DAHUA





МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ART-ARC3000H-03-GW2 – Alarm KIT Supports 150 wireless peripherals Peripherals status display (signal strength, battery level, temperature, program version) Wired, Wi-Fi or GPRS network connection; Dual SIM and Single Standby, auto switching; Automatic network replenishment (ANR); Video linkage on App SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	18.000ден
	DAHUA ART-ARC3800H-03-FW2 Dahua Wireless Alarm KIT Supports alarm video verification through integration of the IPC with the hub; Features voice call alarm; Supports wired and AP network configuration methods, which makes it easier to add the hub to apps and to switch to the hub's network; Supports multi-network redundancy for Ethernet, Wi-Fi and 4G networks to ensure the network remains stable and reliable;	19.500ден
	DAHUA ARD1233-W2 - Wireless PIR detector Pet immunity function; Auto temperature compensation; 3-level sensitivity adjustment; Low battery alarm; Anti-tampering; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability;	2.900ден
	DAHUA ARA33A Detector Bracket	390ден
	DAHUA ARD1731-W2 - Wireless PIR-Camera Maximum resolution 1600*1200; Based on the RF-HD image transmission technology, transmission of 6 HD images with resolution of 1600*1200 needs up to 10 seconds; One-week cloud cache for videos and images; Temperature monitoring;	7.600ден
	DAHUA ARD323-W2 - Wireless Door Detector Signal strength detection; Low battery alarm; Temperature measurement Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure	2.090ден
	DAHUA ARA13-W2 - Wireless outdoor siren IP65 rated; Outdoor product (-25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	6.215ден
	DAHUA ARA12-W2 - Wireless siren Signal strength detection; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure.	3.320ден
	DAHUA ARA24-W2 - Wireless Keyfob SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	1.700ден
	DAHUA ARK30T-W2 - Wireless Keypad Supports 3 shortcut alarms: Medical, fire, emergency; Arm/Disarm with password or IC card; Supports signal strength detection to select suitable installation sites; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication; Cloud update and automatic recovery from update failure.	4.640ден
	DAHUA ARD821-W2 - Wireless Panic Button Two-way RF communication; Provides multiple LED colors to indicate different statuses; Cloud update and automatic recovery from update failure; Offers accidental press prevention; Battery life up to 5 years if used twice a week; IP54 rated	1.960ден

	<p>DAHUA ARM310-W2 - Wireless Input Expander</p> <p>Six types of alarm: intrusion, medical, fire, emergency, gas, and tamper; NC and NO are available for alarm inputs (NO by default); Signal strength detection; Low battery alarm; Temperature monitoring; Frequency hopping function and two-way communication technology ensure communication stability;</p>	2.240ден
	<p>DAHUA ARD912-W2 - Wireless Water Leak Detector</p> <p>Frequency hopping and two-way communication technology ensure that communication is stable; Displays the temperature of the surrounding environment and supports the overheating alarm; Sensitivity adjustment;</p>	3.500ден
	<p>DAHUA ICS1-W2 - Smart Plug</p> <p>Two-way RF communication; Displays the status with an LED indicator; Offers protection against overcurrent, overvoltage, and overheating; Measure the voltage, current and temperature;</p>	2.870ден
	<p>DAHUA ARM7011-W2 Dahua Wireless Relay</p> <p>Frequency hopping and two-way communication technology ensure that communication is stable; Supports jamming detection and communication encryption. Supports cloud update and automatically restores when cloud update fails.</p>	2.130ден
	<p>DAHUA HY-RI151 LED Remote Indicator</p>	777ден
	<p>DAHUA ARA43-W2 - Alarm Repeater</p> <p>Connects up to 32 peripherals; Two-way RF communication; LED indicator displays device status; Supports manual and auto pairing, extending RF distance for your security system; Auto switches from dual antennas to reduce blind area; Battery backs device working for over 35 hours</p>	6.000ден
	<p>DAHUA HY-SA21A-W2 - Wireless Smoke Alarm</p> <p>Split-spectrum sensor technology; Test and silence features in one single button; Loud sound output over 85 dB(A) at 3 meters; Low quiescent current consumption; Surface-mount device (SMD) circuit board design; Low battery warning signal</p>	4.080ден
	<p>DAHUA HY-SAV849HA-E - 5MP IR AI-fire Smoke Sensing Network Camera</p> <p>Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices, and user can import custom voices; 2/2 Alarm in/out, 1/1 audio in/out;</p>	ден
	<p>DAHUA ARM9A4-W2(868) Dahua Wireless Multi IO Transmitter</p> <p>Connection to Hub through RF communication; 16 alarm inputs, 4 relay outputs; 2 auxiliary power outputs with a maximum power of 24W for powering wired detector and siren, and support overload and short circuit detection; AC power and rechargeable battery (optional) two power supply options;</p>	11.380ден


Wireless Alarm System AJAX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p>AJAX Starter Kit White/Black</p> <p>Стартниот комплет за безбедносниот систем Ајах. Комплетот се состои од хаб, детектор за движење, детектор за отворање и приврзок со паник копче</p>	21.000ден
	<p>AJAX HUB - Централна единица White/Black</p> <p>Централна единица (HUB) за безжичен противпровален систем со интегрирани LAN и GSM/GPRS комуникатори. Овозможено додавање и работа на до 100 безжични уреди, со до 50 корисници. Вградена back-up батерија.</p>	13.300ден
	<p>AJAX HUB2 - Централна единица White/Black</p>	19.400ден
	<p>AJAX ReX - Засилувач за сигнал White/Black</p> <p>Безжичен рипитер на сигнал за AJAX системи, кој го појачува сигнало и до два пати, напојување 220VAC, вградена back-up Li-Ion 2A батерија (автономија и до 35 часа. Бела боја</p>	9.600ден
	<p>AJAX MotionProtect - Безжична детекција на простор White/Black</p> <p>Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: / ; Монтажа: Сидна; Степен насигурност: Grade 2;</p>	4.600ден
	<p>AJAX MotionProtect Plus - Безжична детекција на простор White/Black</p> <p>Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR / MW; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: 12m ; Монтажа: Сидна; Степен насигурност: Grade 2;</p>	7.095ден
	<p>AJAX CombiProtect - Безжична детекција на простор White/Black</p> <p>Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR / GB; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: / ; Монтажа: Сидна; Степен насигурност: Grade 2;</p>	7.240ден
	<p>AJAX DoorProtect - Безжична детекција во точка White/Black</p> <p>Безжичен магнетен контакт со приклучок за дополнителен контакт.</p>	2.850ден
	<p>AJAX DoorProtectPlus - Безжична детекција во точка White/Black</p> <p>Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Вибрации / Отворање - Затворање; Метода надетекција: Детектор на вибрации / Reed; Дострел надетекција: 20 mm; Монтажа: Надградна;</p>	4.610ден
	<p>AJAX GlassProtect - Безжична детекција во точка White/Black</p> <p>Безжичен детектор за кршење на стакло со домет до 9m. Бела боја</p>	5.200ден







	<p>AJAX HomeSiren - Безжични сирени White/Black Вградување: Внатрешна; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна; Звучен излез: Прилагодливо, 81-105 dB @ 1m; Трепкачкосветло: LED; IP заштита: IP50;</p>	5.410ден
	<p>AJAX StreetSiren - Безжични сирени White/Black Вградување: Надворешна; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна; Звучен излез: Прилагодливо, 85-113 dB @ 1m; Трепкачкосветло: LED; IP заштита: IP54;</p>	10.900ден
	<p>AJAX MotionProtect Outdoor - Безжична детекција на простор Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Надворешна; Метода надетекција: PIR / AM; Неосетливостна домашнимиленици: <80cm; Дострел надетекција: PIR: 15m; Дострел надетекција: MW: / ; Монтажа: Сидна / Столбна; Степен насигурност: Grade 2;</p>	16.000ден
	<p>AJAX MotionCam WH</p>	11.600ден
	<p>AJAX Keypad - Безжична тастатури White/Black Начин на приказ: Touchsense LED; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна;</p>	7.975ден
	<p>AJAX SpaceControl - Далечински управувач White/Black Безжичен далечински управувач, 4 функциски копчиња, LED известување. Бела боја</p>	2.490ден
	<p>AJAX FireProtect - Безжична детекција на состојбата на околината Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Чад / температура / нагло растење натемпературата; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);</p>	6.300ден
	<p>AJAX FireProtect 2 Heat/Smoke Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Чад / CO / температура / нагло растење натемпературата; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);</p>	8.990ден
	<p>AJAX LeaksProtect - Безжична детекција на состојбата на околината Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Поплава; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);</p>	3.800ден
	<p>Ajax Transmitter - Влезен модул Модул за безжично поврзување на универзални безжични детектори (Optex VX80R, AMC Soutdoor BC исклучно) на AJAX противпровалнитесистеми.</p>	4.020ден
	<p>AJAX MultiTransmitter WH</p>	12.220ден
	<p>AJAX Socket WH / AJAX Socket BL - Безжични излезни модули Намена: Приклучок за 220VAC потрошувачи, Schuko-тип F; Безжичнафреквенција: 868 MHz;</p>	5.050ден

	<p>AJAX WallSwitch BL - Безжични излезни модули Намена: Приклучок за 220VAC потрошувач; Безжичнафреквенција: 868 MHz;</p>	3.070ден
	<p>AJAX Relay BL - Безжични излезни модули Намена: Релеен излез; Безжичнафреквенција: 868 MHz;</p>	3.070ден
	<p>AJAX osBridge Plus - Безжични модули Намена; Безжичнафреквенција: 868 MHz; Компатибилницентрали: Жичани алармни централи; Спојување наалармнатацентрала: Релеи; Број на PGM-и – жичано: 8; Број на зони - Безжично: 99;</p>	5.490ден
	<p>AJAX uartBridge - Безжични модули Намена; Безжичнафреквенција: 868 MHz; Компатибилницентрали: Жичани алармни централи; Спојување наалармнатацентрала: UART; Број на PGM-и – жичано: /; Број на зони - Безжично: 99;</p>	3.290ден









Wired Alarm System PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox Control Panel SP4000 Supports StayD mode; On-board Zones: 4 (8 with ATZ)-Keypad Zones: 15; Expandable to 32 zones; PGMs: 12 -2 Partitions; 4-wire expansion bus-32 User Codes; Supports PCS Series; Supports IP100 Internet Module;Wireless Expansion (RTX3), one way transmitters only;	3.500ден
	Paradox Control Panel SP5500 Supports StayD mode; On-board Zones: 5 ; Keypad Zones: 15; Expandable to 32 zones; PGMs: 16 -2 Partitions; 4-wire expansion bus -32 User Codes; Supports PSC100 GSM Module; Supports IP100 Internet Module; Supports REM3 hand-held remote keypad	3.900ден
	Paradox Control Panel SP6000 Supports StayD mode; On-board Zones: 8 (16 with ATZ); Keypad Zones: 15; Expandable to 32 zones; PGMs: 16; 2 Partitions; 4-wire expansion bus; 32 User Codes; Supports PSC100 GSM Module; Supports IP100 Internet Module; Supports REM3 hand-held remote keypad	4.400ден
	Paradox Control Panel SP7000 Supports StayD mode; On-board Zones: 8 (16 with ATZ); Keypad Zones: 15; Expandable to 32 zones; PGMs: 16; 2 Partitions; 4-wire expansion bus; 32 User Codes; Supports PSC100 GSM Module; Supports IP100 Internet Module; Supports REM3 hand-held	5.300ден

Wireless Alarm System PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox Wireless Control Panel MG5000 StayD Mode; Built-in transceiver (433MHz); 32 zones (any of which can be wireless); 32 users and 32 remote controls (one per user); 2 partitions; 4-wire communication bus (connect up to 15 keypads); Supports REM3 hand-held remote keypad; Supports up to 8 K32RF / K37 wireless keypads; Supports up to 2 RPT1 wireless repeaters; Supports PCS Series; Supports IP100 Internet Module; Supports VDMP3 Plug-in voice dialer; Supports 16 PGMs (any of which can be wireless);	4.800ден
	Paradox Wireless Control Panel MG5050 StayD Mode; Built-in transceiver (433MHz); 32 zones (any of which can be wireless); 32 users and 32 remote controls (one per user); 2 partitions; 4-wire communication bus (connect up to 15 keypads); Supports REM3 hand-held remote keypad; Supports up to 8 K32RF / K37 wireless keypads; Supports up to 2 RPT1 wireless repeaters; Supports PCS Series; Supports IP100 Internet Module; Supports VDMP3 Plug-in voice dialer; Supports 16 PGMs (any of which can be wireless);	5.800ден
	Paradox Wireless Console with GPRS/GSM MG6250 Simultaneous Five-channel Reporting Offers reporting viaGPRS, GSM, SMS, Voice, and traditional landline, with predefinedcommunication sequences to save installation time.; 2 partitions and up to 64 wireless zones; Supports optional quad-band GPRS/GSM module with 2 SIMcards (GPRS14); Built-in transceiver (433 MHz); Speakerphone via GSM or landline; Built-in voice and utility reporting(up to 8 telephonenumber); Two-way voice communication (via GSM or landline);	12.300ден
	Power Adapter Plug PA7 For the MG6250; Provides 7.5Vdc	1.500ден
	Paradox GPRS14 Communication Plug-in Module; Accessory for the MG6250, used to support GPRS/GSM/SMS reporting; Supports 2 standard GSM provider SIM cards, for provider redundancy; Simple installation; connects directly onto PCB	6.200ден
	Modul za internet IP150 Paradox The IP150 Internet Module is an Internet communication module that enables you to control and monitor your security system through any web browser (e.g. Internet Explorer). The IP150 provides freedom to access your system and receive email notifications anywhere in the world.	5.500ден

Keypad Paradox

МОДЕЛ	ХАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	<p>Paradox keypad K636 10-zone LED display; Compatible with E55, MG5000, MG5050 and Spectra SP series; Single partition keypad; StayD status LED; Patented Key Light display (button lights up to indicate an open zone); Arm, Sleep, Stay and Off keys illuminate to indicate partition status; Adjustable backlight</p>	<p>2.200ден</p>
	<p>Paradox keypad K10 H/V 10-zone LED display; Compatible with MG5000, MG5050 and Spectra SP series; Supports StayD Mode; Separate Arm, Sleep, Stay and Off LEDs per partition; Patented Key Light display (button lights up to indicate an open zone); 1 keypad zone input; Independently set chime zones; 7 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight; Connects to 4-wire communication bus</p>	<p>3.035ден</p>
	<p>Paradox keypad K32LED 32-zone LED display; Compatible with MG5000, MG5050 and Spectra SP series; Supports StayD Mode; Separate Arm, Sleep, Stay and Off LEDs per partition; In-field firmware upgrade via 307USB and WinLoad; 1 keypad zone input; Independently set chime zones; 7 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight; Connects to 4-wire communication bus</p>	<p>4.300ден</p>
	<p>Paradox keypad K32LX 32-character blue LCD with programmable labels; Real-time zone alarm display (until disarmed); In-field firmware upgrade via 307USB and WinLoad; StayD status LED; 1 keypad zone input; 8 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight, contrast and scroll speed; Connects to 4-wire expansion bus; Compatible with MG5000, MG5050 and Spectra SP series V2.31 and up;</p>	<p>4.700ден</p>
	<p>Paradox keypad K38 Wireless Powered by 2 "AA" batteries, with built-in backup battery (PA6 is optional), A 6Vdc power adaptor (PA6 not included) is not required but can be used as an alternative power source, 3 keypad-activated panic alarms, Built-in transceiver (433MHz), Compatible with MG6250, MG5000 / MG5050 V3.22, MG5075, Spectra SP V3.22 (except SP4000) and RTX3 V1.42</p>	<p>8.800ден</p>
	<p>Paradox Interactive Touchscreen TM50 12.7 cm vivid color display (480 x 272 pixels); Intuitive, icon-based menus – no manual needed; Control up to 8 PGM outputs; In-field firmware upgradable via micro SD card; 1 zone/temperature input to connect a detection device or aTEMP07 (External Temperature Sensor); Customized translation via webapplication;</p>	<p>11.500ден</p>
	<p>Paradox Interactive Touchscreen TM70 12.7 cm vivid color display (480 x 272 pixels); Intuitive, icon-based menus – no manual needed; Control up to 8 PGM outputs; In-field firmware upgradable via micro SD card; 1 zone/temperature input to connect a detection device or aTEMP07 (External Temperature Sensor); Customized translation via webapplication;</p>	<p>12.150ден</p>
	<p>Power Adapter Plug PA6 For the K32RF and K32WK; Provides 6Vdc at 350mA max</p>	<p>1.500ден</p>




Wired Motion Detector PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox 476 PRO+ Analog Single-Optic PIR; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Extremely high EMI and RFI rejection; PCB uses only surface mount components; Solid-state relay; Patented Auto Pulse Signal Processing; Automatic Temperature Compensation; Metal shield maximizes protection from EMI and RFI signals;	999ден
	Paradox 476 PET P2C Analog Single-Optic PIR; Immune to animals weighing up to 18kg; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Extremely high EMI and RFI rejection; PCB uses only surface mount components; Solid-state relay Automatic Temperature Compensation; Metal shield maximizes protection from EMI and RFI signals;	1.400ден
	Paradox NV5 High-Performance Infrared Motion Detector; Infrared motion detector managed by Full Authority Digital Electronics Control (FADEC); Paradox's Hybrid Cylindrical-Spherical 1.0" lens with 3rd generation 3D Lodiff® Fresnel segments - (10 x 10 m), 102° viewing angle, and 0.5 m to max range	1.100ден
	Paradox DG85 Outdoor High-Security Digital Motion Detector; Impact and temperature resistant casing (-35°C to 50°C); Patented Digital Motion Detection; Extremely reliable and false-alarm free; Dual Optical Filtering System; UV protected lens; Dual optics (2 dual opposed element sensors); Digital Dual Opposed Detection; Multi-level sensitivity adjustment; Two operational modes (Bus or Relay operation)	ден
	Paradox DG457 Glassbreak Detector; Conventional solid-state relay operation; Full audio and infrasonic spectrum analysis; 7 frequency digital filters, digital amplifier gain and frequency fluctuation assessment; Impact and shock wave analysis; High-immunity to RFI and EMI signals; Adjustable sensitivity: covers up to 9m when set to high and up to 4.5m when set to low; Anti-tamper switch	2.245ден
	Paradox DG467 360° Ceiling Mounted Digital Motion Detector; Two operational modes (addressable for the Digiplex and Digiplex EVO series or conventional relay operation); Dual opposed element sensor; Digital Detection; 7m x 6m at 2.4m; 11m x 6m at 3.7m; 360° viewing angle	3.200ден



Wireless Motion Detector PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox PMD2P Wireless Analog Single-Optic PIR (433MHz); Dual element sensor; Immune to animals weighing up to 18kg; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Wireless range in a typical residential environment: 35m with MG6160, MG6130; 70m with MG5000, MG5050 and RTX3; Patented Auto Pulse Signal Processing; Automatic Temperature Compensation;	3.340ден
	Paradox G550 Wireless Glassbreak Detector (433MHz); 6m radius range and 360° coverage pattern protects an entire room with one sensor; Detect breaking of different types of glass including plate, tampered, laminated and wired; Standard Alkaline 3x AAA type battery with low battery supervision; Factory-set sensitivity for safer installation; Recognizes actual pattern of breaking glass across the full audio band;	9.655ден







Remote Control & Wireless Door Contacts

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox REM25 Remote Control with Backlit Buttons (433MHz); Water resistant; Perform up to 5 different actions; Wireless range in a typical residential environment:; 30m with all-in-one consoles and RX1; 45m with MG5000 / MG5050; 60m with RTX3	1.995ден
	Paradox REM101 Emergency/Panic Remote Control (433MHz); Water resistant; Panic function allows user to instantly send panic signal to monitoring station; Includes lanyard attachment to facilitate portability; optional wrist strap and belt clip Includes easily-replaceable CR2032 battery, with a battery life of 3 years with MG6130 / MG6160 / MG6250 and RX1; 45m with MG5000 / MG5050, K32LX and K641LX; 60m with RTX3	1.920ден
	PARADOX Metal Box 28cm X 28 X 8 cm; Provision for multiple module and panel mounting; Many punch-out holes for simple wiring; Easy door removal	2.200ден


GSM Home Alarm System

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	M-WG107T Tuya Smart WiFi GSM Alarm System ♦ APP name:TuyaSmart; ♦ Work with Amazon Alexa/Google Assistance ♦ 4.3 inch touch screen LCD; ♦ Input Voltage:5V/1A ♦ Support 100 wireless detector, remote control and RFID cards; ♦ Low-battery detection/Power off detection ♦ Built in battery to enable the alarm panel continue work when no WiFi;	ден
	M-WSR201 Wireless Signal Repeater with Adapter It is a special device for extending the wireless signals; Working voltage: DC12V; Operating current: 150mA-180mA; Distance extend 500-1000m;	3.000ден





Wireless GSM Home Alarm System Accessories

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	IR202 Wireless PIR motion detector with ON/OFF switch power 6F22 battery 9V, low power indication, adjustable time for alarm delay detecting, distance adjustable, automatically temp. compensation, anti-RFI & anti-EMI battery life 1-2 year, Detecting distance:12m detecting angle: 110 degrees	1.055ден
	Tuya Smart WiFi PIR Sensor - M-WP002 APP name:TuyaSmart; Battery:3V CR123A lithium battery Low-battery detection; PIR sensitivity angle:110 degree; PIR sensitivity distance:10m;	2.100ден
	Wireless Door/Window Magnetic Sensor DS201 It is consisted of transmitter and magnetic part, it is used to detect door, window, or drawer if it is opened or moved , 12 Volt battery included for 3 months, it can be adhesive or by screws.	680ден
	Wireless Panic Button PB101	620ден
	Remote Controller RC105D Wireless Metal Remote ControllerPower: 23A 12V battery; Open distance: 100-150m; Only 2262 IC; Workingfor alarm model G10C ,G10A ,PG992CQ ,GA997CQN ;	930ден
	Remote Controller RC201A Wireless Remote ControllerPower: CR2032 3V Lithium Cell battery; Open distance: 100m; Only 1527 IC; Compatiable with G10C,G10A,GA997CQN;	800ден

Wired Alarm System





МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	PC1864NKEH Alarmna centrala so 8+8 zoni(+ 8 zoni na 8 tastaturi) dellivi vo 8 PARTICII,max.8 tastaturi , 35 korisnicki sifri,memorija za 500 nastani, PC link,vgraden digitalen komunikator,4 PGM izlezi so prosiruvanje do 16,prosiruvanje do max. 64 zoni so pomos na7 PC5108 moduli, prosiruvanje so 32 bezzicni zoni so pomos naRF5108,RF5132 i RFK5501(max.4 bezzicni moduli), prosiruvanje so 64 adresabilni elementi so pomos nadva PC5100	9.000ден

Wired Home Alarm Accessories






МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Gas Detector MT-20083X Wired Gas Leakage Detector HOT! 220V A.C.. power optional,auto-test for malfunction,Alarm Output: sound &flash alarm; wall mounted	1.350ден
	Carbon Monoxide Detector CO101 Wired Carbon Monoxide Detector HOT! 220V A.C.. power optional,auto-test for malfunction,Alarm Output: sound &flash alarm; wall mounted!	1.700ден
	Temperature Detector TD201 Wired Temperature Detector; 9-35VDC, NC/NO output PST-TD201- 220V A.C.. power optional,auto-test forMalfunction, Alarm Output: sound & flash alarm; wall mounted!	1.100ден
	Smoke Detector IR104 Wired photoelectronic smoke detector 12V D.C, Sound & flash alarm, anti white light interference, alarm output: relay output N.O. / N.C, alarm volume: more than 85dB/m.	1.300ден

	Smoke Detector SD603 Wired photoelectronic smoke detector, 12V D.C, Sound & flash alarm, anti white light interference, alarm output: relay output N.O. / N.C, alarm	1.200ден
	Door Sensor RC35 Wired Recessed Door/Window Sensor	155ден
	Door Sensor WD102 Wired Door/Window Magnetic Sensor normal	155ден
	Door Sensor WD103 Wired Door/Window Magnetic Sensor MINI	185ден
	Exit Button PV1 NO/NC/COM Surface Mount Ultra Narrow Size Dimension: 76L*23W*14H(mm); Weight: 0.04kg; Standard Package: 10pcs/bag; Fireproof PVC material;	155ден
	Exit Button DEB02 Wired Door Exit Push Button	500ден
	Exit Button Z30 – Metal casing NO/COM Small Size with Back Box Surface Mount; Dimension: 80L*30W*24H(mm); Weight: 0.14kg; Standard Package: 200pcs/carton/29kg/51*46*25cm; Zinc Alloy Plate and steel button, Wire Drawing Finished;	995ден
	Exit Button NT86 NO/NC/COM with Light Dimension: 86L*86W*25H(mm); Weight: 0.15kg; Input: DC12V; the light will turn to green when active; sensitive distance is adjustable from 1-15cm; Optional Accessories: M86 Mounted Back Box	870ден
	SOS Button EP-WOP Монтажа: Сидна, со завртки или сидна кутија; Начин на активација: Притискање на црвеното копче; Влечење на црвениот конопец; Материјал: ABS пластика (огноотпорна); Боја: Бела плоча со црвено копче и конопец	990ден
	Hand-Held Fire Detector FAB01 Wired fire alarm button; Installation environment: Indoor or dry occasion; Maximum current allowed: 3a; Maximum voltage allowed: 50v; Lowest voltage: 12v	800ден
	Hand-Held Fire Detector ACM-K3G Model: ACM-K3G; Dimensions : 86Lx86Wx50H(mm); Standard Structure : Fireproof Material, Easy to install; Current Rating : 3A 36VDC Max; Output Contact : NO\NC\COM; Operating temp : -10°C ~ 55°C (14°F-131°F); Suitable for Door : Exit Door, Emergence Door; Material Selection : Fireproof Material, Sandblast Finished;	745ден
	Hand-Held Fire Detector ACM-K3W Model: ACM-K3G; Dimensions : 86Lx86Wx50H(mm); Standard Structure : Fireproof Material, Easy to install; Current Rating : 3A 36VDC Max; Output Contact : NO\NC\COM; Operating temp : -10°C ~ 55°C (14°F-131°F); Suitable for Door : Exit Door, Emergence Door; Material Selection : Fireproof Material, Sandblast Finished;	745ден




Infrared Baluster or Beams

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	MT-20L Senzor Photo cell	1.950ден
	IB705 3-beam,wired,Detecting distance: 250M; length:27CM	4.950ден
	IB805 4-beam,wired,Detecting distance: 250M; length:35CM	5.200ден
	IB110 Wireless- wired :twin-beam,outdoor detecting distance:40M,valid length:28cm	3.720ден

Sirens

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Sirena MS102 Wired siren, It directly connects to the main host;OPERATION VOLTAGE:DC6-12V; SOUND TYPE:SINGLE TONE/6-TONE; COLOR:BLACK/WHITE/RED; SIZE:54(W)×48(L)×54(H) mm	ден
	S103 Outdoor - Indoor Wired Sound Horn rated voltage: DC12V; rated current: 1200mA; sound level: 115dB; power: 20W	500ден
	M-CA-210 Outdoor - Indoor Wired Sound Horn Power supply:DC12V; Alarm current:600-1000mA; Alarm Sound:≥120dB;; Dimension: 300*300*200mm; Tones: single tone; Fire-proof ABS or PC material available	990ден
	M-CA-600S Outdoor - Indoor Wired - Sound Horn 6 Tones Black Alarm Power supply:12V Operating; Voltage:6-15VDC; Rated Current: 600/1200 mA; Tones :6 Tones- Single Power: 15W/20W SPL (Db/m)	870ден
	Blinking Rotary signal lamp High bright, High transparency fadeless, low noise, bolt fastening Magnetic solution Environmentally friendly and power saving. Good vibration resistance and stable emitting. Durable and non-fading brilliant beams. Instant and immediate light on. Voltage:DC12V. Long life:50000 hours or more. Waterproof, surge protection	555ден
	Red LED Lamp Flashing Light	555ден
	Siren FS-106 Wired Flashing & Sound Siren	1.485ден
	Siren CA-102 flashing warning strobe & sound siren rated voltage: DC12V/24VDC/110V-220AC; rated current: 300mA; sound level: 120dB; power: 30W/40W; Strobe source: Xenon Tube/Led; flash frequency:70-90time/min	620ден

	Siren HC-36A OPERATION VOLTAGE:DC 6-12V; SOUND TYPE:SINGLE TONE/6-TONE; OUTPUT POWER:10W/15W; COLOR:WHITE; SIZE:110(W)×55(L)×110(H)mm	700ден
	Siren SL-350 Rated Voltage: DC12V ; Operating Voltage: DC9-15V ; Rated Current: 300mA ; Strobe source: Xenon Tube/LED ; Flash Frequency: 70-90 times/minute ; Sound SPL: 110dB ; Operating temperature: -20~60°C	1.200ден
	Siren M-OFS-WG Wireless Wireless Outdoor Flash & Sound Siren with Backup Battery Note: only working for models: WG103, WG106, WG103T, WG107T; G30, G12. Note: Adapter included with tamper switch	2.790ден
	Siren M-WG107T Wireless Outdoor Solar Siren working with PST-WG107T	3.285ден
	Siren PA-200 Outdoor siren with flash, 120dB (without battery) INSIDE METAL COVER FOR DOUBLE PROTECTION; MAGNETIC DYNAMIC SOUNDERS WITH 120DB AT 1M; LEN CORLORS IN RED,BLUE,ORANGE,WHITE; 3 WAY TAMPER SWITCH PROTECTION	2.480ден
	Siren SL-650R OUTER SIREN WITH STROBE LIGHT 24V Siren Voltage DC24v , Power 50W,Siren Current 1200mA , Strobe current 250mA ,Strobe freq 120-150/minute , SPL 128dB ,Lens color REDMaterial ABS/AS/PC	2.850ден
	Paradox SR250 Wireless Siren with Built-in Strobe (433MHz); Compatible with MG Series V4.0 and SP series V4.0 whenusing an RTX3 V1.5; 100db wireless siren with integrated strobe light; Weather-resistant design using a PC/ABS enclosure with UVprotection and a silicone coated PCB (-20°C to 50°C); Battery powered only, no need for AC power; Wireless range in a typical residential environment:- 35m with MG6160, MG6130, and MG6250; 70m with MG5000, MG5050 and RTX3-2.5 hour alarm display (strobe flashes every 4 seconds afterbell cut-off);	10.150ден
	M-ST-DC1 WIFI Smart Door Opener Relay; APP name:TuyaSmart; Work with Amazon Alexa/Google Assistance/IFTTT; Work Voltage: DC7-32V; Wifi Frequency: 2.4GHz; Relay Load: 250V/10A; Work alone, not work with alarm panel together	2.355ден
	RTU5024 GSM Door Opener GSM Frequency , Quad-band 850/900/1800/1900MHz , Digital Output , NC/NO dry contact 3A/240VAC , Power consumption , 12V input Max. 50m A/Average 25mA , SIM Card Supporting 3V SIM Card, Temperature range -20~+60 °C, Backup battery 3.7V/900Mah; Exterior dimension 102mm*D76mm*H27mm	3.999ден
	TTT603 GSM telephone modem GSM Dual Band, Compatible with GSM 900 /1800 MHZnetworks . Built-in Digital antenna; send and receive voice call, send and receive SMS, Interrogate your voicemail; Voice and SMS service; Information at a glance status LEDs, a new voice mailmessages and other important functions; Ring voltage: 68V; Power Supply: DC12V	3.700ден

	Akumulator 12V – 1.3 Ah Akumulator 12V – 4.0 Ah Akumulator 12V – 7.0 Ah Akumulator 12V - 9.0 Ah	900ден 1.300ден 1.700ден 1.400ден
	Transformator 220VAC/16V-30VA vo zastitno kukiste so klemi I osiguruvac	1.180ден
	Rele 12V	185ден

Cable

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Alarm Cable 6 x 0.22, shild 100m , EXTRA	25ден
	Alarm Cable COPPER 6 x 0.22, shild 100m , COPPER EXTRA	35ден
	PP kabeL 2x0,80mm COOPER , RED color	35ден
	PP kabeL- Bavno gorecki –LSZH 2x0,80mm COOPER , LSZH, RED color, nezapaliva izolacija po CEI 20-22 II i IEC 323-3C standardi	40ден
	PP Kabel – Fire Alarm Cable J-H (ST)H 2*2*0,6 MM+0,5MM (TINNED)	29ден
	PP Kabel – Fire Alarm Cable J-H (ST)H 2*2*0,8MM+0,5MM	45ден
	PP Kabel – Fire Resistant Cable JE-H(St)H Bd (FE180 / E90 / PH120)	60ден
	Signal Cable – Power Cable LITCY 3*0,5 MM	42ден

Цените се END USER и истите важат за крајни корисници.

Цените се претставени со пресметан ДДВ.

Гаранција на производите е од 1-24 месеци.

МАКСИПРИНТ го задржува правото на промена на цените без претходна најава.