




dahua
TECHNOLOGY

Максипринт Компјутери ЛТД ДОО
Бул. Туристичка бр.4, Охрид
Охридска банка Жиро сметка:
530000100483931

Контакт: 046-262 500 / 070-249 724 / 070-212 929
e-mail: prodazba@maksiprint.com.mk



HDCVI 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-T1A21-U – 2.8mm 2MP HDCVI IR Eyeball Camera Max. 30 fps@1080p; Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	1.300ден
	DAHUA HAC-T2A21-U – 2.8mm 2MP IR HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	1.400ден
	DAHUA HAC-HDW1200T-Z-A 2MP HDCVI IR Eyeball Camera Max 30fps@1080P; HD and SD output switchable; Built-in mic; 2.7-12mm motorized lens; Max. IR length 60m, Smart IR; IP67, DC12V	4.400ден
	DAHUA HUM1220G-B - 2.8mm 2MP HDCVI Bullet Camera Max 30fps@1080P, 2.8mm fixed lens, DC12V; HD and SD output switchable;	1.750ден
	DAHUA HAC-HUM3200A 2MP IR HDCVI Fixed-focal Cube Camera Max 30 fps@1080p; 10 m illumination distance (940nm IR No IR Exposure); Super Adapt; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC;	2.850ден
	DAHUA HAC-B1A21-U - 2.8mm 2MP IR HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	1.350ден
	DAHUA HAC-B2A21-U – 3.6mm 2MP IR HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	1.450ден
	DAHUA LC1220T-TH - IoT Series - 2.8mm 2MP HDCVI Temperature & Humidity Camera Max 30fps@1080P, 2.8mm fixed lens, Max. IR length 20m, Detection range: -40°C~60°C, 10-95% RH, Smart IR, IP67, DC12V	2.400ден

HDCVI 2MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1200TLM-IL-A – 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	2.620ден
	DAHUA HAC-HFW1200CM-IL-A - 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	2.620ден
	DAHUA HAC-HDW1200CLQ-IL-A – 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; 12 VDC.	1.985ден
	DAHUA HAC-HFW1200TLM-IL-A - 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 40m illumination distance; Super Adapt; Built-in mic; 2.8mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12VDC	2.320ден

HDCVI 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-T1A51-U – 2.8mm 5MP IR HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	1.700ден
	DAHUA HAC-B2A51-U 5MP IR HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	1.750ден
	DAHUA HAC-HDW1500TRQ-A – 2.8mm 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera Max 25 fps@5MP (16:9 video output); Built-in mic (-A); CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 25M; Smart IR; IP50, DC12V;	2.750ден
	DAHUA HAC-EW2501 5MP HDCVI IR-Fisheye Camera 1/2.8" 5Megapixel progressive scan CMOS; Panoramic fisheye lens; Max. 20fps@5MP; Built-in Mic; 120dbtrue WDR, Starlight, 2D&3D NR; Max. IR length 10m, Smart IR; DC12V	9.999ден

HDCVI 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1500CLQ-IL-A 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart Dual Light; 20m illumination distance; Super Adapt; Built-in MIC; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC	2.550ден
	DAHUA HAC-HFW1500RL-IL - 2.8mm 5MP Smart Dual Light HDCVI Two-way Talk Fixed-focal Bullet Camera Max. 25 fps@5MP; Two-way Talk; Smart Dual Light; Smart Light+; 3D NR; 30 m illumination distance; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	2.680ден
	DAHUA HAC-HFW1500TLM-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	3.100ден
	DAHUA HAC-HFW1500TH-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 25 fps@5MP (16:9 video output); Starlight, 3D NR; Smart Dual Light; 80 m illumination distance; Built-in Mic; 3.6 mm fixed lens; IP67, 12 VDC;	4.300ден
	DAHUA HAC-PT1500A-IL-A - 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal PT Camera Max. 25 fps@5MP; Smart Dual Light; Smart Area Lighting; Pan & Tilt; 40 m illumination distance; Super Adapt; Built-in Mic; 2.8mm fixed lens; IP66, 12 VDC.	4.820ден
	DAHUA HAC-PTS1500C-E2-IL-A 2+2MP Smart Dual Light Outdoor HDCVI Dual-Lens PT Camera Max 25 fps@5 MP (16:9 video output); Smart Dual Light; 50 m illumination distance; Super Adapt; Built-in Mic; Linkage Tracking; Manual Linkage; 2.8 mm fixed lens, 6 mm PT Lens; Supports manual adjustment of fixed lens (Vertical: 5° to 10°); IP66, 12 VDC;	6.400ден

5MP WizColor HDCVI Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1549X-IL-A-PRO - 2.8mm 5MP WizColor HDCVI Fixed-focal Eyeball Camera Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt, 130 dB true WDR, 3D NR; Built-in Dual Mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	4.575ден
	DAHUA HAC-HFW1549X-IL-A-PRO 5MP WizColor HDCVI Fixed-focal Bullet Camera Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt, 130 dB true WDR, 3D NR; Built-in Dual Mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	4.575ден

HDCVI 5MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1509TLQ-LED - 3.6mm 5MP Full-color HDCVI Quick-to-install Eyeball Camera Max 25 fps@5MP (16:9 video output); 120dB true WDR, 3D NR; 24/7 color image; 20 m illumination distance; CVI/CVBS/AHD/TVI switchable; IP67, 12 V DC;	2.520ден
	HAC-HFW1509C-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance 2.8 mm fixed lens; IP67, 12V DC	2.520ден
	HAC-HFW1509C-A-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance; Built-in mic; 2.8 mm fixed lens; IP67, 12V DC	2.520ден
	DAHUA HAC-HFW1509TLM-IL-A - 3.6mm 5MP Smart Dual Light Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	3.000ден
	HAC-HFW1509TLM-A-LED - 3.6mm 5MP Full-color HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output) 120 dB true WDR, 3D NR; 24/7 color imaging; Smart Light+; Smart Area Lighting; Built-in Mic; 40 m illumination distance; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed; IP67, 12 VDC;	3.450ден

HDCVI 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1801TLM-IL-A – 2.8mm 4K Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 2.8 mm fixed lens; IP67, 12 VDC;	3.900ден
	DAHUA HAC-HFW1801TLM-IL-A – 3.6mm 4K Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	3.900ден
	DAHUA HAC-HFW1801TH-IL-A 4K Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; Smart Dual Light; 80 m illumination distance; Super Adapt; Built-in Mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	4.250ден

HDCVI 8MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HAC-HDW1809T-A-LED – 2.8mm 4K Full-Color HDCVI Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging 40 m illumination distance; Super Adapt; Built-in MIC(-A); IP67, 12 VDC.	4.700ден

HDCVI 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HDW1800TL-A - 2.8mm 4K Real-time HDCVI IR Eyeball Camera Max. 4K resolution, real-time video transmission, Built-in mic (-A), Max. IR length 30mCVI/CVBS/AHD/TVI switchable, Smart IR, IP67, 12V±30%DC	3.999ден
	DAHUA HAC-HFW1800TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera ax. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	3.890ден
	DAHUA HAC-HFW1801TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	4.065ден
	DAHUA HAC-HFW1800TH-I8 – 3.6mm 4K Real-time HDCVI IR Bullet Camera Max. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	4.220ден
	DAHUA HAC-HFW1801TH-I8 - 3.6mm 4K Starlight HDCVI Fixed IR Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt;CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC.	4.700ден
	DAHUA HFW1801R-Z-IRE6 with Audio2.7-13.5mm 4K 8MP HDCVI IR Bullet Camera 120dB true WDR, 3D NR Max. 4K resolution, CVI/CVBS/AHD/TVI switchable,Auto focus, Motorized lens,Max. IR length 60m, smart IR, IP67, 12V ±30% DC	7.120ден
	DAHUA HAC-HFW2802TU-A – 3.6mm 4K Starlight HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; Starlight, 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	7.030ден

HDCVI Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA SD49225DB-HC 2MP 25x Starlight IR HDCVI PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25× optical zoom; Starlight technology; 120 dB true WDR, 3D NR; Max. 25/30 fps@1080p, 25/30/50/60 fps@720p; IR distance up to 100 m; IP66;	23.970ден

Specialized Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HFW7442H-ZFR 4MP IR Bullet WizMind Network Camera Max outputs 4MP (2688 × 1520) @50 fps/60 fps; 12V DC power output; 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition;	
	DAHUA TPC-BF5421-T Thermal Network Hybrid Bullet Camera Vanadium oxide uncooled focal plane detector; Built-in white light and speaker; Features temperature measurement; Micro SD memory, IP67, PoE, ePoE	
	DAHUA JQ-D70Z Thermometric Blackbody	
	DAHUA ITC413-PW4D Series Dahua Access ANPR Camera High-performance CMOS image sensor and processor that supports continuously extracting metadata 24/7; Easily adapts to scenarios through its motorized vari-focal lens; Adopts intelligent deep learning algorithms and supports recognition of unlicensed vehicles and the type, brand and color of vehicles;	36.900ден

Digital Video Recorder Up to 2MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA XVR1B04-I 4 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth	4.065ден
	DAHUA XVR1B08-I 8 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth;	5.000ден
	DAHUA XVR1B16-I/T 16 Channel Penta-brid 1080N/720p Compact 1U WizSense 16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; 16-channel SMD Plus for analog channels or 18-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles; Supports up to 18-channel IP camera input and each channel can be up to 6 MP.	9.800ден

Digital Video Recorder Up to 6MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA XVR5104HS-I3/T 4CH Penta-brid 5MP Compact 1U WizSense Digital Video Recorder 4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 6-channel IP camera input and each channel can be up to 6 MP; The incoming bandwidth reaches 32 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	7.500ден
	DAHUA XVR5108HS-I3/T 8CH Penta-brid 5MP Value/1080P Compact 1U 1HDD WizSense Digital Video Recorder 8-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 12-channel IP camera input and each channel can be up to 6MP; The incoming bandwidth reaches 64 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	11.000ден
	DAHUA XVR5116HS-I3/T – WizSense 16 Channel Penta-brid 5M-N/1080P Compact Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus; IoT & POS functionalities	15.400ден
	DAHUA XVR5232AN-I3/T 32 Channels Penta-brid WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; IoT & POS functionalities.	33.700ден

Digital Video Recorder Up to 8MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA XVR5104HS-4KL-I3 4 Channel Penta-brid 5MP Compact 1U WizSense Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 8 channels IP camera inputs, each channel up to 8MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus;	9.840ден
	DAHUA XVR5104HS-4KL-I3/T 4CH Penta-brid 4K Value/5MP Compact 1U 1HDD WizSense Digital Video Recorder 4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 8-channel IP camera input and each channel can be up to 8MP; The incoming bandwidth reaches 64 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	10.700ден
	DAHUA XVR5108HS-4KL-I3 - WizSense 8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;	13.950ден
	DAHUA XVR7108H-4K-I3 8 Channels Penta-brid 4K Mini WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	16.050ден
	DAHUA XVR5116H-4KL-I3 16 Channels Penta-brid 4K-N/5MP Mini 1U WizSense H.265+/H.265 dual-stream video compression; · Supports Full-channel AI-Coding; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	29.490ден
	DAHUA XVR5216A-4KL-I3 16 Channels Penta-brid 4K-N/5MP 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	ден
	DAHUA XVR7216AN-4K-I3 16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports 16-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP ; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Up to 16 channels video stream SMD plus;	42.250ден
	DAHUA XVR5232AN-4KL-I3/T 32 Channels Penta-brid 4K-N/5MP WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression.; Supports 32-channel AI-Coding.; Supports HDCVI/AHD/TVI/CVBS/IP video inputs.; Max 32 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	55.000ден

Hard Disk Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	HDD 1TB	ден
	HDD 2TB	ден
	HDD 4TB	ден
	HDD 6TB	ден
	HDD 8TB	ден

Memory Card & USB Flash Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DHI-TF-C100/64GB microSD Memory Card	900ден
	DHI-TF-C100/128GB microSD Memory Card	1.300ден
	DHI-TF-C100/256GB microSD Memory Card	2.000ден
	DHI-USB-P629-32-64GB USB Flash Drive	650ден
	DHI-USB-P629-32-128GB USB Flash Drive	1.000ден
	DHI-USB-P629-32-256GB USB Flash Drive	2.000ден

IPC Smart-Dual Light 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-B1E29-A-IL 2MP ECO Smart Dual Light Fixed-focal Bullet Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE; IP67 protection;	3.380ден
	DAHUA IPC-T1E29-A-IL 2MP ECO Smart Dual Light Fixed-focal Eyeball Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE; IP67 protection;	3.380ден
	DAHUA IPC-HDBW1239E1-A-IL 2MP Entry Smart Dual Light Fixed-focal Dome Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.; Outputs max. 2 MP (1920 × 1080)@25/30 fps; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 and IK08 protection; Supports human detection;	4.200ден
	DAHUA IPC-PT1239H-PV 2MP Smart Dual Light Active Deterrence Network PT Camera 1/2.8" 2Megapixel CMOS; Max. 25/30 fps@2MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way Talk; Easy App Controls;	4.250ден

IPC 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HDW2230T-AS-S2 2MP Lite IR Fixed-focal Eyeball Network Camera 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2MP (1920 × 1080)@25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Max. 256 G micro SD card; built-in MIC; 12V DC/PoE power supply; IP67 protection;	2.790ден
	DAHUA IPC-T1E20-A 2MP ECO IR Fixed-focal Eyeball Network Camera 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Built in Mic; 12 VDC power supply; IP67protection;	ден
	DAHUA IPC-B1E20-A 2MP ECO IR Fixed-focal Bullet Network Camera 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30; Built in Mic; 12 VDC power supply; IP67 protection;	2.680ден
	DAHUA IPC-HDBW1230E - 2.8mm 2MP IR Mini-Dome Network Camera 1/2.7" 2Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding; 25/30fps@1080P(1920x1080); Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring; 2.8mm fixed lens; Max IR LEDs length 30m; IP67, IK10, PoE	4.370ден
	DAHUA IPC-HDBW5241R-ASE 2MP IR Fixed-focal Dome WizMind Network Camera Outputs max. 2MP (1920x1080) @25/30fps; Built-in IR LED, and the max. illumination distance is 50 m; With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc; IP67 and IK10 protection; SMD 3.0;	10.900ден

	DAHUA IPC-HDBW5241E-ZE 2MP IR Vari-focal Vandal-proof Dome WizMind Network Camera Outputs max. 2MP (1920×1080) @25/30 fps; Built-in IR LED, and the max. illumination distance is 40 m; With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting; ePoE; IP67 and IK10 protection; SMD 3.0;	13.990ден
	DAHUA SD22204UE-GN – Lite Series 2MP 4x Starlight PTZ Network Camera 1/2.8" STARVIS™ CMOS; Powerful 4x optical zoom; Day/Night(ICR), Ultra DNR; Max. 25/30fps@1080P; Max 100°/s pan speed · IVS Support PoE; IP66, IK10	14.140ден

IPC 4MP Full-Color/Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-B1E49-A-IL 4MP ECO Smart Dual Light Fixed-focal Bullet Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2560 × 1440)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE power supply, easy for installation; IP67 protection; Supports human detection;	4.590ден
	DAHUA IPC-HDBW1439E1-A-IL 4MP Entry Smart Dual Light Fixed-focal Dome Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs Max. 4 MP (2560 × 1440)@25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, IP67 and IK08 protection;	5.235ден
	DAHUA IPC-PT1439H-PV – 2.8mm 4MP Smart Dual Light Active Deterrence Network PT Camera 1/2.8" 4Megapixel CMOS; Max. 25/30 fps@4MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way Talk; Easy App Controls;	5.165ден

IPC 4MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-T1E40-A - 2.8mm 4MP ECO IR Fixed-focal Eyeball Network Camera MP 1/3" CMOS image sensor, low luminance, and high definition image.; Outputs max. 4 MP (2560 × 1440)@30 fps; H.265 codec, high compression rate, ultra-low bit rate; and the max. illumination distance is 30 m; ROI, SMART H.264+/H.265+; Bulit in Mic; IP67 protection;	3.380ден
	DAHUA IPC-HFW1431T-ZS-S4 4MP Entry IR Vari-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 50 m; 12V DC/PoE power supply;	8.500ден

IPC 4MP WizColor Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HDBW2449E-S-IL 4MP Smart Dual Light Fixed-focal Dome WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560 × 1440@25/30 fps; Built-in IR LED and warm light, the max. IR illumination distance is 30 m and the max. warm light distance is 30 m. 12 VDC/PoE power supply, easy for installation; IP67, IK10 protection; SMD Plus;	7.860ден
	DAHUA IPC-HDW2449T-S-PRO 4MP WizColor Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps; Built-in warm light, and the max. illumination distance is 30m; Supports max. 256 G MicroSD card; built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; SMD Plus;	8.120ден
	DAHUA IPC-HFW2449TL-S-PRO 4MP WizColor Fixed-focal Bullet WizSense Network Camera 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Built-in warm light, and the max. illumination distance is 50 m; Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict; Supports max. 256 G Micro SD card; built in Mic;	8.120ден
	DAHUA SD2C400NA-B-PV-PRO 4MP WizColor WizSense Network PT Camera 1/1.8" 4Megapixel STARVIS™ CMOS; WizColor technology; Max. 25/30 fps@4MP; H.265 encoding; SMD3.0; Perimeter protection; Two-way Talk; Auto Tracking(Lite); Preset Patrol; IP66 protection;	9.085ден

IPC 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HFW2541E-S - 3.6mm 5MP IR Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, high definition image; Outputs max. 5 MP (2592 × 1944) @20 fps; Abnormality detection: Motion detection, video tampering, scene changing, audio detection, IP conflict, illegal access, and voltage detection	7.540ден
	DAHUA IPC-HDBW5541R-ASE 5MP IR Fixed-focal Dome WizMind Network Camera MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960×1668) @25/30 fps; Built-in IR LED, and the max. illumination distance is 50 m; th deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting;	13.110ден

IPC 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HFW2549S-S-IL 5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	8.110ден

IPC 6MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HDW1639T-A-IL 6MP Smart Dual Light Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP@20 fps, and supports 2688 × 1520@25/30fps; Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	5.500ден
	DAHUA IPC-HFW1639TC-A-IL 6MP Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6MP @20 fps, and supports 2688 × 1520@25/30 fps; H.265 codec, Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	5.500ден

8MP Wiz-Color IPC Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HFW2849TL-S-PRO 8MP WizColor Fixed-focal Bullet WizSense Network Camera 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm light, and the max. illumination distance is 50 m; Supports max. 256 G Micro SD card; built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; SMD Plus;	10.990ден
	DAHUA IPC-HFW2849M-S-B-PRO 8MP WizColor Fixed-focal Bullet WizSense Network Camera 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@20 fps, and supports 4 MP (2688 × 1520)@25/30 fps; Built-in warm light, and the max. illumination distance is 50 m; Supports max. 256 G Micro SD card; built in Mic; 12 VDC/PoE power supply; IP67 protection;	10.990ден
	IPC-PT2849C1-S-PV-PRO 8MP WizColor Active Deterrence WizSense Network PT Camera 1/1.8" 8 Megapixel CMOS; WizColor Technology; Max. 20 fps@8MP; H.265 Encoding; SMD 3.0; Perimeter Protection; Two-way Talk; Auto Tracking Lite; Tour; IP66 Protection;	ден

IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA IPC-HDW1839T-A-IL 8MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; Supports human detection;	6.700ден
	DAHUA IPC-HFW1839TC-A-IL 8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; . 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection.; Supports human detection;	6.700ден
	DAHUA IPC-HDW2849TM-S-IL 8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 8-MP 1/2.7" CMOS image sensor and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, Illumination distance is 30 m and the max. warm light distance is 30 m;	8.900ден

IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA HDBW2841R-ZAS 8MP IR Vari-focal Dome WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding;	13.185ден
	DAHUA IPC-HFW2831S-S-S2 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	7.640ден

	DAHUA IPC-HFW2831T-AS-S2 3.6mm 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	9.570ден
	DAHUA IPC-HFW2841T-AS 8MP IR Fixed-focal Bullet WizSense Network Camera Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps. Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	9.130ден
	DAHUA IPC-HFW2841T-ZAS 8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	12.870ден
	DAHUA IPC-HFW2831TP-ZS – Lite Series 8MP WDR IR Bullet Network Camera 1/1.8" 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	13.230ден
	DAHUA IPC-HFW3849T1-AS-PV-S3 8MP Smart Dual Illumination Active Deterrence Bullet Camera 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m; Alarm: 1 in, 1 out; audio: 1 in, 1 out;	15.990ден
	DAHUA IPC-HFW3849T-ZAS-IL 8MP Smart Dual Light Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; light, the max. IR distance is 60 m and the max. warm light distance is 60 m; toring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human), stay detection, loitering detection, face detection (full image); 12 VDC/PoE power supply; IP67, IK10 (optional, IEC 62262:2002) protection; SMD 4.0; Supports AI SSA;	14.590ден

IPC Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA SD4A425DB-HNY 4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@4MP; IR distance up to 100 m; Auto-tracking 1.0; Perimeter protection.; Face detection; SMD 3.0; IP66;	32.000ден
	DAHUA SD5A225GB-HNR 2MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25x optical zoom; Max.50/60fps@2M; IR distance up to 150 m; Auto Tracking 3.0; Face Detection; SMD 4.0; PoE+; IP67, IK10	35.850ден
	DAHUA SD5A232GB-HNR 2MP 32x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; 32x optical zoom.; Starlight technology; Max.50/60fps@2M; IR distance up to 150 m; Auto-tracking 3.0; Perimeter protection; Face detection; SMD 4.0; IP67, IK10;	48.800ден
	DAHUA SDT4E425-4F-GB-A-PV1 X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera 1/2.8" 4Megapixel F1.0 CMOS; Detail: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30fps@4M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	39.120ден
	DAHUA SD5A445GB-HNR 4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ CMOS; 45x optical zoom; Starlight technology; Max. 25/30fps@4M; IR distance up to 150 m; Auto-tracking 3.0; Perimeter protection; Face detection; SMD 4.0; IP67, IK10;	62.350ден
	DAHUA SDT4E425-8P-GB-APV1 8+4MP 25x TiOC Network Panoramic PTZ Camera Overview channel: Outputs 180° wide angle splicing image; Detail channel: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30 fps@8M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	48.850ден
	DAHUA SD49825GB-HNR 8MP 25x Starlight IR Network PTZ Camera 1/2.8" 8Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@8M; IR distance up to 100 m; Perimeter protection; Face detection ; SMD 4.0; IP66;	43.000ден
	DAHUA IPC-PFW8802-A180 4x2MP Multi-Sensor Panoramic IR Bullet Network Camera Four 1/1.9" 2Megapixel progressive scan CMOS; H.265/H.264 triple-stream encoding; Support 180-degree panoramic view; Day/Night(ICR), 3DNR, AWB, AGC, BLC, WDR; Smart detection; Max. IR LEDs length 30m; Micro SD memory, IP67, IK10,PoE+	42.000ден

IPC 2MP/4MP Wi-Fi Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA H5A 5MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	3.450ден
	DAHUA H4C 4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	3.450ден
	DAHUA SD1A203T-GN-W – IR-15m 2MP 3x Starlight IR PTZ Wi-Fi Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS , Powerful 3x optical zoom, Starlight, WDR, Max. 5/30fps@1080P, IVS, Support Wi-Fi, IP66	7.500ден

IPC Wi-Fi Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA F4C-LED 4MP Fixed-focal Wi-Fi Full-Color Bullet Network Camera AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	3.700ден

IPC Wi-Fi Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA DH-T3A-IL 3MP Fixed-focal Wi-Fi Turret Network Camera 3MP Clear images with sharp details; AI Human Detection; AI Vehicle Detection; Built-in Mic; Smart Dual Light; IP67 Protection; Wi-Fi 6; H.265; Bluetooth Pairing; DMSS App; Supports Micro SD Card;	3.990ден
	DAHUA DH-T5A-IL 5MP Fixed-focal Wi-Fi Turret Network Camera 5MP Clear images with sharp details; AI Human Detection; AI Vehicle Detection; Built-in Mic; Smart Dual Light; IP67 Protection; Wi-Fi 6; H.265; Bluetooth Pairing; DMSS App; Supports Micro SD Card;	3.990ден
	DAHUA F4C-PV 4MP Fixed-focal Wi-Fi Smart Dual-Light Bullet Network Camera AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology; Built-in warm light and IR LED, and the max. illumination distance is 30 m.	3.800ден
	DAHUA F5D-PV 5MP Fixed-focal Wi-Fi Bullet Network Camera Clear images with sharp details; Sound and Light Alarm; AI Human Detection; AI Vehicle Detection; Two-way Talk; IP67 Protection; Red and Blue Warning Light; H.265; Wi-Fi 6; Bluetooth pairing; Supports Micro SD Card; DMSS App;	3.990ден
	DAHUA P5I-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 5MP; Sound and Light Alarm; Smart Dual Light; Auto Tracking; AI Human Detection; AI Vehicle Detection; IP66 Protection; Two-way Talk; H.265; Bluetooth Pairing; Wi-Fi 6; Supports Micro SD Card;	4.500ден

	DAHUA P5AS-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 5MP; Sound and Light Alarm; Red and Blue Warning Light; AI Human Detection; AI Vehicle Detection; Auto Tracking; Preset Patrol; Wi-Fi 6; One Camera for 360° View; Smart Dual Light; Bluetooth Pairing;	4.700ден
	DAHUA P5B-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 360° monitoring without blind spots; Sound and Light Alarm Provides instant alarms to deter intruders; AI Human Detection; AI Vehicle Detection; Auto Tracking; Fast pairing with Bluetooth; Seamless integration of speed and anti-interference; Two-way audio;	5.450ден
	DAHUA P5F-PV 5MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera 5MP, Beyond Sharpness; Sound and Light Alarm; Auto Tracking; AI Human Detection; AI Vehicle Detection; Preset Patrol; IP66 Protection; Two-way Talk; Bluetooth Pairing; Wi-Fi 6; DMSS App; H.265;	6.990ден
	DAHUA P8F-PV 8MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera 4K Ultra HD, Beyond Sharpness; Sound and Light Alarm; Auto Tracking; AI Human Detection; AI Vehicle Detection; Preset Patrol; IP66 Protection; Two-way Talk; Bluetooth Pairing; Wi-Fi 6; DMSS App; H.265;	7.500ден
	DAHUA P5D-5F-PV 5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera Dual Channel Smart Detection; AI Human Detection; Dual 3K; Dual-lens, Double Vision; Adjustable Dual-lens Angles; Auto Tracking; Preset Patrol; IP66 Protection; Smart Dual Light; Sound and Light Alarm; Bluetooth Pairing; Wi-Fi 6; H.265;	7.000ден

Solar and 4G Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA BP3EW-4G APOLLO 4G Solar Security System 3MP; Full-color; Long-lasting Power, Non-stop Protection; AI Precise Detection with Quick Wake Up; AOV (Always-On Video) Mode; Sound and Light Alarm; Two-way Talk; 4G Connection; H.265; IP66 Protection; Supports Micro SD Card;	8.560ден
	DAHUA P4F-PV-4G 4MP Outdoor Wizcolor Fixed-focal 4G Pan & Tilt Network Camera 4G Connection; One Camera for 360° View; AI Human Detection; AI Vehicle Detection; Sound and Light Alarm; Two-way Talk; Auto Tracking; IP66 Protection; Supports Micro SD Card;	9.040ден
	DAHUA BF4CA-4G-XL/ M0508-K 4MP 4G Battery Bullet Network Camera Solar Monitoring System Long-lasting Power, Non-stop Protection; AI Precise Detection with Quick Wake Up; AOV (Always-On Video) Mode; Sound and Light Alarm; Smart Dual Light; 4G Connection; Supports Micro SD Card; IP66 Protection;	9.990ден

Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA NVR2116-S3 16 Channel Smart 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding ; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;	5.500ден
	DAHUA NVR4104HS-EI 4CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 80 Mbps; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	9.330ден
	DAHUA NVR4104HS-P-4KS3 4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps or 4 × 4 MP@30 fps; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; Supports EPTZ, and one-click arming and disarming;	11.400ден
	DAHUA NVR4104HS-P-4KS3(960GB) 4CH Compact 1U 4PoE 1SSD 960GB Lite Network Video Recorder Comes with an internal 960GB SSD; Max. decoding capability: 8 × 1080p @30 fps or 4 × 4 MP@30 fps; Max. 80/80/60 Mbps incoming/ recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map;	14.950ден
	DAHUA NVR4108HS-EI 8CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	11.500ден
	DAHUA NVR4108HS-8P-EI 8CH Compact 1U 8PoE 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus;	17.200ден
	DAHUA NVR4208-8P-4KS2/L 8 Channel 1U 2HDDs 8PoE Network Video Recorder New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD; Supports remote configuration and management of IPC, such as set ting parameters	10.400ден
	DAHUA NVR4116HS-EI 16CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	14.600ден

	DAHUA NVR4116-8P-4KS2/L 16 Channel Smart 1U 1HDD 8PoE Network Video Recorder New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device;	11.200ден
	DAHUA NVR4216-16P-EI 16CH 1U 16PoE 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	28.780ден
	DAHUA NVR5216-8P-4KS2E 16 Channel 1U 8PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 · Max 320Mbps Incoming Bandwidth · Up to 12MP Resolution for Preview and Playback; HDMI/VGA simultaneous video output; All PoE ports support ePoE & EoC; Point of Sale (POS); ANPR; Fisheye Dewarping;	19.990ден
	DAHUA NVR5216-16P-EI 16CH 2HDD 1U NETWORK VIDEO RECORDER Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30 fps; Supports IP cameras with a resolution up to 32 MP; Supports AcuPick with up to 16 channels; Provides access to remote storage devices via iSCSI to expand storage capacity	38.500ден
	DAHUA NVR4816-16P-4KS2/I 16 Channel 2U 16PoE 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Storage or forwarding at 256 Mbps (160 Mbps when AI function enabled); Max. decoding capability: 10 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting; Support IPC UPnP, 16PoE ports;	29.600ден
	DAHUA NVR5816-R-4KS2 16 Channel 2U 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Max 320Mbps Incoming Bandwidth; Supports RAID 0/1/5/10; Up to 12MP Resolution for Preview and Playback; 2HDMI/2VGA simultaneous video output; ANPR by Camera; Automatic Network Replenishment (ANR) Technology; Fisheye Dewarping; Smart Fan;	29.700ден
	DAHUA NVR4232-EI 32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection and recognition, perimeter protection;	17.400ден
	DAHUA NVR5232-EI2 32 Channels 1U 2HDDs WizSense Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; AI by Recorder; AI by Camera; Supports EPTZ, and one-click arming and disarming;	32.000ден
	DAHUA NVR5464-EI 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps	45.000ден


	incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel;	
	DAHUA NVR5464-EI2 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	55.900ден
	DAHUA NVR5864-EI2 64CH 2U 8HDDs WizSense Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	78.120ден

Wireless Alarm System

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ART-ARC3000H-03-GW2(868) – Alarm KIT Supports 150 wireless peripherals Peripherals status display (signal strength, battery level, temperature, program version) Wired, Wi-Fi or GPRS network connection; Dual SIM and Single Standby, auto switching; Automatic network replenishment (ANR); Video linkage on App SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	18.000ден
	DAHUA ART-ARC3800H-03-FW2 Dahua Wireless Alarm KIT Supports alarm video verification through integration of the IPC with the hub; Features voice call alarm; Supports wired and AP network configuration methods, which makes it easier to add the hub to apps and to switch to the hub's network; Supports multi-network redundancy for Ethernet, Wi-Fi and 4G networks to ensure the network remains stable and reliable;	19.500ден
	DAHUA ARD1233-W2 - Wireless PIR detector Pet immunity function; Auto temperature compensation; 3-level sensitivity adjustment; Low battery alarm; Anti-tampering; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability;	2.900ден
	DAHUA ARA33A Detector Bracket	390ден
	DAHUA ARD1731-W2 Wireless PIR-Camera Maximum resolution 1600*1200; Based on the RF-HD image transmission technology, transmission of 6 HD images with resolution of 1600*1200 needs up to 10 seconds; One-week cloud cache for videos and images; Temperature monitoring;	7.600ден
	DAHUA ARD323-W2 - Wireless door detector Signal strength detection; Low battery alarm; Temperature measurement Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure	2.090ден
	DAHUA ARA13-W2 - Wireless outdoor siren IP65 rated; Outdoor product (–25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	6.800ден
	DAHUA ARA12-W2 - Wireless siren Signal strength detection; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure.	3.320ден
	DAHUA ARA24-W2 Wireless keyfob SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	1.700ден
	DAHUA ARK30T-W2 - Wireless Keypad Supports 3 shortcut alarms: Medical, fire, emergency; Arm/Disarm with password or IC card; Supports signal strength detection to select suitable installation sites; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication; Cloud update and automatic recovery from update failure.	4.640ден
	DAHUA ARD821-W2 - Wireless Panic Button Two-way RF communication; Provides multiple LED colors to indicate different statuses; Cloud update and automatic recovery from update failure; Offers accidental press prevention; Battery life up to 5 years if used twice a week; IP54 rated	1.960ден

	DAHUA ARM310-W2 - Wireless input expander Six types of alarm: intrusion, medical, fire, emergency, gas, and tamper; NC and NO are available for alarm inputs (NO by default); Signal strength detection; Low battery alarm; Temperature monitoring; Frequency hopping function and two-way communication technology ensure communication stability;	2.240ден
	DAHUA ARD912-W2(868D) Wireless Water Leak Detector Frequency hopping and two-way communication technology ensure that communication is stable; Displays the temperature of the surrounding environment and supports the overheating alarm; Sensitivity adjustment;	3.500ден
	DAHUA ICS1-W2-868 Smart Plug Two-way RF communication; Displays the status with an LED indicator; Offers protection against overcurrent, overvoltage, and overheating; Measure the voltage, current and temperature;	2.870ден
	DAHUA ARM7011-W2 Dahua Wireless Relay Frequency hopping and two-way communication technology ensure that communication is stable; Supports jamming detection and communication encryption. Supports cloud update and automatically restores when cloud update fails.	2.130ден
	DAHUA HY-RI151 LED Remote Indicator	360ден
	DAHUA ARA43-W2 - Alarm Repeater Connects up to 32 peripherals; Two-way RF communication; LED indicator displays device status; Supports auto pairing, extending RF distance for your security system; Auto switches from dual antennas to reduce blind area; Battery backs device working for over 35 hours	6.000ден
	DAHUA HY-SA21A-W2(868) Wireless Smoke Alarm Split-spectrum sensor technology; Test and silence features in one single button; Loud sound output over 85 dB(A) at 3 meters; Low quiescent current consumption; Surface-mount device (SMD) circuit board design; Low battery warning signal	4.080ден
	DAHUA HY-SAV849HA-E 5MP IR AI-fire Smoke Sensing Network Camera Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices, and user can import custom voices; 2/2 Alarm in/out, 1/1 audio in/out;	ден
	DAHUA ARM9A4-W2(868) Dahua Wireless Multi IO Transmitter Connection to Hub through RF communication; 16 alarm inputs, 4 relay outputs; 2 auxiliary power outputs with a maximum power of 24W for powering wired detector and siren, and support overload and short circuit detection; AC power and rechargeable battery (optional) two power supply options;	11.380ден

Professional Monitoring Dahua Monitor

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	21.45" FHD Monitor DHI-LM22-H200 Suitable for continuous 24/7 operation; Ultra-thin body with metal housing; Micro bezel design, elegant appearance, ultra-light base; 178°H/178°V extra-wide viewing angle for overall viewing performance;	9.620ден
	27" FHD Monitor DHI-LM27-B200S Light and cost-effective plastic housing; Ultra-narrow bezel , elegant appearance, Metal base; 178°H/178°V extra-wide viewing angle for overall viewing performance; Anti-blue light design, eye-protective; Low energy consumption, long service life;	9.390ден
	27" Monitor DHI-LM27-C200 The 1920*1080 resolution produces clearer and more vivid pictures; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB. It meets the designer's demand of image texture; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB.	9.480ден
	32" FHD Monitor DAHUA LM32-F200 Light and cost-effective plastic housing · suitable for continuous 24/7 operation · 178°H/178°V extra-wide viewing angle for overall viewing performance; · Built-in speakers; Physical button and infrared remote dual control mode	17.390ден
	43" FHD Monitor DHI-LM43-F200 Light and cost-effective plastic housing; suitable for continuous 24/7 operation; 178°H/178°V extra-wide viewing angle for overall viewing performance; High fidelity digital processing for a brilliant and vivid video; 8ms fast response time	20.150ден
	43" FHD Monitor DHL43-F600 Industrial level LCD panel, suitable for continuous 24/7 operation · Physical resolution of 1920×1080 · High fidelity digital processing for a brilliant and vivid video · 5ms fast response time for no motion blur, judder or ghosting	26.650ден
	Bracket for monitor TV 14" - 42"	500ден
	Bracket for monitor TV 26" - 63"	650ден
	Bracket for monitor TV 26" - 63"	1.050ден

IPC Wi-Fi 2MP Smart Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	M-WJ01 TuYa Smart 1080P 2.0MP Wifi Super Mini Camera APP name:TuYaSmart; Standard Lens: 2.4mm; H.264 Real time; Support Monitor; Support Android & Iphone Mobile View; Night vision distance: 5-8M; 5V, 1A;Maximum support 64G TF card;Support ONVIF, can work with NVR	3.500ден
	VR 2MP IP Panoramic Fisheye PTZ camera H.264 Compression,Dual Stream(0.1M-8Mbps); LED:4pcs LED 30M (With IR CUT), Fisheye 1.44mm 185° Lens ; WIFI: 3DB Antenna;; Motion Dectction, Alert Action, CMS For PC; Audio: Built-in 45DB Microphone; Built-in 8 Assault 2-Watt Speakers; Built in Antenna; Without RJ45 Port; White Light LED	2.000ден
	IPW-THS-901 WiFi Smart PT Camera Indoor Support 1080P/3MP/5MP Video Record/View; Built-in 4pcs Array IR Led; IR Distance More than 5~10 Meters; Simple installation; 360 degree panoramic picture; Two Way Audio(Built-in Mic, Louder speaker);H.265/H.264 HD High Profile image decoding;Pan Rotation:355°,TiltRotation:75°;	3.500ден
	2MP Camera TV 288ZD Wireless WiFi with AUTO TRACKING Image sensor: GC1034 Video: Image sensor: 2MP/1080P Image coding standard: Smart H.264+, Monitor image quality: 1280*720/640 * 360 private cloud WIFI Networking, AP hotspot added Extension: IR-CUT, TF Card: maximum support for 128GB TF CardWIFI: support. Lens: 3.6mm.	2.300ден
	1080PDual CarCamera Color: Black; Material: ABS; Display: 2 Inch IPS Screen; Camera: 1080P Front Camera + 480P Inside Camera + 480P Rear Camera; View Angle: 140° Front + 90° Inside + 90° Rear; Loop; Date Stamp: Support; Memory Card: Max. 128G(Not Included); Battery: Built-in 150mAh Lithium Battery; Current Frequency: 50/60Hz; Power: 5V, 1.5-2A;Photo Format: JPEG; File Format: MOV	3.450ден

Accessories

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DH-PFM906 Integrated Mount Tester Supports IPC, HDCVI, AHD, HDTVI, CVBS and SDI monitor video display; HDMI input and output; 12 VDC 2A and USB 5V 2A output; 7-in 1080p HD full-angle retina capacitive IPS touchscreen; TDR network cable test and cable tracker function; Optical power meter function	
	DAHUA PFT1300 PoE Extender Support passive PoE cascade power supply and Ethernet data exchange; Support IEEE 802.3af/at standard power supply IP Camera;	2.500ден
	DAHUA PFM800-4K 1-CH Passive Video Balun	450ден
	Balun 1CH Video 4K-8MP	300ден

Ethernet Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA SF1005L 5-Port Unmanaged Ethernet Switch Supports five 10/100 Mbps adaptive ports; Small and light, it is easy to carry and has multiple chips embedded in it; Easy to operate;	700ден
	DAHUA SF1008L 8-Port Unmanaged Ethernet Switch Supports eight 10/100 Mbps adaptive ports; Small and light, it is easy to carry and has multiple chips embedded in it; Easy to operate;	990ден

Wireless Access Point

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA EAP5212-C AC12 Ceiling Mount Access Point Up to 1.2 Gbps wireless speed; Supports dual concurrent wireless networks; Offers seamless roaming; MU-MIMO technology delivers a fast wireless network that can be accessed by multiple devices at the same time;	5.450ден

Wireless Routers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA N3 N300 Wireless Router The wireless speed reaches up to 300 Mbps for IEEE 802.11n, allowing smooth internet access; 1 × WAN port and 3 × LAN ports that expand network coverage; Two external antennas offer a wider signal coverage;	1.400ден
	DAHUA AC12 AC1200 Wireless Router 1.2 Gbps Wireless Speed(300 Mbps@2.4 GHz, 867 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac standard); Beamforming for better Coverage; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2); Guest Wi-Fi;	2.500ден
	DAHUA AX15M AX1500 Wireless Router 6th Gen Wireless Technology; 1.5 Gbps Wireless speed (300 Mbps@2.4 GHz, 1201Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3); Guest Wi-Fi;	2.945ден
	DAHUA AX30 AX3000 Wireless Router 6th Gen Wireless Technology; 3 Gbps Wireless speed (574 Mbps@2.4 GHz, 2402 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); 160 MHz channel width; Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3);	5.540ден
	DAHUA MAX18-3 Pack of 3 Mesh Wireless Router Offers wireless access and high bandwidth; 1 gigabit WAN port and 2 gigabit LAN ports; Easily switches between LAN and WAN; Supports accessing 1000 Mbps optical fiber broadband; Supports being managed through the WiLynk app	14.990ден

Unmanaged Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	MV-1010B Port: 8 POE * 100Mbps + 2 RJ45 * 100Mbps; Power Supply Protocol: IEEE802.3AF/AT, maximum output 30W per port; Backplane Bandwidth: 2.0Gbps; Total Power: 52V 120W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN function.	4.000ден
	MV-1011GB Port: 8 POE * 100Mbps + 2RJ45*1000Mbps +1*1000Mbps-SFP; Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 7.6Gbps; Total Power: 52V 120W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	7.300ден
	MV-16F22GB Port: 16 POE * 100Mbps + 2RJ45*1000Mbps +2*1000Mbps-SFP; Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 11.2Gbps; Total Power: 52V 250W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	12.500ден
	MV-24F22GB Port: 24 POE * 100Mbps + 2RJ45*1000Mbps +2*1000Mbps-SFP; Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 12.8Gbps; Total Power: 52V 320W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	15.700ден
	DAHUA CS4006-4ET2GT-36 6-Port Cloud Managed Desktop Switch with 4-Port PoE Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards; Meets the requirements of IEEE802.3af, IEEE802.3at power supply standards; Manages PoE power consumption and PoE power on/off.	3.120ден
	DAHUA PFS4006-4ET-60 6-Port 10/100Mbps Unmanaged Desktop Switch with 4 PoE Ports Layer two commercial switch; Supports IEEE802.3, IEEE802.3u, IEEE802.3ab and IEEE802.3x standards; MDI/MDIX self-adaptation; RJ-45 port supports 10/100 Mbps self-adaptation, and conforms to 802.3at, and 802.3af power supply standards; Port 1 supports Hi-PoE 60W power supply; 250m PoE power supply;	3.650ден
	DAHUA SF1010LP 10-Port Fast Ethernet Switch with 8-Port PoE Support eight 10/100M; PoE power supply ports, and two 10/100M uplink ports; Support 802.3af and 802.3at standards; Operating Temperature: -10°C to +55°C; Support 250 m long distance PoE transmission; Support PoE watchdog	4.960ден
	DAHUA CS4010-8ET2GT-60 10-Port Cloud Managed Desktop Gigabit Switch with 8-Port PoE 8 × RJ-45 Gigabit PoE ports, 2 × RJ-45 Gigabit ports; 60 W total PoE budget, 802.3af/at on all PoE ports, additional Hi-PoE on orange port; h to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, 250 Meter Long Distance PoE;	4.490ден
	DAHUA PFS3110-8ET-96 8-Port PoE Switch (Unmanaged) Layer two Hardened PoE switch; Supports PoE power management; MAC auto learning and aging, MAC address capacity is 8K; Conforms to IEEE802.3af and IEEE802.3at power supply standard; Port 1-2 supports Hi-PoE 60W power supply; Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards;	6.945ден

	DAHUA S3016-16GT 16-Port Unmanaged Gigabit Switch 16 × RJ-45 10/100/1000 ports; The all-gigabit ports transmit data without lag; Features aggregation mode which aggregates uplink ports; Features isolation mode which isolates all the ports from each other; With its solid full metal design, the device has great heat dissipation and no fan;	4.665ден
	DAHUA S3218-16ET-135 18-Port Unmanaged Desktop Switch with 16-Port 16 × RJ-45 10/100 Mbps (PoE) ports, 2 × RJ-45 10/100/1000 Mbps ports and 2 × SFP 1000 Mbps ports; Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt; PoE watchdog real-time monitors camera statuses and automatically reboots faulty network cameras; Up to 250m transmission distance	10.850ден
	DAHUA S3024-24GT 24-Port Unmanaged Gigabit Switch 24 × RJ-45 10/100/1000 ports; The all-gigabit ports transmit data without lag; Features aggregation mode which aggregates uplink ports; Features isolation mode which isolates all the ports from each other;	6.390ден
	DAHUA S3226-24ET-240 26-Port Unmanaged Switch with 24-Port PoE Intelligent PoE; PD Alive(PoE Watchdog); Long Distance PoE Transmission; Smooth Transmission; Wide Working Temperature: -10 to 55°C (14°F to 131°F)	17.730ден

Managed Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA CS4218-16ET-135 18-Port Cloud Managed Desktop Switch with 16-Port PoE Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof;	14.680ден
	DAHUA DH-PFS4218-16ET-240-V3 16-Port PoE Switch Layer 2 management PoE switch; PoE budget: 240W; Support PoE, PoE+, Hi-PoE; 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300); 250 meters long distance PoE transmission · PoE management, PoE Setting/Event Statistics/Green PoE · Search and upgrade via ConfigTool;	20.190ден
	DAHUA CS4220-16GT-135 20-Port Cloud Managed Desktop Gigabit Switch with 16-Port PoE Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof;	12.895ден
	DAHUA CS4226-24ET-240 26-Port Cloud Managed Desktop Switch with 24-Port PoE Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z standards; Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing.	17.700ден
	DAHUA PFS4226-24ET-360 24-port 100 Mbps + 2-port Gigabit Managed PoE Switch Intelligent PoE; Red port supports 90W IEEE802.3bt; Web management with friendly interface and easy operation; 250 m long distance PoE transmission; PoE watchdog;	24.840ден

	DAHUA S4228-24GT-240 28-Port Managed Desktop Gigabit Switch with 24-Port PoE Layer 2 network management PoE switch; Supports web, and network management software based on SNMP; Network redundancy: STP/RSTP. Supports IEEE802.3af, IEEE802.3at; Port 1 and port 2 support IEEE802.3bt, and are compatible with Hi-PoE; Supports PoE watchdog; Supports 250 m long-distance transmission mode;	26.690ден
	DAHUA S4228-24GT-360 28-Port Managed Desktop Gigabit Switch with 24-Port PoE Layer 2 network management PoE switch; Supports web, and network management software based on SNMP; Supports PoE power consumption management; Supports IEEE802.3af, IEEE802.3at; Supports PoE watchdog; Supports 250 m long-distance transmission mode.	34.560ден
	DAHUA S5436-24GF8GT4XF 36-Port L2+ Managed Gigabit Switch with 4-Port 10G SFP+ All-gigabit port design (10 gigabit uplink port); Supports STP, RSTP and ERPS; IEEE802.1Q-based VLAN configuration; Static link aggregation and static LACP; Easy to manage the device through the webpage; EMC compliant, the device is lightning proof; Desktop mount and rack mount;	37.230ден

Uninterruptible Power Supply (UPS)


МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA PFM350-360 Uninterruptible Power Supply 600VA/360W Line-interactive Wide input voltage range: AC81~145V or AC140~290V, meet the requirements in different parts for electric network fluctuation; Boost and buck AVR for voltage stabilization; Off-mode charging, cold start function and full protection; Continuous power supply for preventing data loss; Compact size;	6.200ден
	DAHUA PFM3350-1000 Uninterruptible Power Supply 230V - Line-interactive 1000VA/600W Comes with a wide voltage input range of 170~280 VAC, and easily adapts to fluctuations and various grid environments; Offers digital voltage stabilization; Fast charging in just 4 hours; Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	5.230ден
	DAHUA PFM3350-1500 Uninterruptible Power Supply 230V - Line-interactive 1500VA/900W Comes with a wide voltage input range of 170~280 VAC, and easily adapts to fluctuations and various grid environments; Operates quietly for a serene environment; Offers digital voltage stabilization and automatically adjusts the voltage; Fast charging in just 4 hours; Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	11.450ден
	DAHUA PFM3350-2000 Uninterruptible Power Supply 230V - Line-interactive 2000VA/1200W Comes with a wide voltage input range of 170~280 VAC, and easily adapts to fluctuations and various grid environments; Operates quietly for a serene environment; Offers digital voltage stabilization and automatically adjusts the voltage; Fast charging in just 4 hours; Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	13.170ден


Power Supply and Adapter

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DC12V2A Power Adapter DAHUA PFM300 Easy installation and wall mount, structural water-proof; Support -30 °C ~+70 °C wide-range temperature operation, and the full load efficiency of the power; supply can be up to 100% at these temperatures; With junction function for camera wiring or can place video balun with HDCVI/AHD/TVI/CVBS cameras;	779ден
	DAHUA PFM344D-4CH - Switching Power Supply The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	900ден
	DAHUA PFM344D-8CH - Switching Power Supply The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	1.200ден
	POWER SUPPLY 5A / 12V DC for CCTV Camera BIG Input voltage 165 – 250 V; DC power 60W; Miniature size, high power density; ;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection	650ден
	POWER SUPPLY 10A / 12V DC for CCTV Camera BIG Input voltage 165 – 250 V; DC power 120W; Miniature size, high power density;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	850ден
	POWER SUPPLY 15A / 12V DC for CCTV Camera BIG Input voltage 165 – 250 V; DC power 180W;Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	1.050ден
	POWER SUPPLY 20A / 12V DC for CCTV Camera BIG Input voltage 165 – 250 V; DC power 240W; High Miniature size, high power density;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	1.200ден
	POWER SUPPLY 30A / 12V DC for CCTV Camera BIG Input voltage 165 – 250 V; DC power 360W; Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	2.000ден
	4C5A 220V AC input, 3A - 5 channel, 12VDC output, input voltage 165 – 250 V	1.600ден
	9C10A 220V AC input, 5A - 9 channel, 12VDC output, input voltage 165 – 250 V	2.200ден
	18CH20A 220V AC input, 20A - 18 channel, 12VDC output, input voltage 165 – 250V	3.100ден
	DC12V4A 5-ch - CCTV Distributed Power Box DAHUA PFM340-5CH 5 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access. Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	3.970ден

	DC12V5A 9-ch - CCTV Distributed Power Box DAHUA PFM341-9CH 9 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	4.960ден
	DAHUA PFM343-19CH - CCTV Distributed Power Supply Box 19 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	9.920ден

Junction Box for CCTV Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Plastic Flush UNIVERSAL Junction Box for DOME CAMERA, Camera housing with bracket, PLASTIC	120ден
	J-BOX01DS UNIVERSAL Water-proof Junction Box for BULLET CAMERA OUTDORE, Camera housing with bracket, Material: Aluminum, Operating Temperature: -40°C ~60°C	400ден
	J-BOX04PL – Bracket Plastic	200ден
	J-BOX05PL – Bracket Plastic	200ден
	J-BOX06PL – Bracket Plastic	250ден
	J-BOX07PL – Bracket Plastic	200ден
	J-BOX08PL – Dome Bracket Plastic	300ден
	DAHUA PFB204W	880ден
	Dahua PFA1320R Plastic Junction Box	200ден
	DAHUA PFA122 Water-proof Junction Box	1.260ден
	DAHUA PFA130-E Water-proof Junction Box	800ден
	DAHUA PFA130-E Water-proof Junction Box	800ден
	DAHUA PFA13A Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: φ96.8mm x 33.5mm	600ден
	DAHUA PFA134 Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: φ90mm x 35mm	560ден
	DAHUA PFA135 Water-proof Junction Box, Camera housing with bracket, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design,	640ден

	DAHUA PFA136 Water-proof Junction Box, Material: Aluminum, Product Dimension: $\phi 110\text{mm} \times 33.5\text{mm}$ Pipe Thread: Operating Temperature: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$	585ден
	DAHUA PFA137 Junction Box Material: aluminum	535ден
	DAHUA PFA150 Pole Mount Bracket	1.550ден
	Camera Bracket 110*250mm	1.999ден
	Camera Bracket 60cm	1.500ден
	J-BOX100B 200mm*155mm*80mm	600ден
	J-BOX800B 260mm*230mm*80mm	800ден
	J-BOX800C 280mm*230mm*80mm	900ден

Face Recognition Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ASI3213A-W Face Recognition Access Controller 4.3 inch glass touch screen with a resolution of 480 × 272; 2-MP wide-angle dual-lens camera with IR illumination and DWDR; Multiple unlock methods including face, card and password. You can also combine them to create your own personal unlock methods; Supports mask detection; Supports visitor QR code with DSS Pro Platform; Recognizes faces 0.3 m to 1.5 m away (0.98 ft-4.92 ft); as a face recognition accuracy rate of 99.9%;	11.550ден

Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ASI1201E-D Water-proof RFID Standalone Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	5.000ден
	DAHUA ASI1201E – Mifare Water-proof RFID Standalone Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	5.000ден
	DAHUA ASI1201A Standalone Reader Touch keyboard and LCD display; Support 30,000 valid cards & 150,000 records; Support multiple cards(default IC card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;	5.500ден
	DAHUA ASI1201A-D Standalone Reader Touch keyboard and LCD display; Support 30,000 valid cards & 150,000 records; Support multiple cards(default ID card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;	5.500ден
	DAHUA ASI2212J – Mifare Dahua Single Door IC Card, Password, Fingerprint Access Standalone 2.4" TFT display screen with a resolution of 240 × 320. · Audio prompts. · Supports 5,000 users, 5,000 cards, 5,000 passwords, 3,000 finger prints, and 100,000 records. · The security module expansion is supported to enhance security and protect against the device being opened during a power failure. · Fingerprint/card/remote/password	7.500ден
	DAHUA ASI2212J-D Dahua Single Door ID Card, Password, Fingerprint Access Standalone 2.4" TFT display screen with a resolution of 240 × 320. · Audio prompts. · Supports 5,000 users, 5,000 cards, 5,000 passwords, 3,000 finger prints, and 100,000 records. · The security module expansion is supported to enhance security and protect against the device being opened during a power failure. · Fingerprint/card/remote/password	7.500ден

	DAHUA ASI1212M-DW Dahua Card Swiping, Password, Fingerprint Access Standalone The front part of the case is made of zinc alloy and the back part is made of plastic. Supports 10,000 users, 10,000 passwords, 10,000 cards, 3,000 fingerprints and 100,000 records; Mechanical keypad with backlighting; Supports RS-485 communication and Wiegand communication; Buzzer and indicator light; Supports doorbell; Supports security extension modules for access control, preventing doors from being forcefully opened;	8.090ден
	DAHUA ASI1212M-W - Mifare Dahua Card Swiping, Password, Fingerprint Access Standalone The front part of the case is made of zinc alloy and the back part is made of plastic. Supports 10,000 users, 10,000 passwords, 10,000 cards, 3,000 fingerprints and 100,000 records; Mechanical keypad with backlighting; Supports RS-485 communication and Wiegand communication; Buzzer and indicator light; Supports doorbell; Supports security extension modules for access control, preventing doors from being forcefully opened;	8.090ден

Access Control

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ASA1222G-D Time & Attendance Terminal Supports Mifare card/ID card reading distance 1 cm-3 cm, card swiping response time; Fingerprint verification response time ≤0.5 s, fingerprint recognition time ≤1.5 s; Operating temperature: 0°C to +55°C, operating humidity: ≤93%; Supports three attendance modes: fixed, manual/auto and forced;	8.100ден

Access Control – Slave

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ASR1101A-D RFID Reader Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) · 125KHz(EM-ID); Red and Green LEDs; Sensitive touch keypad with blue backlight; Watch dog function ensure device free from halting; Beep Buzzer and LED indicator; Surface mounted installation	1.950ден
	DAHUA ASR1200E – Mifare Water-proof RFID Reader Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	1.200ден
	DAHUA ASR1200E-D Water-proof RFID Reader Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	1.200ден
	DAHUA ASR1201D-D Slim Water-proof RFID Reader Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) 125KHz(EM-ID); Red and Blue LEDs; Watch dog function ensure device free from halting; Water-proof(Outdoor use); Surface/Flush mounted installation	1.750ден

Controllers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DEE1010B Access Control Extension Module Decent appearance; Easy connection; Access control function extension	2.700ден



**DAHUA ASC2104B-T
Four Door Slave Access Control Module**

Support 20,000 valid cards & 30,000 records; Support multiple cards; Support card, password, fingerprint and combination; Only work with ASC2204-H with CAN bus; Wiegand or RS-485 interface to readers; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;

6.200ден

IPC Villa Door Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA VTO1301R-W Wi-Fi Villa Door Station Ultra slim design; PC and ABS material make it ideal for indoor and outdoor use. Offers two-way video call with indoor monitors; Video call through app; IR illumination and auto WDR; Wi-Fi connection; IP65 rated; H.264 and H.265.	3.500ден
	DAHUA VTO2111D-P-S2 IP Villa Door Station High definition camera; WDR; Operating temperature -30°C–60°C; IP65; Supports auto IR illumination and D/N; Card/app remote/indoor monitor unlock; Supports two-way voice call; 10,000 cards; Tamper Alarm; Control two locks	9.870ден
	DAHUA VTO2211G-WP IP Villa Wi-Fi Door Station Tamper alarm; Standard PoE; Control two locks; Supports wireless network; Card unlock, app unlock, and indoor monitor unlock; Two-way audio and voice call through app; Card capacity: 10,000; Thin lightweight design;	10.490ден
	VTO6222E-P 2-wire IP Apartment Door Station Highly durable and elegant, it is made of aluminum panel, and has a mechanical keypad. 2MP HD camera. Supports 5,000 users and 10,000 cards. Supports multiple unlock methods including password, IC card, and unlocks remotely. Provides 12 VDC, 600 mA power. IP65 rated. IK08 rated. Standard PoE power supply.	16.580ден
	DAHUA VTO6521F Apartment Door Station 4.3 inch IPS display; screen resolution 800×480; 2MP CMOS; true WDR; Aluminum anode surface; metal button; IP65, IK07; Operating temperature: -30°C to +60°C; Auto light illumination reduces light pollution; Multiple unlock modes: Password unlock, IC card unlock, and remote unlock; Support 20,000 users and 10,000 cards; Support full duplex; management platform, and voice call through APP; Support SIP server; Support duress alarm, tamper alarm, and door sensor timeout alarm;	19.990ден
	DAHUA VTO6631QB-WP IP & Wi-Fi Villa Door Station Ultra-thin frame design; 5-inch IPS screen with a high resolution of 720 × 1280; MP wide angle camera with H: 119°, V: 66° and D: 142° FOV; Unlocks through IC and ID cards, Bluetooth cards, face and password; Recognizes faces 0.3 to 2 m away (0.98 to 6.56 ft), and has a face recognition accuracy rate of 99.9% and a one to many identification time of 0.2 sec per face.	16.580ден
	DAHUA VTO3311Q-WP Wi-Fi Villa Door Station Full metal casing design. Customizable Number of Buttons. Wi-Fi connection. 1/2.8" 2-MP HD CMOS camera. IR illumination and auto WDR. Supports two locks. Voice call and unlocking through app. IK08 and IP65 rated. H.264 and H.265. Unlock with IC card. PoE power supply. Included rain cover.	12.500ден

	DAHUA VTH1550CH IP Indoor Monitor 7" TFT Capacitive touch screen; IPC surveillance; Alarm integration Micro SD card optional, max 32GB; Record & Snapshot(SD card needed)	5.740ден
	DAHUA VTH2611L-WP Dahua Wi-Fi Indoor Monitor 4.3" TFT capacitive touchscreen; Unlock the door; Set DND period; IPC surveillance; 4-channel alarm input and 1-channel alarm output; Supports standard PoE; Ethernet and Wi-Fi.	5.500ден
	DAHUA VTH2621GW-WP IP Indoor Monitor 7" TFT capacitive touch screen, 1024 × 600 · 6-channel alarm input and 1-channel alarm output; Wi-Fi ; Standard PoE · Door station and IPC monitor ; H.265 and H.264 video decoding; High performance & cost-effective	6.800ден
	DAHUA VTH2621G-WP IP & Wi-Fi Indoor Monitor 7" TFT capacitive touch screen, 1024 × 600; 6-channel alarm input and 1-channel alarm output; Wi-Fi; Standard PoE; Door station and IPC monitor; H.265 and H.264 video decoding; High performance & cost-effective	6.800ден
	VTH5421EW-H Wi-Fi Digital Indoor Monitor with Handset 7 inch LCD, 1024 (H)×600(V); 6 alarm input ports; 1 alarm output port; 1 12V DC power output port provides power for peripheral alarm devices and sensors; 16kbps audio stream; You can answer calls hands free;	9.300ден
	DAHUA VTH5321GW-W Android 7-inch digital indoor monitor Android 8.1; More User-Friendly UI; Ethernet and Wi-Fi; 7" TFT Capacitive touch Screen, 1024×600; Quick configuration for villa system;	10.500ден

IPC Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA KTP03 Video Intercom KIT Megapixel image sensor · Supports IR illumination and night vision. · Two-way audio and voice call through app. · Can be managed through the management platform; supports voice call between App and the door station. · Card unlock, unlock on the indoor monitor, and remote unlock through the App. · Supports IP65	16.950ден

IPC 2-wire Hybrid Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA KTX01 Video Intercom KIT 2-wire Hybrid Villa Door Station; Aluminum alloy front panel; Auto IR illumination; Video messages can be left for unanswered calls. (SD card is required for VTH); Features nameplate and DWDR; Supports local lock and second lock; Offers anti-tampering alarm; IP65 and IK07 rated;	19.500ден

Analogue Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA KTA02 Video Intercom Kit 7" TFT screen; Video intercom function: Unlock, voice call, video call, volume adjustment; System Capacity: 2 door stations + 3 indoor monitors; Multiple bell sound; Supports digital wide dynamic range (DWDR)	7.390ден
	DHI-KTA04 Video Intercom Kit Video intercom function: Unlock, voice call, video call, volume adjustment and doorway monitoring · Multiple bell sounds · Support digital wide dynamic range (DWDR); Display 4.3" TFT	6.490ден


Wired Apartment Outdoor Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DHI-VTO1210C-X IP&Analog Apartment Outdoor Station; 1.3MP CMOS camera, H:75° 3" STN LCD screen, phonebook; Stainless steel panel, IP54,IK07 Night vision & Approaching induction; Video & Audio messaging Surface & Flush mounted	16.535ден
	DHI-VTH1200DS 4.3" Analog Indoor Monitor; 4.3" TFT LCD screen Color video & audio intercom; Alarm intergration Suface & Flush mounted	2.790ден
	DHI-VTH2020A 7" Analog Indoor Monitor; 7" TFT LCD screen Color video & audio intercom; Alarm intergration Surface mounted	4.000ден
	DHI-VTNA1040B 4ch Analog Distributor;4ch distributor 30 cascading;Used in Analog apartment systemDC24V, Max 20W	2.430ден
	VTNS1060A Network power supply for IP System; Decent appearance Protocol network power supply switch; Connect max 6 indoor monitors with the Cat 5e cable,	1.200ден
	ADS-65LSI-19-1 DC 24V 2.5A Power Supply Input: 100-240V ~50/60Hz Required for the VTNA 1040B Switch	2.050ден

UTP Cable Cat5 & Cat6

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	PFM920I-5EUN – 305m UTP CAT5E Cable 305m (1000 ft)/carton U/UTP sCAT5E, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor material; Customized PVC outer sheath ; CE CPR Eca flame retardant class certified;	28ден
	PFM923I-6UN-C – 305m UTP CAT6 Cable 305m (1,000.66 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor; Customized LSZH outer sheath; CE CPR Eca flame retardant class certified;	35ден

Cable

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	RG6 Coaxial Braiding 80*0.12 +Bonded AL-foil+PVC 100m. White Color 100m/roll,	20ден
	RG59 Coaxial CCS Braiding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	22ден
	RG59 Coaxial 100% COPPER Braiding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	30ден
	RG59+2x0.75 COMBO Braiding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	35ден
	RG59+2x0.75 COMBO so SAJLA Braiding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	ден
	RG59+2x0.50 COMBO COPPER Braiding 112 +Bonded AL-foil+PVC + 2x0.50mm power COPPER. White Color, 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	ден
	FTP Cat5E - 24AWG Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box Grey Color	20ден
	FTP Cat5E - 24AWG so SAJLA Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA Grey Color	30ден
	FTP Cat5E - 24AWG so SAJLA COPPER Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA Grey Color	40ден

	FTP Cat5E 24AWG - 100% FULL COOPER CU Network Cable CU (100% Copper), with aluminium foil , and transparent PET film , Conductor 0.51mm , Pass Fluke test on 100M - 305m Box Grey Color	35ден
	FTP Cat6E 23AWG Network Cable , with aluminium foil , and transparent PET film, Conductor 0.57mm - 305m Box Grey Color	30ден
	FTP Cat6E 23AWG - 100% FULL COOPER Network Cable CU (100% Copper) , with aluminium foil , and transparent PET film , Conductor 0.57mm - 305m Box Grey Color 18.6	40ден
	FTP Cat 6A S/FTP LSOH ISDN; 4/6 Mbps Token Ring (IEEE 802.5); 100 Mbps CDDI; 250 Mbps ATM Power over Ethernet (PoE); 10 BASE-T Ethernet (IEEE 802.3j); 100 BASE-VG AnyLAN (IEEE 802.12); 1000 BASE-T 1 Gigabit Ethernet (IEEE 802.3 ab); 10 GBASE-T 10 Gigabit Ethernet (IEEE 802.3 an);	65ден
	FTP Cat 6A F/FTP LSOH ISDN; 4/6 Mbps Token Ring (IEEE 802.5); 100 Mbps CDDI; 250 Mbps ATM Power over Ethernet (PoE); 10 BASE-T Ethernet (IEEE 802.3j); 100 BASE-VG AnyLAN (IEEE 802.12); 1000 BASE-T 1 Gigabit Ethernet (IEEE 802.3 ab); 10 GBASE-T 10 Gigabit Ethernet (IEEE 802.3 an);	50ден
	ALARM CABLE 6 x 0.22, shield 100m , EXTRA	25ден
	ALARM CABLE COPPER 6 x 0.22, shield 100m , COPPER EXTRA	35ден
	Signal Cable – Power Cable LITCY 3*0,5 MM	42ден

Цените се крајни и истите важат за крајни корисници.

Цените се со пресметан ДДВ.

Гаранција на производите е 12 – 24 месеци.

МАКСИПРИНТ го задржува правото на промена на цените без претходна најава.