MAKSIPRINT
DISTRIBUTION & SECURITY

ВИДЕО НАДЗОР

ЦЕНОВНИК



ЛИЦЕНЦИРАНА КОМПАНИЈА ЗА ТЕХНИЧКО ОБЕЗБЕДУВАЊЕ
МАКСИПРИНТ

CERTIFIED
dahua
TECHNOLOGY
DISTRIBUTOR

dahua
TECHNOLOGY

Максипринт Компјутери ЛТД ДОО
Бул. Туристичка бр.4, Охрид
Охридска банка Жиро сметка:
530000100483931
Контакт: 046-262 500 / 070-249 724 / 070-212 929
e-mail: prodazba@maksiprint.com.mk



HDCVI 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-T1A21-U – 2.8mm** **2MP HDCVI IR Eyeball Camera** Max. 30 fps@1080p; Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	**1.300ден**
	**DAHUA HAC-T2A21-U – 2.8mm** **2MP IR HDCVI Fixed-focal Eyeball Camera** Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**1.400ден**
	**DAHUA HAC-HDW1200T-Z-A** **2MP HDCVI IR Eyeball Camera** Max 30fps@1080P; HD and SD output switchable; Built-in mic; 2.7-12mm motorized lens; Max. IR length 60m, Smart IR; IP67, DC12V	**4.400ден**
	**DAHUA HUM1220G-B - 2.8mm** **2MP HDCVI Bullet Camera** Max 30fps@1080P,2.8mm fixed lens,DC12V; HD and SD output switchable;	**1.750ден**
	**DAHUA HAC-HUM3200A** **2MP IR HDCVI Fixed-focal Cube Camera** Max 30 fps@1080p; 10 m illumination distance (940nm IR No IR Exposure); Super Adapt; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC;	**2.850ден**
	**DAHUA HAC-B1A21-U - 2.8mm** **2MP IR HDCVI Fixed-focal Bullet Camera** Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**1.350ден**
	**DAHUA HAC-B2A21-U – 3.6mm** **2MP IR HDCVI Fixed-focal Bullet Camera** Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**1.450ден**
	**DAHUA HAC-B3A21-Z** **2MP HDCVI IR Bullet Camera** Max 30fps@1080P; CVI/CVBS/AHD/TVI switchable; 2.7-12mm motorized lens Max. IR length 40m, Smart IR · IP67, DC12V	**3.600ден**
	**DAHUA LC1220T-TH - IoT Series - 2.8mm** **2MP HDCVI Temperature & Humidity Camera** Max 30fps@1080P, 2.8mm fixed lens, Max. IR length 20m, Detection range: -40°C~60°C, 10-95% RH, Smart IR, IP67, DC12V	**2.400ден**

01.10.2026

HDCVI 2MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	*ЦЕНА*
	**DAHUA HAC-HDW1200TLM-IL-A – 2.8mm** **2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera** Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	**2.620ден**
	**DAHUA HAC-HDW1200CLQ-IL-A – 2.8mm** **2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera** Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic;2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; 12 VDC.	**1.985ден**
	**DAHUA HAC-HFW1200TLM-IL-A - 2.8mm** **2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max. 30 fps@1080p; 3D NR; Smart Dual Light; 40m illumination distance; Super Adapt; Built-in mic; 2.8mm fixed lens;CVI/CVBS/AHD/TVI switchable; IP67,12VDC	**2.320ден**

HDCVI 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-T1A51-U – 2.8mm** **5MP IR HDCVI Fixed-focal Eyeball Camera** Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	**1.700ден**
	**DAHUA HAC-B2A51-U** **5MP IR HDCVI Fixed-focal Bullet Camera** Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**1.750ден**
	**DAHUA HAC-HDW1500TRQ-A – 2.8mm** **5MP Starlight HDCVI Quick-to-install IR Eyeball Camera** Max 25 fps@5MP (16:9 video output); Built-in mic (-A); CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 25M; Smart IR; IP50, DC12V;	**2.750ден**
	**DAHUA HAC-EW2501** **5MP HDCVI IR-Fisheye Camera** 1/2.8” 5Megapixel progressive scan CMOS; Panoramic fisheye lens; Max. 20fps@5MP; Built-in Mic; 120dbtrue WDR, Starlight, 2D&3D NR; Max. IR length 10m,Smart IR;DC12V	**9.999ден**

01.10.2026

HDCVI 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-HDW1500CLQ-IL-A 2.8mm** **5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera** Max 25 fps@5MP (16:9 video output); Smart Dual Light; 20m illumination distance; Super Adapt; Built-in MIC; CVI/CVBS/AHD/TVI switchable; IP67,12 VDC	**2.550ден**
	**DAHUA HAC-HFW1500RL-IL – 2.8mm** **5MP Smart Dual Light HDCVI Two-way Talk Fixed-focal Bullet Camera** Max. 25 fps@5MP; Two-way Talk; Smart Dual Light; Smart Light+; 3D NR; 30 m illumination distance; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**2.680ден**
	**DAHUA HAC-HFW1500TLM-IL-A – 3.6mm** **5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**3.100ден**
	**DAHUA HAC-HFW1500TLM-IL-A – 3.6mm** **5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**3.100ден**
	**DAHUA HAC-HFW1500TH-IL-A – 3.6mm** **5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max. 25 fps@5MP (16:9 video output); Starlight, 3D NR; Smart Dual Light; 80 m illumination distance; Built-in Mic; 3.6 mm fixed lens; IP67, 12 VDC;	**4.300ден**
	**DAHUA HAC-PT1500A-IL-A – 2.8mm** **5MP Smart Dual Light HDCVI Fixed-focal PT Camera** Max. 25 fps@5MP; Smart Dual Light; Smart Area Lighting; Pan & Tilt; 40 m illumination distance; Super Adapt; Built-in Mic; 2.8mm fixed lens; IP66, 12 VDC.	**4.820ден**
	**DAHUA HAC-PTS1500C-E2-IL-A** **2+2MP Smart Dual Light Outdoor HDCVI Dual-Lens PT Camera** Max 25 fps@5 MP (16:9 video output); Smart Dual Light; 50 m illumination distance; Super Adapt; Built-in Mic; Linkage Tracking; Manual Linkage; 2.8 mm fixed lens, 6 mm PT Lens; Supports manual adjustment of fixed lens (Vertical: 5° to 10°); IP66, 12 VDC;	**6.400ден**

5MP WizColor HDCVI Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-HDW1549X-IL-A-PRO - 2.8mm** **5MP WizColor HDCVI Fixed-focal Eyeball Camera** Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt,130 dB true WDR, 3D NR; Built-in Dual Mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**4.575ден**
	**DAHUA HAC-HFW1549X-IL-A-PRO** **5MP WizColor HDCVI Fixed-focal Bullet Camera** Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt,130 dB true WDR, 3D NR; Built-in Dual Mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**4.575ден**

HDCVI 5MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-HDW1509TLQ-LED - 3.6mm** **5MP Full-color HDCVI Quick-to-install Eyeball Camera** Max 25 fps@5MP (16:9 video output); 120dB true WDR, 3D NR;24/7 color image;20 m illumination distance; CVI/CVBS/AHD/TVI switchable;IP67, 12 V DC;	**2.520ден**
	**HAC-HFW1509C-LED – 2.8mm with Audio** **5MP Full-color HDCVI Bullet Camera** Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance 2.8 mm fixed lens; IP67, 12V DC	**2.520ден**
	**HAC-HFW1509C-A-LED – 2.8mm with Audio** **5MP Full-color HDCVI Bullet Camera** Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance; Built-in mic; 2.8 mm fixed lens; IP67, 12V DC	**2.520ден**
	**DAHUA HAC-HFW1509TLM-IL-A – 3.6mm** **5MP Smart Dual Light Bullet Camera** Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	**3.000ден**
	**HAC-HFW1509TLM-A-LED – 3.6mm** **5MP Full-color HDCVI Fixed-focal Bullet Camera** Max 25 fps@5MP (16:9 video output) 120 dB true WDR, 3D NR; 24/7 color imaging; Smart Light+; Smart Area Lighting; Built-in Mic; 40 m illumination distance; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed; IP67, 12 VDC;	**3.450ден**

HDCVI 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-HDW1801TLM-IL-A – 2.8mm** **4K Smart Dual Light HDCVI Fixed-focal Eyeball Camera** Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 2.8 mm fixed lens; IP67, 12 VDC;	**3.900ден**
	**DAHUA HAC-HFW1801TLM-IL-A – 3.6mm** **4K Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	**3.900ден**
	**DAHUA HAC-HFW1801TH-IL-A** **4K Smart Dual Light HDCVI Fixed-focal Bullet Camera** Max. 15 fps@4K; Smart Dual Light; 80 m illumination distance; Super Adapt; Built-in Mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	**4.250ден**

HDCVI 8MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HAC-HDW1809T-A-LED – 2.8mm** **4K Full-Color HDCVI Eyeball Camera** Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging 40 m illumination distance; Super Adapt; Built-in MIC(-A); IP67, 12 VDC.	**4.700ден**

HDCVI 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HDW1800TL-A - 2.8mm** **4K Real-time HDCVI IR Eyeball Camera** Max. 4K resolution, real-time video transmission, Built-in mic (-A), Max. IR length 30mCVI/CVBS/AHD/TVI switchable, Smart IR, IP67, 12V±30%DC	**3.999ден**
	**DAHUA HAC-HFW1800TL-A - 3.6mm** **4K Real-time HDCVI IR Bullet Camera** ax. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	**3.890ден**
	**DAHUA HAC-HFW1801TL-A - 3.6mm** **4K Real-time HDCVI IR Bullet Camera** 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	**4.065ден**
	**DAHUA HAC-HFW1800TH-I8 – 3.6mm** **4K Real-time HDCVI IR Bullet Camera** Max. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	**4.220ден**
	**DAHUA HAC-HFW1801TH-I8 - 3.6mm** **4K Starlight HDCVI Fixed IR Bullet Camera** Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt;CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC.	**4.700ден**
	**DAHUA HFW1801R-Z-IRE6 with Audio2.7-13.5mm** **4K 8MP HDCVI IR Bullet Camera** 120dB true WDR, 3D NR Max. 4K resolution, CVI/CVBS/AHD/TVI switchable,Auto focus, Motorized lens,Max. IR length 60m, smart IR, IP67, 12V ±30% DC	**7.120ден**
	**DAHUA HAC-HFW2802TU-A – 3.6mm** **4K Starlight HDCVI Fixed-focal Bullet Camera** Max. 15 fps@4K; Starlight, 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	**7.030ден**

HDCVI Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA SD49225DB-HC** **2MP 25x Starlight IR HDCVI PTZ Camera** 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25× optical zoom; Starlight technology; 120 dB true WDR, 3D NR; Max. 25/30 fps@1080p, 25/30/50/60 fps@720p; IR distance up to 100 m; IP66;	**23.970ден**

Specialized Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HFW7442H-ZFR** **4MP IR Bullet WizMind Network Camera** Max outputs 4MP (2688 × 1520) @50 fps/60 fps; 12V DC power output; 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition;	
	**DAHUA TPC-BF5421-T** **Thermal Network Hybrid Bullet Camera** Vanadium oxide uncooled focal plane detector; Built-in white light and speaker; Features tempeature measurement; Micro SD memory, IP67, PoE, ePoE	
	**DAHUA JQ-D70Z** **Thermometric Blackbody**	
	**DAHUA ITC413-PW4D** **Series Dahua Access ANPR Camera** High-performance CMOS image sensor and processor that supports continuously extracting metadata 24/7; Easily adapts to scenarios through its motorized vari-focal lens; Adopts intelligent deep learning algorithms and supports recognition of unlicensed vehicles and the type, brand and color of vehicles;	**36.000ден**

Digital Video Recorder Up to 2MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA XVR1B04-I** **4 Channel Penta-brid 1080N/720p Cooper 1U WizSense** H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 5 channels IP camera inputs, each channel up to 2MP;Max 20 Mbps incoming bandwidth	**4.100ден**
	**DAHUA XVR1B08-I** **8 Channel Penta-brid 1080N/720p Cooper 1U WizSense** H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth;	**5.000ден**
	**DAHUA XVR1B16-I/T** **16 Channel Penta-brid 1080N/720p Compact 1U WizSense** 16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; 16-channel SMD Plus for analog channels or 18-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles; Supports up to 18-channel IP camera input and each channel can be up to 6 MP.	**9.800ден**

Digital Video Recorder Up to 6MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA XVR5104HS-I3/T** **4CH Penta-brid 5MP Compact 1U WizSense Digital Video Recorder** 4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 6-channel IP camera input and each channel can be up to 6 MP; The incoming bandwidth reaches 32 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	**7.500ден**
	**DAHUA XVR5108HS-I3/T** **8CH Penta-brid 5MP Value/1080P Compact 1U 1HDD WizSense Digital Video Recorder** 8-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 12-channel IP camera input and each channel can be up to 6MP; The incoming bandwidth reaches 64 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	**11.000ден**
	**DAHUA XVR5116HS-I3/T – WizSense** **16 Channel Penta-brid 5M-N/1080P Compact Digital Video Recorder** H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus; IoT & POS functionalities	**18.990ден**
	**DAHUA XVR5232AN-I3/T** **32 Channels Penta-brid WizSense Digital Video Recorder** H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; IoT & POS functionalities.	**33.700ден**


Digital Video Recorder Up to 8MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA XVR5104HS-4KL-I3** **4 Channel Penta-brid 5MP Compact 1U WizSense** Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 8 channels IP camera inputs, each channel up to 8MP; Up to 1 channel video streamPerimeter Protection; Up to 4 channels video streamSMD Plus;	**9.840ден**
	**DAHUA XVR5104HS-4KL-I3/T** **4CH Penta-brid 4K Value/5MP Compact 1U 1HDD WizSense Digital Video Recorder** 4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder; Supports up to 8-channel IP camera input and each channel can be up to 8MP; The incoming bandwidth reaches 64 Mbps; Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes;	**10.700ден**
	**DAHUA XVR5108HS-4KL-I3 - WizSense** **8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder** H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;	**13.950ден**
	**DAHUA XVR5108HS-4KL-I3/T - WizSense** **8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder** H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;	**15.500ден**
	**DAHUA XVR7108H-4K-I3** **8 Channels Penta-brid 4K Mini WizSense Digital Video Recorder** H.265+/H.265 dual-stream video compression. Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	**16.050ден**
	**DAHUA XVR5116H-4KL-I3** **16 Channels Penta-brid 4K-N/5MP Mini 1U WizSense** H.265+/H.265 dual-stream video compression; · Supports Full-channel AI-Coding; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	**29.490ден**
	**DAHUA XVR5216A-4KL-I3** **16 Channels Penta-brid 4K-N/5MP 1U WizSense** H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	**33.200ден**
	**DAHUA XVR7216AN-4K-I3** **16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder** H.265+/H.265 dual-stream video compression; Supports 16-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP ; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Up to 16 channels video stream SMD plus;	**42.250ден**
	**DAHUA XVR5232AN-4KL-I3/T** **32 Channels Penta-brid 4K-N/5MP WizSense Digital Video Recorder.** H.265+/H.265 dual-stream video compression.; Supports 32-channel AI-Coding.; Supports HDCVI/AHD/TVI/CVBS/IP video inputs.; Max 32 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	**55.000ден**

Hard Disk Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	HDD 1TB	ден
	HDD 2TB	ден
	HDD 4TB	ден
	HDD 6TB	ден
	HDD 8TB	ден

Memory Card & USB Flash Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DHI-TF-C100/64GB microSD Memory Card	900ден
	DHI-TF-C100/128GB microSD Memory Card	1.300ден
	DHI-TF-C100/256GBmicroSD Memory Card	2.000ден
	DHI-USB-P629-32-64GB USB Flash Drive	650ден
	DHI-USB-P629-32-128GB USB Flash Drive	1.000ден
	DHI-USB-P629-32-256GB USB Flash Drive	2.000ден

MAKSPRINT
DISTRIBUTION & SECURITY

dahua TECHNOLOGY

IPC Smart-Dual Light 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-B1E29-A-IL** **2MP ECO Smart Dual Light Fixed-focal Bullet Network Camera** 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE; IP67 protection;	**3.380ден**
	**DAHUA IPC-T1E29-A-IL** **2MP ECO Smart Dual Light Fixed-focal Eyeball Network Camera** 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE; IP67 protection;	**3.380ден**
	**DAHUA IPC-HDBW1239E1-A-IL** **2MP Entry Smart Dual Light Fixed-focal Dome Network Camera** 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.; Outputs max. 2 MP (1920 × 1080)@25/30 fps; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 and IK08 protection; Supports human detection;	**4.200ден**
	**DAHUA IPC-PT1239H-PV** **2MP Smart Dual Light Active Deterrence Network PT Camera** 1/2.8" 2Megapixel CMOS; Max. 25/30 fps@2MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way Talk; Easy App Controls;	**4.250ден**

IPC 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HDW2230T-AS-S2** **2MP Lite IR Fixed-focal Eyeball Network Camera** 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2MP (1920 × 1080)@25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Max. 256 G micro SD card; built-in MIC; 12V DC/PoE power supply; IP67 protection;	**2.790ден**
	**DAHUA IPC-T1E20-A** **2MP ECO IR Fixed-focal Eyeball Network Camera** 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Bulit in Mic; 12 VDC power supply; IP67protection;	**ден**
	**DAHUA IPC-B1E20-A** **2MP ECO IR Fixed-focal Bullet Network Camera** 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30; Built in Mic; 12 VDC power supply; IP67 protection;	**2.680ден**
	**DAHUA IPC-HDBW1230E – 2.8mm** **2MP IR Mini-Dome Network Camera** 1/2.7" 2Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding; 25/30fps@1080P(1920x1080); Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: 2.8mm fixed lens; Max IR LEDs length 30m; IP67, IK10, PoE	**4.370ден**
	**DAHUA IPC-HDBW5241R-ASE** **2MP IR Fixed-focal Dome WizMind Network Camera** Outputs max. 2MP (1920×1080) @25/30fps; Built-in IR LED, and the max. illumination distance is 50 m; With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc; IP67 and IK10 protection; SMD 3.0;	**10.900ден**

01.10.2026

	**DAHUA IPC-HDBW5241E-ZE** **2MP IR Vari-focal Vandal-proof Dome WizMind Network Camera** Outputs max. 2MP (1920×1080) @25/30 fps; Built-in IR LED, and the max. illumination distance is 40 m; With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting; ePoE; IP67 and IK10 protection; SMD 3.0;	**13.990ден**
	**DAHUA SD22204UE-GN – Lite Series** **2MP 4x Starlight PTZ Network Camera** 1/2.8” STARVIS™ CMOS; Powerful 4x optical zoom; Day/Night(ICR), Ultra DNR; Max. 25/30fps@1080P; Max 100°/s pan speed · IVS Support PoE; IP66, IK10	**14.140ден**

IPC 4MP Full-Color/Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	*ЦЕНА*
	**DAHUA IPC-B1E49-A-IL** **4MP ECO Smart Dual Light Fixed-focal Bullet Network Camera** 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2560 × 1440)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE power supply, easy for installation; IP67 protection; Supports human detection;	**4.590ден**
	**DAHUA IPC-HDBW1439E1-A-IL** **4MP Entry Smart Dual Light Fixed-focal Dome Network Camera** 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs Max. 4 MP (2560 × 1440)@25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m;Built in Mic; 12 VDC/PoE power supply, IP67 and IK08 protection;	**5.235ден**
	**DAHUA IPC-PT1439H-PV – 2.8mm** **4MP Smart Dual Light Active Deterrence Network PT Camera** 1/2.8" 4Megapixel CMOS; Max. 25/30 fps@4MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way Talk; Easy App Controls;	**5.165ден**

IPC 4MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-T1E40-A - 2.8mm** **4MP ECO IR Fixed-focal Eyeball Network Camera** MP 1/3" CMOS image sensor, low luminance, and high definition image.; Outputs max. 4 MP (2560 × 1440)@30 fps; H.265 codec, high compression rate, ultra-low bit rate; and the max. illumination distance is 30 m; ROI, SMART H.264+/H.265+; Bulit in Mic; IP67 protection;	**3.380ден**
	**DAHUA IPC-HDW1431T-ZS-S4** **4MP Entry IR Vari-focal Eyeball Netwok Camera** 4MP, 1/3” CMOS image sensor, low illuminance, high image definition; 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps; · Built-in IR LED, max. IR distance: 50 m; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments; 12V DC/PoE power supply;	**8.500ден**
	**DAHUA IPC-HFW1431T-ZS-S4** **4MP Entry IR Vari-focal Bullet Netwok Camera** 4MP, 1/3” CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 50 m; 12V DC/PoE power supply;	**8.500ден**

IPC 4MP WizColor Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HDBW2449E-S-IL** **4MP Smart Dual Light Fixed-focal Dome WizSense Network Camera** 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560 × 1440@25/30 fps; Built-in IR LED and warm light , the max. IR illumination distance is 30 m and the max. warm light distance is 30 m.12 VDC/PoE power supply, easy for installation; IP67, IK10 protection; SMD Plus;	**7.860ден**
	**DAHUA IPC-HDW2449T-S-PRO** **4MP WizColor Fixed-focal Eyeball WizSense Network Camera** 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps; Built-in warm light, and the max. illumination distance is 30m; Supports max. 256 G MicroSD card; built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; SMD Plus;	**8.120ден**
	**DAHUA IPC-HFW2449TL-S-PRO** **4MP WizColor Fixed-focal Bullet WizSense Network Camera** 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Built-in warm light, and the max. illumination distance is 50 m; Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict; Supports max. 256 G Micro SD card; built in Mic;	**8.120ден**
	**DAHUA SD2C400NA-B-PV-PRO** **4MP WizColor WizSense Network PT Camera** 1/1.8" 4Megapixel STARVIS™ CMOS; WizColor technology; Max. 25/30 fps@4MP; H.265 encoding; SMD3.0; Perimeter protection; Two-way Talk; Auto Tracking(Lite); Preset Patrol; IP66 protection;	**9.085ден**

IPC 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HFW2541E-S – 3.6mm** **5MP IR Fixed-focal Bullet WizSense Network Camera** 5-MP 1/2.7" CMOS image sensor, low luminance, high definition image; Outputs max. 5 MP (2592 × 1944) @20 fps; Abnormality detection: Motion detection, video tampering, scene changing, audio detection, IP conflict, illegal access, and voltage detection	**7.540ден**
	**DAHUA IPC-HDBW5541R-ASE** **5MP IR Fixed-focal Dome WizMind Network Camera** MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960×1668) @25/30 fps; Built-in IR LED, and the max. illumination distance is 50 m; th deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting;	**13.110ден**

IPC 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HFW2549S-S-IL** **5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera** 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	**8.110ден**

IPC 6MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HDW1639T-A-IL** **6MP Smart Dual Light Fixed-focal Eyeball Network Camera** 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP@20 fps, and supports 2688 × 1520@25/30fps;Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	**5.500ден**
	**DAHUA IPC-HDBW1639E1-A-IL** **6MP Entry Smart Dual Light Fixed-focal Dome Network Camera** 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP (3200 × 1800)@20 fps, and supports 2688×1520 (2688 × 1520)@25/30 fps. Built-in warm light and IR LED, the max. IR illumination distance is 30 m and the max. warm light distance is 30 m; 12 VDC/PoE power supply; IP67 and IK08 protection; Supports human detection;	**5.700ден**
	**DAHUA IPC-HFW1639TC-A-IL** **6MP Smart Dual Light Fixed-focal Bullet Network Camera** 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6MP @20 fps, and supports 2688 × 1520@25/30 fps; H.265 codec, Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	**5.500ден**

8MP Wiz-Color IPC Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HFW2849TL-S-PRO** **8MP WizColor Fixed-focal Bullet WizSense Network Camera** 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm light, and the max. illumination distance is 50 m; Supports max. 256 G Micro SD card; built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; SMD Plus;	**11.400ден**
	**DAHUA IPC-HFW2849M-S-B-PRO** **8MP WizColor Fixed-focal Bullet WizSense Network Camera** 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@20 fps, and supports 4 MP (2688 × 1520)@25/30 fps; Built-in warm light, and the max. illumination distance is 50 m; Supports max. 256 G Micro SD card; built in Mic; 12 VDC/PoE power supply; IP67 protection;	**10.990ден**
	**IPC-PT2849C1-S-PV-PRO** **8MP WizColor Active Deterrence WizSense Network PT Camera** 1/1.8" 8 Megapixel CMOS; WizColor Technology; Max. 20 fps@8MP; H.265 Encoding; SMD 3.0; Perimeter Protection; Two-way Talk; Auto Tracking Lite; Tour; IP66 Protection;	**ден**

IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA IPC-HDW1839T-A-IL** **8MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera** 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; Supports human detection;	**6.700ден**
	**DAHUA IPC-HDBW1639E1-A-IL** **6MP Entry Smart Dual Light Fixed-focal Dome Network Camera** 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP (3200 × 1800)@20 fps, and supports 2688×1520 (2688 × 1520)@25/30 fps. Built-in warm light and IR LED, the max. IR illumination distance is 30 m and the max. warm light distance is 30 m; 12 VDC/PoE power supply; IP67 and IK08 protection; Supports human detection;	**6.900ден**
	**DAHUA IPC-HFW1839TC-A-IL** **8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera** 1/2.7" CMOS image sensor, low luminance, and high definition image; . 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection.; Supports human detection;	**6.700ден**
	**DAHUA IPC-HDW2849TM-S-IL** **8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera** 8-MP 1/2.7" CMOS image sensor and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, Illumination distance is 30 m and the max. warm light distance is 30 m;	**8.900ден**

IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA HDBW2841R-ZAS** **8MP IR Vari-focal Dome WizSense Network Camera** 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding;	**13.185ден**
	**DAHUA IPC-HFW2831S-S-S2** **8MP Lite IR Fixed-focal Bullet Network Camera** 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	**7.640ден**
	**DAHUA IPC-HFW2831T-AS-S2 3.6mm** **8MP Lite IR Fixed-focal Bullet Network Camera** 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	**9.570ден**
	**DAHUA IPC-HFW2841T-AS** **8MP IR Fixed-focal Bullet WizSense Network Camera** Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps.Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	**9.130ден**
	**DAHUA IPC-HFW2841T-ZAS** **8MP IR Vari-focal Bullet WizSense Network Camera** 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m.Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	**12.870ден**

	**DAHUA IPC-HFW2831TP-ZS – Lite Series** **8MP WDR IR Bullet Network Camera** 1/1.8” 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	**13.230ден**
	**DAHUA IPC-HFW3849T1-AS-PV-S3** **8MP Smart Dual Illumination Active Deterrence Bullet Camera** 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 ml Alarm: 1 in, 1 out; audio: 1 in, 1 out;	**15.990ден**
	**DAHUA IPC-HFW3849T-ZAS-IL** **8MP Smart Dual Light Vari-focal Bullet WizSense Network Camera** 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; light, the max. IR distance is 60 m and the max. warm light distance is 60 m; toring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human), stay detection, loitering detection, face detection (full image); 12 VDC/PoE power supply; IP67, IK10 (optional, IEC 62262:2002) protection; SMD 4.0; Supports AI SSA;	**14.590ден**
	**DAHUA IPC-PFW3849S-A180-AS-PV** **2x4MP TiOC Duo Splicing Fixed-focal Bullet WizSense Network Camera** Outputs 180° wide angle splicing image; Outputs max. 8 MP (4096 × 1860)@20 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED and warm light, the max. IR illumination distance is 25 m and warm light distance is 20 m; 12 VDC/PoE power supply, easy for installation; IP67 protection; Sound and light alarm;	**20.500ден**

IPC Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA SD4A425DB-HNY** **4MP 25x Starlight IR WizSense Network PTZ Camera** 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@4MP; IR distance up to 100 m; Auto-tracking 1.0; Perimeter protection.; Face detection; SMD 3.0; IP66;	**32.000ден**
	**DAHUA SD5A225GB-HNR** **2MP 25x Starlight IR WizSense Network PTZ Camera** 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25x optical zoom; Max.50/60fps@2M; IR distance up to 150 m; Auto Tracking 3.0; Face Detection; SMD 4.0; PoE+; IP67, IK10	**35.850ден**
	**DAHUA SD3D416NB-GNY** **4M 16x IR WizSense Network PTZ Camera** 1/2.8" 4Megapixel CMOS; 16x optical zoom; Starlight technology; Max. 25/30 fps@4MP; IR distance up to 80 m; IVS(Human/Vehicle Detection); SMD 3.0; IP66; Smart Light +; Tour;	**20.700ден**
	**DAHUA SDT4E425-4F-GB-A-PV1** **X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera** 1/2.8" 4Megapixel F1.0 CMOS; Detail: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30fps@4M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	**39.120ден**
	**DAHUA SDT4E425-8P-GB-APV1** **8+4MP 25x TiOC Network Panoramic PTZ Camera** Overview channel: Outputs 180° wide angle splicing image; Detail channel: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30 fps@8M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	**48.850ден**
	**DAHUA SD5A432GB-HNR** **4MP 32x Starlight IR WizSense Network PTZ Camera** 1/2.8" 4Megapixel STARVIS™ CMOS; Powerful 32x optical zoom; Max. 25/30 fps@4M; IR distance up to 150 m; Auto Tracking 3.0; Face Detection; SMD 4.0; PoE+; IP67, IK10;	**49.990ден**
	**DAHUA SD49825GB-HNR** **8MP 25x Starlight IR Network PTZ Camera** 1/2.8" 8Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@8M; IR distance up to 100 m; Perimeter protection; Face detection ; SMD 4.0; IP66;	**53.750ден**
	**DAHUA IPC-PFW8802-A180** **4x2MP Multi-Sensor Panoramic IR Bullet Network Camera** Four 1/1.9” 2Megapixel progressive scan CMOS; H.265/H.264 triple-stream encoding; Support 180-degree panoramic view; Day/Night(ICR), 3DNR, AWB, AGC, BLC, WDR; Smart detection; Max. IR LEDs length 30m; Micro SD memory, IP67, IK10,PoE+	**42.000ден**

01.10.2026

IPC 2MP/4MP Wi-Fi Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA H5A** **5MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera** One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	**3.450ден**
	**DAHUA H4C** **4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera** One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	**3.450ден**
	**DAHUA SD1A203T-GN-W – IR-15m** **2MP 3x Starlight IR PTZ Wi-Fi Network Camera** 1/2.8” 2Megapixel STARVIS™ CMOS , Powerful 3x optical zoom, Starlight, WDR, Max. 5/30fps@1080P, IVS, Support Wi-Fi,, IP66	**7.500ден**

IPC Wi-Fi Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA F4C-LED** **4MP Fixed-focal Wi-Fi Full-Color Bullet Network Camera** AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	**3.700ден**

IPC Wi-Fi Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	*ЦЕНА*
	**DAHUA DH-T3A-IL** **3MP Fixed-focal Wi-Fi Turret Network Camera** 3MP Clear images with sharp details; AI Human Detection; AI Vehicle Detection; Built-in Mic; Smart Dual Light; IP67 Protection; Wi-Fi 6; H.265; Bluetooth Pairing; DMSS App; Supports Micro SD Card;	**3.990ден**
	**DAHUA DH-T5A-IL** **5MP Fixed-focal Wi-Fi Turret Network Camera** 5MP Clear images with sharp details; AI Human Detection; AI Vehicle Detection; Built-in Mic; Smart Dual Light; IP67 Protection; Wi-Fi 6; H.265; Bluetooth Pairing; DMSS App; Supports Micro SD Card;	**3.990ден**
	**DAHUA F4C-PV** **4MP Fixed-focal Wi-Fi Smart Dual-Light Bullet Network Camera** AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology;Built-in warm light and IR LED, and the max. illumination distance is 30 m.	**3.800ден**
	**DAHUA F5D-PV** **5MP Fixed-focal Wi-Fi Bullet Network Camera** Clear images with sharp details; Sound and Light Alarm; AI Human Detection; AI Vehicle Detection; Two-way Talk; IP67 Protection; Red and Blue Warning Light; H.265; Wi-Fi 6; Bluetooth pairing; Supports Micro SD Card; DMSS App;	**3.990ден**
	**DAHUA P5I-PV** **5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera** 5MP; Sound and Light Alarm; Smart Dual Light; Auto Tracking; AI Human Detection; AI Vehicle Detection; IP66 Protection; Two-way Talk; H.265; Bluetooth Pairing; Wi-Fi 6; Supports Micro SD Card;	**4.500ден**

01.10.2026

	**DAHUA P5AS-PV** **5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera** 5MP; Sound and Light Alarm; Red and Blue Warning Light; AI Human Detection; AI Vehicle Detection; Auto Tracking; Preset Patrol; Wi-Fi 6; One Camera for 360° View; Smart Dual Light; Bluetooth Pairing;	**4.700ден**
	**DAHUA P5B-PV** **5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera** 360° monitoring without blind spots; Sound and Light Alarm Provides instant alarms to deter intruders; AI Human Detection;AI Vehicle Detection; Auto Tracking; Fast pairing with Bluetooth; Seamless integration of speed and anti-interference; Two-way audio;	**5.450ден**
	**DAHUA P5F-PV** **5MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera** 5MP, Beyond Sharpness; Sound and Light Alarm; Auto Tracking; AI Human Detection; AI Vehicle Detection; Preset Patrol; IP66 Protection; Two-way Talk; Bluetooth Pairing; Wi-Fi 6; DMSS App; H.265;	**6.990ден**
	**DAHUA P8F-PV** **8MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera** 4K Ultra HD, Beyond Sharpness; Sound and Light Alarm; Auto Tracking; AI Human Detection; AI Vehicle Detection; Preset Patrol; IP66 Protection; Two-way Talk; Bluetooth Pairing; Wi-Fi 6; DMSS App; H.265;	**7.500ден**
	**DAHUA P5D-5F-PV** **5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera** Dual Channel Smart Detection; AI Human Detection; Dual 3K; Dual-lens, Double Vision; Adjustable Dual-lens Angles; Auto Tracking; Preset Patrol; IP66 Protection; Smart Dual Light; Sound and Light Alarm; Bluetooth Pairing; Wi-Fi 6; H.265;	**7.000ден**

Solar and 4G Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA BP3EW-4G** **APOLLO 4G Solar Security System** 3MP; Full-color; Long-lasting Power, Non-stop Protection; AI Precise Detection with Quick Wake Up; AOV (Always-On Video) Mode; Sound and Light Alarm; Two-way Talk; 4G Connection; H.265; IP66 Protection; Supports Micro SD Card;	**8.560ден**
	**DAHUA P4F-PV-4G** **4MP Outdoor Wizcolor Fixed-focal 4G Pan & Tilt Network Camera** 4G Connection; One Camera for 360° View; AI Human Detection; AI Vehicle Detection; Sound and Light Alarm; Two-way Talk; Auto Tracking; IP66 Protection; Supports Micro SD Card;	**9.040ден**
	**DAHUA BF4CA-4G-XL/ M0508-K** **4MP 4G Battery Bullet Network Camera Solar Monitoring System** Long-lasting Power, Non-stop Protection; AI Precise Detection with Quick Wake Up; AOV (Always-On Video) Mode; Sound and Light Alarm; Smart Dual Light; 4G Connection; Supports Micro SD Card; IP66 Protection;	**9.990ден**

Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA NVR2116-S3** **16 Channel Smart 1U 1HDD Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding ; AI by camera: perimeter protection,and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;	**5.500ден**
	**DAHUA NVR4104HS-EI** **4CH Compact 1U 1HDD WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 80 Mbps; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	**9.330ден**
	**DAHUA NVR4104HS-P-4KS3** **4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder** Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps or 4 × 4 MP@30 fps; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; Supports EPTZ, and one-click arming and disarming;	**11.400ден**
	**DAHUA NVR4104HS-P-4KS3(960GB)** **4CH Compact 1U 4PoE 1SSD 960GB Lite Network Video Recorder** Comes with an internal 960GB SSD; Max. decoding capability: 8 × 1080p @30 fps or 4 × 4 MP@30 fps; Max. 80/80/60 Mbps incoming/ recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map;	**14.950ден**
	**DAHUA NVR4108HS-EI** **8CH Compact 1U 1HDD WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	**11.500ден**
	**DAHUA NVR4108HS-8P-EI** **8CH Compact 1U 8PoE 1HDD WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus;	**17.200ден**
	**DAHUA NVR4208-8P-4KS2/L** **8 Channel 1U 2HDDs 8PoE Network Video Recorder** New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD; Supports remote configuration and management of IPC, such as set ting parameters	**10.400ден**
	**DAHUA NVR4116HS-EI** **16CH Compact 1U 1HDD WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	**14.600ден**

	**DAHUA NVR4116-8P-4KS2/L** **16 Channel Smart 1U 1HDD 8PoE Network Video Recorder** New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device;	**11.200ден**
	**DAHUA NVR4216-16P-EI** **16CH 1U 16PoE 2HDDs WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	**28.780ден**
	**DAHUA NVR5216-8P-4KS2E** **16 Channel 1U 8PoE 4K&H.265 Pro Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264 · Max 320Mbps Incoming Bandwidth · Up to 12MP Resolution for Preview and Playback; HDMI/VGA simultaneous video output; All PoE ports support ePoE & EoC; Point of Sale (POS); ANPR; Fisheye Dewarping;	**19.990ден**
	**DAHUA NVR5216-16P-EI** **16CH 2HDD 1U NETWORK VIDEO RECORDER** Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30 fps; Supports IP cameras with a resolution up to 32 MP; SUpports AcuPick with up to 16 channels; Provides access to remote storage devices via iSCSI to expand storage capacity	**38.500ден**
	**DAHUA NVR4816-16P-4KS2/I** **16 Channel 2U 16PoE 8HDDs WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Storage or forwarding at 256 Mbps (160 Mbps when AI function enabled); Max. decoding capability: 10 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plu; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting; Support IPC UPnP, 16PoE ports;	**29.600ден**
	**DAHUA NVR5816-R-4KS2** **16 Channel 2U 4K&H.265 Pro Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Max 320Mbps Incoming Bandwidth; Supports RAID 0/1/5/10; Up to 12MP Resolution for Preview and Playback; 2HDMI/2VGA simultaneous video output; ANPR by Camera; Automatic Network Replenishment (ANR) Technology; Fisheye Dewarping; Smart Fan;	**29.700ден**
	**DAHUA NVR4232-EI** **32CH 1U 2HDDs WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection and recognition, perimeter protection;	**17.400ден**
	**DAHUA NVR5232-EI2** **32 Channels 1U 2HDDs WizSense Network Video Recorder** Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; AI by Recorder; AI by Camera; Supports EPTZ, and one-click arming and disarming;	**32.000ден**
	**DAHUA NVR5464-EI** **64 Channels 1.5U 4HDDs WizSense Network Video Recorder** Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps	**45.000ден**

	incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel;	
	**DAHUA NVR5464-EI2** **64 Channels 1.5U 4HDDs WizSense Network Video Recorder** Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	**55.900ден**
	**DAHUA NVR5864-EI2** **64CH 2U 8HDDs WizSense Network Video Recorder** Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	**78.120ден**



Wireless Alarm System

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA ART-ARC3000H-03-GW2(868) – Alarm KIT** Supports 150 wireless peripherals Peripherals status display (signal strength, battery level, temperature, program version) Wired, Wi-Fi or GPRS network connection; Dual SIM and Single Standby, auto switching; Automatic network replenishment (ANR); Video linkage on App SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	**17.440ден**
	**DAHUA ART-ARC3800H-03-FW2 Dahua Wireless Alarm KIT** Supports alarm video verification through integration of the IPC with the hub; Features voice call alarm; Supports wired and AP network configuration methods, which makes it easier to add the hub to apps and to switch to the hub's network; Supports multi-network redundancy for Ethernet, Wi-Fi and 4G networks to ensure the network remains stable and reliable;	**19.500ден**
	**DAHUA ARD1233-W2 - Wireless PIR detector** Pet immunity function; Auto temperature compensation; 3-level sensitivity adjustment; Low battery alarm; Anti-tampering; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability;	**2.900ден**
	**DAHUA ARA33A** **Detector Bracket**	**390ден**
	**DAHUA ARD1731-W2** **Wireless PIR-Camera** Maximum resolution 1600*1200; Based on the RF-HD image transmission technology, transmission of 6 HD images with resolution of 1600*1200 needs up to 10 seconds; One-week cloud cache for videos and images; Temperature monitoring;	**7.600ден**
	DAHUA ARD333-W2(868S) - Dahua Wireless Door Detector Signal strength detection; Low battery alarm; Temperature monitoring; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure;	**2.320ден**
	**DAHUA ARA13-W2 - Wireless outdoor siren** IP65 rated; Outdoor product (–25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	**6.800ден**
	**DAHUA ARA13-W2 - Wireless outdoor siren** IP65 rated; Outdoor product (–25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	**6.800ден**
	**DAHUA ARA12-W2 - Wireless siren** Signal strength detection; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure.	**3.320ден**
	**DAHUA ARA24-W2** **Wireless keyfob** SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	**1.700ден**
	**DAHUA ARK30T-W2 - Wireless Keypad** Supports 3 shortcut alarms: Medical, fire, emergency; Arm/Disarm with password or IC card; Supports signal strength detection to select suitable installation sites; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication; Cloud update and automatic recovery from update failure.	**4.640ден**

01.10.2026

	**DAHUA ARD821-W2 - Wireless Panic Button** Two-way RF communication; Provides multiple LED colors to indicate different statuses; Cloud update and automatic recovery from update failure; Offers accidental press prevention; Battery life up to 5 years if used twice a week; IP54 rated	**1.960ден**
	DAHUA ARM310-W2 - Wireless input expander Six types of alarm: intrusion, medical, fire, emergency, gas, and tamper; NC and NO are avaliable for alarm inputs (NO by default); Signal strength detection; Low battery alarm; Temperature mornitoring; Frequency hopping function and two-way communication technology ensure communication stability;	**2.240ден**
	**DAHUA ARD912-W2(868D)** **Wireless Water Leak Detector** Frequency hopping and two-way communication technology ensure that communication is stable; Displays the temperature of the surrounding environment and supports the overheating alarm; Sensitivity adjustment;	**3.500ден**
	**DAHUA ICS1-W2-868** **Smart Plug** Two-way RF communication; Displays the status with an LED indicator; Offers protection against overcurrent, overvoltage, and overheating; Measure the voltage, current and temperature;	**2.870ден**
	**DAHUA ARM7011-W2** **Dahua Wireless Relay** Frequency hopping and two-way communication technology ensure that communication is stable;Supports jamming detection and communication encryption.Supports cloud update and automatically restores when cloud update fails.	**2.130ден**
	**DAHUA HY-RI151** **LED Remote Indicator**	**580ден**
	**DAHUA ARA43-W2 - Alarm Repeater** Connects up to 32 peripherals; Two-way RF communication; LED indicator displays device status; Supports auto paring, extending RF distance for your security system; Auto switches from dual antennas to reduce blind area; Battery backs device working for over 35 hours	**6.000ден**
	**DAHUA HY-SA21A-W2(868)** **Wireless Smoke Alarm** Split-spectrum sensor technology; Test and silence features in one single button; Loud sound output over 85 dB(A) at 3 meters; Low quiescent current consumption; Surface-mount device (SMD) circuit board design; Low battery warning signal	**4.080ден**
	**DAHUA HY-SAV849HA-E** **5MP IR AI-fire Smoke Sensing Network Camera** Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices, and user can import custom voices; 2/2 Alarm in/out, 1/1 audio in/out;	**ден**
	**DAHUA ARM9A4-W2(868)** **Dahua Wireless Multi IO Transmitter** Connection to Hub through RF communication; 16 alarm inputs, 4 relay outputs; 2 auxiliary power outputs with a maximum power of 24W for powering wired detector and siren, and support overload and short circuit detection; AC power and rechargeable battery (optional) two power supply options;	**11.380ден**

01.10.2026

Proffesional Monitoring Dahua Monitor		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**21.45" FHD Monitor DHI-LM22-H200** Suitable for continuous 24/7 operation; Ultra-thin body with metal housing; Micro bezel design, elegant appearance, ultra-light base; 178°H/178°V extra-wide viewing angle for overall viewing performance;	**9.620ден**
	**27" FHD Monitor DHI-LM27-B200S** Light and cost-effective plastic housing; Ultra-narrow bezel , elegant appearance, Metal base; 178°H/178°V extra-wide viewing angle for overall viewing performance; Anti-blue light design,eye-protective; Low energy consumption, long service life;	**9.390ден**
	**27" Monitor DHI-LM27-C200** The 1920*1080 resolution produces clearer and more vivid pictures; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB. It meets the designer's demand of image texture; Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB.	**9.480ден**
	**32" FHD Monitor DAHUA LM32-F200** Light and cost-effective plastic housing · suitable for continuous 24/7 operation · 178°H/178°V extra-wide viewing angle for overall viewing performance; · Built-in speakers; Physical button and infrared remote dual control mode	**17.390ден**
	**43" FHD Monitor DHI-LM43-F200** Light and cost-effective plastic housing; suitable for continuous 24/7 operation; 178°H/178°V extra-wide viewing angle for overall viewing performance; High fidelity digital processing for a brilliant and vivid video; 8ms fast response time	**20.150ден**
	**43" FHD Monitor DHL43-F600** Industrial level LCD panel, suitable for continuous 24/7 operation · Physical resolution of 1920×1080 · High fidelity digital processing for a brilliant and vivid video · 5ms fast response time for no motion blur, judder or ghosting	**26.650ден**
	**Bracket for monitor TV 14”- 42"**	**500ден**
	**Bracket for monitor TV 26”- 63"**	**650ден**
	**Bracket for monitor TV 26”- 63"**	**1.050ден**

IPC Wi-Fi 2MP Smart Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**M-WJ01 Tuya Smart 1080P 2.0MP Wifi Super Mini Camera** APP name:TuyaSmart; Standard Lens: 2.4mm; H.264 Real time; Support Monitor; Suport Android & Iphone Mobile View; Night vision distance: 5-8M; 5V, 1A;Maximum support 64G TF card;Support ONVIF, can work with NVR	**3.500ден**
	**VR 2MP IP Panoramic Fisheye PTZ camera** H.264 Compression,Dual Stream(0.1M-8Mpbs); LED:4pcs **LED 30M**(With IR CUT), **Fisheye 1.44mm 185° Lens**; WIFI: 3DB Antenna;, Motion Dectction, Alert Action, CMS For PC; Audio: Built-in 45DB Microphone; Built-in 8 Assault 2-Watt Speakers; Built in Antenna; Without RJ45 Port; White Light LED	**2.000ден**
	**IPW-THS-901 WiFi Smart PT Camera Indoor** Support 1080P/3MP/5MP Video Record/View; Built-in 4pcs Array IR Led; IR Distance More than 5~10 Meters; Simple installation; 360 degree panoramic picture; Two Way Audio(Built-in Mic, Louder speaker);H.265/H.264 HD High Profile imag e decoding;Pan Rotation:355°,TiltRotation:75°;	**3.500ден**
	**2MP Camera TV 288ZD Wireless WiFi with AUTO TRACKING** Image sensor: GC1034 Video: Image sensor: 2MP/1080P Image coding standard: Smart H.264+, **Monitor image quality: 1280*720/640 * 360** private cloud WIFI Networking, AP hotspot added Extension: IR-CUT, TF Card: maximum support for 128GB TF CardWIFI: support.**Lens: 3.6mm**.	**2.300ден**
	**1080PDual CarCamera** Color: Black; Material: ABS; Display: 2 Inch IPS Screen; Camera: 1080P Front Camera + 480P Inside Camera + 480P Rear Camera; View Angle: 140° Front + 90° Inside + 90° Rear; Loop; Date Stamp: Support; Memory Card: Max. 128G(Not Included); Battery: Built-in 150mAh Lithium Battery; Current Frequency: 50/60Hz; Power: 5V, 1.5-2A;Photo Format: JPEG; File Format: MOV	**3.450ден**

Accessories

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DH-PFM906** **Integrated Mount Tester** Supports IPC, HDCVI, AHD, HDTVI, CVBS and SDI monitor video display; HDMI input and output; 12 VDC 2A and USB 5V 2A output; 7-in 1080p HD full-angle retina capacitive IPS touchscreen; TDR network cable test and cable tracker function; Optical power meter function	
	**DAHUA PFT1300 PoE Extender** Support passive PoE cascade power supply and Ethernet data exchange; Support IEEE 802.3af/at standard power supply IP Camera;	**2.500ден**

01.10.2026

	**DAHUA PFM800-4K** **1-CH Passive Video Balun**	**450ден**
	**Balun 1CH Video 4K-8MP**	**300ден**

Ethernet Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA SF1005L** **5-Port Unmanaged Ethernet Switch** Supports five 10/100 Mbps adaptive ports; Small and light, it is easy to carry and has multiple chips embedded in it; Easy to operate;	**700ден**
	**DAHUA SF1008L** **8-Port Unmanaged Ethernet Switch** Supports eight 10/100 Mbps adaptive ports; Small and light, it is easy to carry and has multiple chips embedded in it; Easy to operate;	**990ден**

Wireless Access Point

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA EAP5212-C** **AC12 Ceiling Mount Access Point** Up to 1.2 Gbps wireless speed; Supports dual concurrent wireless networks; Offers seamless roaming; MU-MIMO technology delivers a fast wireless network that can be accessed by multiple devices at the same time;	**5.450ден**

Wireless Routers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA N3** **N300 Wireless Router** The wireless speed reaches up to 300 Mbps for IEEE 802.11n, allowing smooth internet access; 1 × WAN port and 3 × LAN ports that expand network coverage; Two external antennas offer a wider signal coverage;	**1.400ден**
	**DAHUA AC12** **AC1200 Wireless Router** 1.2 Gbps Wireless Speed(300 Mbps@2.4 GHz, 867 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac standard); Beamforming for better Coverage; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2); Guest Wi-Fi;	**2.500ден**
	**DAHUA AX18** **AX1800 Wireless Router** 6th Gen Wireless Technology; 1.8 Gbps Wireless speed (574 Mbps@2.4 GHz, 1201Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3); Guest Wi-Fi; Parental Control;	**2.560ден**
	**DAHUA AX30** **AX3000 Wireless Router**	

	6th Gen Wireless Technology; 3 Gbps Wireless speed (574 Mbps@2.4 GHz, 2402 Mbps@5 GHz); Backward compatible (IEEE 802.11 b/g/n/ac/ax standard); 160 MHz channel width; Beamforming for better Coverage; OFDMA and 1024-QAM; Bi-directional MU-MIMO; WiFi protected Access(WPA/WPA2/WPA3);	**5.050ден**
	**DAHUA MAX18-3 Pack of 3** **Mesh Wireless Route** Offers wireless access and high bandwidth; 1 gigabit WAN port and 2 gigabit LAN ports; Easily switches between LAN and WAN; Supports accessing 1000 Mbps optical fiber broadband; Supports being managed through the WiLynk app	**14.990ден**

Unmanaged Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**MV-1010B** **Port: 8 POE * 100Mbps + 2 RJ45 * 100Mbps;** Power Supply Protocol: IEEE802.3AF/AT,maximum output 30W per port; Backplane Bandwidth: 2.0Gbps; Total Power: 52V 120W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN function.	**4.000ден**
	**MV-1011GB** **Port: 8 POE * 100Mbps + 2RJ45*1000Mbps +1*1000Mbps-SFP;** Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 7.6Gbps; Total Power: 52V 120W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	**7.300ден**
	**MV-16F22GB** **Port: 16 POE * 100Mbps + 2RJ45*1000Mbps +2*1000Mbps-SFP;** Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 11.2Gbps; Total Power: 52V 250W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	**12.500ден**
	**MV-24F22GB** Port: 24 POE * 100Mbps + 2RJ45*1000Mbps +2*1000Mbps-SFP; Power Supply Protocol: IEEE802.3AF/AT, maximum output of 30W per port; Backplane Bandwidth: 12.8Gbps; Total Power: 52V 320W; Power Pins: 12+, 36-; Operating Mode: Supports 250-meter long-distance transmission and one-key VLAN.	**15.700ден**
	**DAHUA CS4006-4ET2GT-36** **6-Port Cloud Managed Desktop Switch with 4-Port PoE** Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards; Meets the requirements of IEEE802.3af, IEEE802.3at power supply standards; Manages PoE power consumption and PoE power on/off.	**3.120ден**
	**DAHUA PFS4006-4ET-60** **6-Port 10/100Mbps Unmanaged Desktop Switch with 4 PoE Ports** Layer two commercial switch; Supports IEEE802.3, IEEE802.3u, IEEE802.3ab and IEEE802.3x standards; MDI/MDIX self-adaptation; RJ-45 port supports 10/100 Mbps self-adaptation, and confirms to 802.3at, and 802.3af power supply standards; Port 1 supports Hi-PoE 60W power supply; 250m PoE power supply;	**3.650ден**
	**DAHUA PFS3008-8GT** **8-Port Unmanaged Gigabit Switch** Supports eight 10/100/1000 Mbps adaptive ports; Small and light, it is easy to carry and has multiple chips embedded in it; Easy to operate; Communication Standard: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3x;	**6.800ден**

	**DAHUA SF1010LP** **10-Port Fast Ethernet Switch with 8-Port PoE** Support eight 10/100M; PoE power supply ports, and two 10/100M uplink ports; Support 802.3af and 802.3at standards; Operating Temperature: -10°C to +55°C; Support 250 m long distance PoE tansmission; Support PoE watchdog	**4.960ден**
	**DAHUA CS4010-8ET2GT-60** **10-Port Cloud Managed Desktop Gigabit Switch with 8-Port PoE** 8 × RJ-45 Gigabit PoE ports, 2 × RJ-45 Gigabit ports; 60 W total PoE budget, 802.3af/at on all PoE ports, additional Hi-PoE on orange port; h to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, 250 Meter Long Distance PoE;	**4.490ден**
	**DAHUA PFS3110-8ET-96** **8-Port PoE Switch (Unmanaged)** Layer two Hardened PoE switch; Supports PoE power management; MAC auto learning and aging, MAC address capacity is 8K; Conforms to IEEE802.3af and IEEE802.3at power supply standard; Port 1-2 supports Hi-PoE 60W power supply; Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards;	**6.945ден**
	**DAHUA S3016-16GT** **16-Port Unmanaged Gigabit Switch** 16 × RJ-45 10/100/1000 ports; The all-gigabit ports transmit data without lag; Features aggregation mode which aggregates uplink ports; Features isolation mode which isolates all the ports from each other; With its solid full metal design, the device has great heat dissipation and no fan;	**4.665ден**
	**DAHUA S3218-16ET-135** **18-Port Unmanaged Desktop Switch with 16-Port** 16 × RJ-45 10/100 Mbps (PoE) ports, 2 × RJ-45 10/100/1000 Mbps ports and 2 × SFP 1000 Mbps ports; Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt; PoE watchdog real-time monitors camera statues and automatically reboots faulty network cameras; Up to 250m transmissiondistance	**10.850ден**
	**DAHUA S3024-24GT** **24-Port Unmanaged Gigabit Switch** 24 × RJ-45 10/100/1000 ports; The all-gigabit ports transmit data without lag; Features aggregation mode which aggregates uplink ports; Features isolation mode which isolates all the ports from each other;	**6.390ден**
	**DAHUA S3226-24ET-240** **26-Port Unmanaged Switch with 24-Port PoE** Intelligent PoE; PD Alive(PoE Watchdog); Long Distance PoE Transmission; Smooth Transmission; Wide Working Temperature: –10 to 55°C (14°F to 131°F)	**17.730ден**

Managed Desktop Switch

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA CS4218-16ET-135** **18-Port Cloud Managed Desktop Switch with 16-Port PoE** Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof;	**14.680ден**
	**DAHUA DH-PFS4218-16ET-240-V3** **16-Port PoE Switch** Layer 2 management PoE switch; PoE budget: 240W; Support PoE, PoE+, Hi-PoE; 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300); 250 meters long distance PoE transmission · PoE management, PoE Setting/Event Statistics/Green PoE · Search and upgrade via ConfigTool;	**20.190ден**



	**DAHUA CS4220-16GT-135** **20-Port Cloud Managed Desktop Gigabit Switch with 16-Port PoE** Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof;	**12.895ден**
	**DAHUA CS4226-24ET-240** **26-Port Cloud Managed Desktop Switch with 24-Port PoE** Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x, IEEE802.3ab,IEEE802.3z standards; Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards; Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE; A wide operating temperature range and a full metal casing.	**17.700ден**
	**DAHUA PFS4226-24ET-360** **24-port 100 Mbps + 2-port Gigabit Managed PoE Switch** Intelligent PoE; Red port supports 90W IEEE802.3bt; Web management with friendly interface and easy operation; 250 m long distance PoE transmission; PoE watchdog;	**24.840ден**
	**DAHUA S4228-24GT-240** **28-Port Managed Desktop Gigabit Switch with 24-Port PoE** Layer 2 network management PoE switch; Supports web, and network management software based on SNMP; Network redundancy: STP/RSTP. Supports IEEE802.3af, IEEE802.3at; Port 1 and port 2 support IEEE802.3bt, and are compatible with Hi-PoE; Supports PoE watchdog; Supports 250 m long-distance transmission mode;	**26.690ден**
	**DAHUA S4228-24GT-360** **28-Port Managed Desktop Gigabit Switch with 24-Port PoE** Layer 2 network management PoE switch; Supports web, and network management software based on SNMP; Supports PoE power consumption management; Supports IEEE802.3af, IEEE802.3at; Supports PoE watchdog; Supports 250 m long-distance transmission mode.	**34.560ден**
	**DAHUA S5436-24GF8GT4XF** **36-Port L2+ Managed Gigabit Switch with 4-Port 10G SFP+** All-gigabit port design (10 gigabit uplink port); Supports STP, RSTP and ERPS; IEEE802.1Q-based VLAN configuration; Static link aggregation and static LACP; Easy to manage the device through the webpage; EMC compliant, the device is lightning proof; Desktop mount and rack mount;	**37.230ден**

Uninterruptible Power Supply (UPS)

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA PFM350-360 Uninterruptible Power Supply** **600VA/360W Line-interactive** Wide input voltage range: AC81~145V or AC140~290V, meet the requirements in different parts for electric network fluctuation; Boost and buck AVR for voltage stabilization; Off-mode charging, cold start function and full protection; Continuous power supply for preventing data loss; Compact size;	**6.200ден**
	**DAHUA PFM3350-1000 Uninterruptible Power Supply** **230V - Line-interactive 1000VA/600W** Comes with a wide voltage input range of 170–280 VAC, and easily adapts to fluctuations and various grid environments; Offers digital voltage stabilization; Fast charging in just 4 hours; Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	**5.230ден**
	**DAHUA PFM3350-1500 Uninterruptible Power Supply** **230V - Line-interactive 1500VA/900W** Comes with a wide voltage input range of 170–280 VAC, and easily adapts to fluctuations and various grid environments; Operates quietly for a serene environment; Offers digital voltage stabilization and automatically adjusts the voltage; Fast charging in just 4 hours;	**11.450ден**

	Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	
	**DAHUA PFM3350-2000 Uninterruptible Power Supply** **230V - Line-interactive 2000VA/1200W** Comes with a wide voltage input range of 170–280 VAC, and easily adapts to fluctuations and various grid environments; Operates quietly for a serene environment; Offers digital voltage stabilization and automatically adjusts the voltage; Fast charging in just 4 hours; Rapid switching of 4-8 milliseconds; Protects against overload, short circuit, overcharging, and overdischarge;	**13.170ден**

Power Supply and Adapter




МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DC12V2A Power Adapter DAHUA PFM300** Easy installation and wall mount, structural water-proof; Support -30 ℃ ~+70 ℃ wide-range temperature operation, and the full load efficiency of the power; supply can be up to 100% at these temperatures; With junction function for camera wiring or can place video balun with HDCVI/AHD/TVI/CVBS cameras;	**779ден**
	**DAHUA PFM344D-4CH - Switching Power Supply** The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	**900ден**
	**DAHUA PFM344D-8CH - Switching Power Supply** The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices; Designed with protection against overcurrent, overvoltage, and short circuits; Surge protection: common mode: ±4 kV, differential mode: ±2 Kv; Fireproof;	**1.200ден**
	**POWER SUPPLY 5A / 12V DC for CCTV Camera BIG** Input voltage 165 – 250 V; DC power 60W; Miniature size, high power density; ;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection	**650ден**
	**POWER SUPPLY 10A / 12V DC for CCTV Camera BIG** Input voltage 165 – 250 V; DC power 120W; Miniature size, high power density;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	**850ден**
	**POWER SUPPLY 15A / 12V DC for CCTV Camera BIG** Input voltage 165 – 250 V; DC power 180W;Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	**1.050ден**
	**POWER SUPPLY 20A / 12V DC for CCTV Camera BIG** Input voltage 165 – 250 V; DC power 240W; High Miniature size, high power density;Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	**1.200ден**
	**POWER SUPPLY 30A / 12V DC for CCTV Camera BIG** Input voltage 165 – 250 V; DC power 360W; Miniature size, high power density; Adjustable output voltage for single output types, 10.8 - 13.2V at 12V; Short circuit, overload and over voltage protection;	**2.000ден**
	**4C5A** 220V AC input, 3A - 5 channel, 12VDC output, input voltage 165 – 250 V	**1.600ден**

	**9C10A** 220V AC input, 5A - 9 channel, 12VDC output, input voltage 165 – 250 V	**2.200ден**
	**18CH20A** 220V AC input, 20A - 18 channel, 12VDC output, input voltage 165 – 250V	**3.100ден**
	**DC12V4A 5-ch - CCTV Distributed Power Box DAHUA PFM340-5CH** 5 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access. Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	**3.970ден**
	**DC12V5A 9-ch - CCTV Distributed Power Box DAHUA PFM341-9CH** 9 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	**4.960ден**
	**DAHUA PFM343-19CH - CCTV Distributed Power Supply Box** 19 Channel security camera power supply distribution box with individual LED output indicator and metal case by lock key to prevent unauthorized access; · Wide voltage input: AC90~264Vac, meet the requirements in different parts for electric	**9.920ден**

01.10.2026

Junction Box for CCTV Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**Plastic Flush** UNIVERSAL Junction Box for DOME CAMERA, Camera housing with bracket, PLASTIC	**120ден**
	**J-BOX01DS** UNIVERSAL Water-proof Junction Box for BULLET CAMERA OUTDORE, Camera housing with bracket, Material: Aluminum, Operating Temperature: -40ºC ~60ºC	**400ден**

	**J-BOX04PL – Bracket Plastic**	**200ден**
	**J-BOX05PL – Bracket Plastic**	**200ден**
	**J-BOX06PL – Bracket Plastic**	**250ден**
	**J-BOX07PL – Bracket Plastic**	**200ден**
	**J-BOX08PL – Dome Bracket Plastic**	**300ден**
	**DAHUA PFB204W**	**880ден**
	**Dahua PFA1320R Plastic Junction Box**	**200ден**
	**DAHUA PFA122** **Water-proof Junction Box**	**1.260ден**
	**DAHUA PFA130-E** **Water-proof Junction Box**	**800ден**
	**DAHUA PFA130-E** **Water-proof Junction Box**	**800ден**
	**DAHUA PFA13A** Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: ϕ96.8mm x 33.5mm	**600ден**
	**DAHUA PFA134** Water-proof Junction Box, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design, Product Dimension: ϕ90mm x 35mm	**560ден**
	**DAHUA PFA134-B** Water-proof Junction Box, Material: Aluminum &SECC , Junction Box ,Neat & Integrated design, Product Dimension: ϕ90mm x 35mm	**550ден**
	**DAHUA PFA135** Water-proof Junction Box, Camera housing with bracket, Material: Aluminum & SECC , Junction Box ,Neat & Integrated design,	**640ден**
	**DAHUA PFA136** Water-proof Junction Box, Material: Aluminum, Product Dimension: ϕ110mm x 33.5mm Pipe Thread: Operating Temperature: -40ºC ~60ºC	**585ден**
	**DAHUA PFA137** **Junction Box** Material: aluminum	**535ден**
	**DAHUA PFA150** **Pole Mount Bracket**	**1.550ден**

01.10.2026

	Camera Bracket 110*250mm	1.999ден
	Camera Bracket 60cm	1.500ден
	J-BOX100B 200mm*155mm*80mm	600ден
	J-BOX800B 260mm*230mm*80mm	800ден
	J-BOX800C 280mm*230mm*80mm	900ден

01.10.2026

Face Recognition Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA ASI3213A-W** **Face Recognition Access Controller** 4.3 inch glass touch screen with a resolution of 480 × 272; 2-MP wide-angle dual-lens camera with IR illumination and DWDR; Multiple unlock methods including face, card and password. You can also combine them to create your own personal unlock methods; Supports mask detection; Supports visitor QR code with DSS Pro Platform; Recognizes faces 0.3 m to 1.5 m away (0.98 ft-4.92 ft); as a face recognition accuracy rate of 99.9%;	**11.550ден**

Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	***DAHUA ASI1201E-D*** **Water-proof RFID Standalone** Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	**5.000ден**
	***DAHUA ASI1201E – Mifare*** **Water-proof RFID Standalone** Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC;Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	**5.000ден**
	***DAHUA ASI1201A*** ***Standalone Reader*** Touch keyboard and LCD display; Support 30,000 valid cards & 150,000 records; Support multiple cards(default IC card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;	**5.500ден**
	***DAHUA ASI1201A-D*** ***Standalone Reader*** Touch keyboard and LCD display; Support 30,000 valid cards & 150,000 records; Support multiple cards(default ID card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;	**5.500ден**
	**DAHUA ASI2212J – Mifare** **Dahua Single Door IC Card, Password, Fingerprint Access Standalone** 2.4" TFT display screen with a resolution of 240 × 320. · Audio prompts. · Supports 5,000 users, 5,000 cards, 5,000 passwords, 3,000 finger prints, and 100,000 records. · The security module expansion is supported to enhance security and protect against the device being opened during a power failure. · Fingerprint/card/remote/password	**7.500ден**
	**DAHUA ASI2212J-D** **Dahua Single Door ID Card, Password, Fingerprint Access Standalone** 2.4" TFT display screen with a resolution of 240 × 320. · Audio prompts. · Supports 5,000 users, 5,000 cards, 5,000 passwords, 3,000 finger prints, and 100,000 records. · The security module expansion is supported to enhance security and protect against the device being opened during a power failure. · Fingerprint/card/remote/password	**7.500ден**

	**DAHUA ASI1212M-DW** **Dahua Card Swiping,Password,Fingerprint Access Standalone** The front part of the case is made of zinc alloy and the back part is made of plastic. Supports 10,000 users, 10,000 passwords, 10,000 cards, 3,000 fingerprints and 100,000 records; Mechanical keypad with backlighting; Supports RS-485 communication and Wiegand communication; Buzzer and indicator light; Supports doorbell; Supports security extension modules for access control, preventing doors from being forcefully opened;	**8.090ден**
	**DAHUA ASI1212M-W - Mifare** **Dahua Card Swiping,Password,Fingerprint Access Standalone** The front part of the case is made of zinc alloy and the back part is made of plastic. Supports 10,000 users, 10,000 passwords, 10,000 cards, 3,000 fingerprints and 100,000 records; Mechanical keypad with backlighting; Supports RS-485 communication and Wiegand communication; Buzzer and indicator light; Supports doorbell; Supports security extension modules for access control, preventing doors from being forcefully opened;	**8.090ден**

Access Control

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA ASA1222G-D Time & Attendance Terminal** Supports Mifare card/ID card reading distance 1 cm-3 cm, card swiping response time; Fingerprint verification response time ≤0.5 s, fingerprint recognition time≤1.5 s; Operating temperature: 0°C to +55°C , operating humidity: ≤93%; Supports three attendance modes: fixed, manual/auto and forced;	**8.100ден**

Access Control – Slave

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	***DAHUA ASR1101A-D*** **RFID Reader** Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) · 125KHz(EM-ID); Red and Green LEDs; Sensitive touch keypad with blue backlight; Watch dog function ensure device free from halting; Beep Buzzer and LED indicator;Surface mounted installation	**1.950ден**
	**DAHUA ASR1200E – Mifare** **Water-proof RFID Reader** Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	**1.200ден**
	**DAHUA ASR1200E-D** **Water-proof RFID Reader** Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	**1.200ден**
	**DAHUA ASR1201D-D** **Slim Water-proof RFID Reader** Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) 125KHz(EM-ID); Red and Blue LEDs; Watch dog function ensure device free from halting; Water-proof(Outdoor use); Surface/Flush mounted installation	**1.750ден**


Controllers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DEE1010B** **Access Control Extension Module** Decent appearance; Easy connection; Access control function extension	**2.700ден**

	**DAHUA ASC2104B-T** **Four Door Slave Access Control Module** Support 20,000 valid cards & 30,000 records; Support multiple cards; Support card, password, fingerprint and combination; Only work with ASC2204-H with CAN bus;Wiegand or RS-485 interface to readers; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	**6.200ден**

IPC Villa Door Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA VTO1301R-W** **Wi-Fi Villa Door Station** Ultra slim design; PC and ABS material make it ideal for indoor and outdoor use. Offers two–way video call with indoor monitors; Video call through app; IR illumination and auto WDR; Wi-Fi connection; IP65 rated; H.264 and H.265.	**3.500ден**
	**DAHUA VTO2111D-P-S2** **IP Villa Door Station** High definition camera; WDR; Operating temperature -30°C–60°C;IP65;Supports auto IR illumination and D/N; Card/app remote/indoor monitor unlock; Supports two-way voice call; 10,000 cards; Tamper Alarm; Control two locks	**9.870ден**
	**DAHUA VTO2211G-WP** **IP Villa Wi-Fi Door Station** Tamper alarm; Standard PoE; Control two locks; Supports wireless network; Card unlock, app unlock, and indoor monitor unlock; Two-way audio and voice call through app;Card capacity: 10,000; Thin lightweight design;	**10.490ден**
	**VTO6222E-P** **2-wire IP Apartment Door Station** Highly durable and elegant, it is made of aluminum panel, and has a mechanical keypad. 2MP HD camera. Supports 5,000 users and 10,000 cards. Supports multiple unlock methods including password, IC card, and unlocks remotely. Provides 12 VDC, 600 mA power. IP65 rated. IK08 rated. Standard PoE power supply.	**17.780ден**
	**DAHUA VTO6521F** **Apartment Door Station** 4.3 inch IPS display; screen resolution 800×480; 2MP CMOS; true WDR; Aluminum anode surface; metal button; IP65, IK07; Operating temperature: -30°C to +60°C; Auto light illumination reduces light pollution; Multiple unlock modes: Password unlock, IC card unlock, and remote unlock; Support 20,000 users and 10,000 cards; Support full duplex; management platform, and voice call through APP; Support SIP server; Support duress alarm, tamper alarm, and door sensor timeout alarm;	**19.990ден**
	**DAHUA VTO6631QB-WP** **IP & Wi-Fi Villa Door Station** Ultra-thin frame design; 5-inch IPS screen with a high resolution of 720 × 1280; MP wide angle camera with H: 119°, V: 66° and D: 142° FOV; Unlocks through IC and ID cards, Bluetooth cards, face and password; Recognizes faces 0.3 to 2 m away (0.98 to 6.56 ft), and has a face recognition accuracy rate of 99.9% and a one to many identification time of 0.2 sec per face.	**19.300ден**
	**DAHUA VTO3311Q-WP** **Wi-Fi Villa Door Station** Full metal casing design.Customizable Number of Buttons.Wi-Fi connection. 1/2.8" 2-MP HD CMOS camera.IR illumination and auto WDR.Supports two locks.Voice call and unlocking ;through app.IK08 and IP65 rated.H.264 and H.265.Unlock with IC card.PoE power supply.Included rain cover.	**12.500ден**

	**DAHUA VTH1550CH** **IP Indoor Monitor** 7" TFT Capacitive touch screen; IPC surveillance; Alarm integration Micro SD card optional, max 32GB; Record & Snapshot(SD card needed)	**5.740ден**
	**DAHUA VTH2611L-WP** **Dahua Wi-Fi Indoor Monitor** 4.3" TFT capacitive touchscreen; Unlock the door; Set DND period; IPC surveillance; 4-channel alarm input and 1-channel alarm output; Supports standard PoE; Ethernet and Wi-Fi.	**5.500ден**
	**DAHUA VTH2621GW-WP** **IP Indoor Monitor** 7" TFT capacitive touch screen, 1024 × 600 · 6-channel alarm input and 1-channel alarm output; **Wi-Fi**; Standard PoE · Door station and IPC monitor ; H.265 and H.264 video decoding; High performance & cost-effective	**6.800ден**
	**DAHUA VTH2621G-WP** **IP & Wi-Fi Indoor Monitor** 7" TFT capacitive touch screen, 1024 × 600; 6-channel alarm input and 1-channel alarm output; Wi-Fi; Standard PoE; Door station and IPC monitor; H.265 and H.264 video decoding; High performance & cost-effective	**6.800ден**
	**VTH5421EW-H Wi-Fi** **Digital Indoor Monitor with Handset** 7 inch LCD, 1024 (H)×600(V); 6 alarm input ports; 1 alarm output port; 1 12V DC power output port provides power for peripheral alarm devices and sensors; 16kbps audio stream; You can answer calls hands free;	**9.300ден**
	**DAHUA VTH5321GW-W** **Android 7-inch digital indoor monitor** Android 8.1;More User-Friendly UI;Ethernet and Wi-Fi;7" TFT Capacitive touch Screen,1024×600;Quick configuration for villa system;	**10.500ден**

01.10.2026

IPC Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA KTP03 Video Intercom KIT** Megapixel image sensor · Supports IR illumination and night vision. · Two-way audio and voice call through app. · Can be managed through the management platform; supports voice call between App and the door station. · Card unlock, unlock on the indoor monitor, and remote unlock through the App. · Supports IP65	**16.950ден**

IPC 2-wire Hybrid Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	***DAHUA* KTX01 Video Intercom KIT** 2-wire Hybrid Villa Door Station; Aluminum alloy front panel; Auto IR illumination; Video messages can be left for unanswered calls. (SD card is required for VTH); Features nameplate and DWDR; Supports local lock and second lock; Offers anti-tampering alarm; IP65 and IK07 rated;	**19.500ден**

Analogue Video Intercom KIT

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA KTA02** **Video Intercom Kit** 7" TFT screen; Video intercom function: Unlock, voice call, video call, volume adjustment;System Capacity: 2 door stations + 3 indoor monitors;Multiple bell sound; Supports digital wide dynamic range (DWDR)	**7.390ден**
	**DHI-KTA04** **Video Intercom Kit** Video intercom function: Unlock, voice call, video call, volume adjustment and doorway monitoring · Multiple bell sounds · Support digital wide dynamic range (DWDR); Display 4.3" TFT	**6.490ден**

Wired Apartment Outdoor Station

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DHI-VTO1210C-X** IP&Analog Apartment Outdoor Station; 1.3MP CMOS camera, H:75° 3" STN LCD screen, phonebook; Stainless steel panel, IP54,IK07 Night vision & Approaching induction; Video & Audio messaging Surface & Flush mounted	**16.535ден**
	**DHI-VTH1200DS** 4.3" Analog Indoor Monitor; 4.3" TFT LCD screen Color video & audio intercom; Alarm intergration Sufrace & Flush mounted	**2.790ден**
	**DHI-VTH2020A** 7" Analog Indoor Monitor; 7" TFT LCD screen Color video & audio intercom; Alarm intergration Surface mounted	**4.000ден**
	**DHI-VTNA1040B** 4ch Analog Distributor;4ch distributor 30 cascading;Used in Analog apartment systemDC24V, Max 20W	**2.430ден**
	**VTNS1060A** Network power supply for IP System; Decent appearance Protocol network power supply switch; Connect max 6 indoor monitors with the Cat 5e cable,	**1.200ден**
	**ADS-65LSI-19-1** DC 24V 2.5A Power Supply Input: 100-240V ~50/60Hz Required for the VTNA 1040B Switch	**2.050ден**

01.10.2026


MAKSIPRINT
DISTRIBUTION & SECURITY

dahua TECHNOLOGY





Dahua Network Cable

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**DAHUA PFM920I-5EUN – 305m UTP CAT5E Cable** 305m (1000 ft)/carton U/UTP sCAT5E, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor material; Customized PVC outer sheath ; CE CPR Eca flame retardant class certified;	**28ден**
	**DAHUA PFM923I-6UN-C – 305m UTP CAT6 Cable** 305m (1,000.66 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor; Customized LSZH outer sheath; CE CPR Eca flame retardant class certified;	**40ден**
	**DAHUA PFM923I-FN-CD** **305m F/UTP CAT6 Network Cable (White,LSZH,CPR Dca)** 305 m (1000 ft)/carton F/UTP CAT6, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor material; Customized LSZH outer sheath; CE CPR Dca flame retardant class certified; 10-year warranty;	**55ден**
	**DAHUA PFM923-6AU-CD** **305m U/UTP CAT6A Network Cable (White,LSZH,CPR Dca)** 305 m (1000 ft)/roll U/UTP CAT6A, power over Ethernet, compatible with one cable; High-purity oxygen-free copper conductor material; Customized LSZH outer sheath; CE CPR Dca flame retardant class certified; 10-year warranty;	**60ден**

Cable

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	**RG6 Coaxial** Brainding 80*0.12 +Bonded AL-foil+PVC 100m. White Color 100m/roll,	**20ден**
	**RG59 Coaxial CCS** Brainding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	**22ден**
	**RG59 Coaxial 100% COPPER** Brainding 112 +Bonded AL-foil+PVC 100/200m Black COLOR	**30ден**
	**RG59+2x0.75 COMBO** Brainding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	**35ден**
	**RG59+2x0.75 COMBO so SAJLA** Brainding 112 +Bonded AL-foil+PVC + 2x0.75mm power. Black and White COLOR 100M/Roll ; 200M/Roll ; 200M/Drum ; 300M/Drum	**ден**

01.10.2026

	**RG59+2x0.50 COMBO COPPER** Brainding 112 +Bonded AL-foil+PVC + 2x0.50mm power COPPER. White Color, 100M/Roll ; 200M/Roll ; 200M/Roll ; 300M/Drum ; 300M/Drum	**ден**
	**FTP Cat5E - 24AWG** Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m BoxGrey Color	**20ден**
	**FTP Cat5E - 24AWG so SAJLA** Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA **Grey Color**	**30ден**
	**FTP Cat5E - 24AWG so SAJLA COPPER** Network Cable , with aluminium foil , and transparent PET film, Conductor 0.51mm - 305m Box SO SAJLA **Grey Color**	**40ден**
	**FTP Cat5E 24AWG - 100% FULL COOPER** CU Network Cable CU (100% Copper), with aluminium foil , and transparent PET film , Conductor 0.51mm , Pass Fluke test on 100M - 305m Box Grey Color	**35ден**
	**FTP Cat6E 23AWG** Network Cable , with aluminium foil , and transparent PET film, Conductor 0.57mm - 305m Box**Grey Color**	**30ден**
	**FTP Cat6E 23AWG - 100% FULL COOPER** Network Cable CU (100% Copper) , with aluminium foil , and transparent PET film , Conductor 0.57mm - 305m Box **Grey Color** 18.6	**40ден**
	**FTP Cat 6A S/FTP LSOH** ISDN; 4/6 Mbps Token Ring (IEEE 802.5); 100 Mbps CDDI; 250 Mbps ATM Power over Ethernet (PoE); 10 BASE-T Ethernet (IEEE 802.3j); 100 BASE-VG AnyLAN (IEEE 802.12); 1000 BASE-T 1 Gigabit Ethernet (IEEE 802.3 ab); 10 GBASE-T 10 Gigabit Ethernet (IEEE 802.3 an);	**65ден**
	**FTP Cat 6A F/FTP LSOH** ISDN; 4/6 Mbps Token Ring (IEEE 802.5); 100 Mbps CDDI; 250 Mbps ATM Power over Ethernet (PoE); 10 BASE-T Ethernet (IEEE 802.3j); 100 BASE-VG AnyLAN (IEEE 802.12); 1000 BASE-T 1 Gigabit Ethernet (IEEE 802.3 ab); 10 GBASE-T 10 Gigabit Ethernet (IEEE 802.3 an);	**50ден**
	**ALARM CABLE** 6 x 0.22, shild 100m , EXTRA	**25ден**
	**ALARM CABLE COPPER** 6 x 0.22, shild 100m , COPPER EXTRA	**35ден**
	**Signal Cable – Power Cable** LITCY 3*0,5 MM	**42ден**

Цените се крајни и истите важат за крајни корисници.

Цените се со пресметан ДДВ.

Гаранција на производите е 12 – 24 месеци.

МАКСИПРИНТ го задржува правото на промена на цените без претходна најава.